

Bid Number AN-2023-24 # 01

Bid Title: Invitation to bid on Rescue Pumper at Andover Fire Department

Status: Open

Category: Fire Department

Description: **Rescue Pumper for Andover Fire Department 11 School Rd., Andover Ct 06232**

Sealed Bids for a *Rescue Pumper* for the Andover Fire Department 11 School Rd must be received by the Town Managers office, 17 School Rd Andover CT 06232 **by Noon local time on 7/3/2023**. One printed copy and one electronic copy on a USB flash drive shall be provided. At this time, they will be publicly opened and read.

Any questions about this bid shall be mailed to Shawn Covell scovell22@comcast.net

Posted 6/1/2023

Bid Requirements:

Bid Bond

No bid bond is required for this RFP.

Performance Bond

As the Town of Andover plans for finance this apparatus, a 100% performance bond is a requirement.

Financing

The Town of Andover is requiring financing proposals for a 10 year financing period. Please provide a proposal for financing in your response.

SERVICE CENTER

The dealership supplying the apparatus must maintain a full service, repair and warranty center. The service center must be owned and operated by the dealership, which must be an established business entity. Third party service or repair services shall not be allowed. Furthermore, the dealership's service center and office must be located in a commercial business district, neither the office or service center may be located in a residential district, No Exception. **This is a complicated apparatus and the only one the Town of Andover owns of this type, these requirements have been set to insure minimal out of service time. These requirements are set forth to assure competent 24-hr. service can be provided without interruption. (THERE SHALL BE NO EXCEPTIONS TO THE SERVICE REQUIREMENTS)**

THE LOCAL DEALERSHIP SHALL HAVE THE FOLLOWING WITHOUT EXCEPTION:

- 1) Full Fire Apparatus CAD system for fire apparatus.
- 2) Minimum of Twenty (20) years of continuous ownership and management.
- 3) Certified in-house pump mechanics for the following pump:
Hale
Waterous
- 4) International air terminal within five (5) miles for receipt of air shipments of service parts.

5) Certified in-house mechanics the following areas:

EVT – Master Mechanic
EVT – Fire pumps and accessories
EVT – Aerial fire apparatus
REYCO – Spring maintenance and repair/replacement
CLASS 1 – Multiplexed electrical systems
GENERATOR - Harrison
AIR COMPRESSOR SERVICE
American Bristol
Mako
DETROIT DIESEL
Engine tune up
DDEC III & IV

6) Certified warranty center for the chassis being supplied. (Must supply documentation from chassis builder)

7) Four (4), Mobile service unit –fully stocked with tools & parts. (Must supply photographic proof)

8) 15,000sqft of heated indoor storage/repair area. (Must supply aerial photographic proof, no exception)

9) MIG & TIG welder and cutting torches.

10) PPG certified service center.

11) Digital camera for repair photographs.

12) Capability of servicing several large fire apparatuses (aerials, tankers and pumpers) simultaneously indoors with cabs fully tilted and aerial devices removed from their beds.

13) Plasma cutter.

14) Factory certified in-house aerial mechanics with **CERTIFICATION FROM OEM OF AERIAL DEVICE.**

15) 24-hour emergency onsite service at our fire house.

16) On site service, preventative maintenance and warranty repairs. The apparatus shall not be driven back and forth to the apparatus dealership for warranty & service work.

17) A Laptop computer & Pro-Link 9000 diesel engine reader and analytical device. An onsite print-out device with the following cartridges:

DDEC motors

ATEC application

MERITOR ABS braking system

CUMMINS motors

18) Harrison generator warranty/ service center.

19) Vogel lubrication refill pumps – in service center and on mobile service units.

20) Hydraulic hose coupling system with fittings and hose in house.

21) V-Mux Multiplexed USB downloader.

22) Metal Shear capable of cutting a 12' long piece of metal. (Must supply photographic proof)

23) Service center must have the ability to lift a minimum of 120,000# and support three (3) axels. (Must supply photographic proof)

24) Synthetic grease system.

25) Robinair 34788-NP A/C recovery and recharge; fully automatic system.

26) Fifty-eight foot Cross/Down State Of The Art future cure paint booth.

The dealership shall have a factory authorized service center within 50 miles of the Andover FD.

**THERE SHALL BE NO EXCEPTIONS TO THE SERVICE CENTER REQUIREMENTS
NEW DEALER LICENSE**

All bidders shall supply copy with the bid of their DMV license to sell new vehicles for their state of incorporation. Used dealer, general repairer or limited repairer licenses ARE NOT ACCEPTABLE. The **Andover** Fire Department is buying a new vehicle and requires that any dealer selling the apparatus be a licensed and bonded New Vehicle Dealer. The department

requires this license so that Lemon Law for new vehicles can be enforced. Furthermore, the department wishes to avoid split responsibility with warranty and service repairs on the vehicle and requires that any firm supplying the new apparatus have a proper license per CT State Statutes to repair motor vehicles. The department requires that the firm selling the apparatus be responsible for all service and warranty repairs for the vehicle. Third party service centers are not acceptable.

Please input your dealer number here so the **Andover** Fire Department can do a quick check in the DMV database _____.

Signature of person attesting to the above statement _____.

Typed name of person signing this document _____.

MOBILE SERVICE

It is the intent of the **Andover** Fire Department to inspect each bidder's service center, personnel and mobile service units. Service of this vehicle is of the utmost importance to the purchaser. It is completely **unacceptable** for any bidder not to have mobile service units, in house personnel or a service center. Third party service is **NOT ACCEPTABLE, NO EXCEPTION.**

To insure that each bidder has in-house mobile service units and onsite service personnel, the **Andover** Fire Department will conduct the following inspection:

Each bidder shall bring their mobile service units to our firehouse for inspection.

The apparatus must be brought to our firehouse by a fulltime mechanic employed by the local dealership supplying the apparatus.

The mobile service unit shall bring its registration or title showing the name of apparatus dealership as the owner.

*In addition, the personnel attending shall bring a copy of the local dealerships workmen's compensation and garage liability policies in **THEIR** name for our inspection.*

REFERENCE LIST

All bidders shall supply a list of surrounding cities in which their pumpers are located. No bids shall be accepted from any contractor who cannot show they have done at least 100 similar type units. **(WITHIN New England NO EXCEPTIONS)**

DELIVERY

The apparatus shall be driven from the final stage manufacturer to the **Andover** Fire Department in order to provide a "test run" of the completed apparatus. To ensure that the intended "test run" is accomplished, this distance shall not be less than 1,500 miles. **(NO EXCEPTIONS)**

Insurance

The Dealer and manufacturer shall provide evidence of insurance coverage .

Delivery Time

All respondents shall state their delivery time in days.

Exceptions to Specifications

No response shall be accepted that takes total exception to these specifications. The Andover FD understands that different manufacturers use components that may be of comparable quality. All exceptions to these specifications shall be listed on a separate sheet, referencing the specific section that is being excepted.

The Andover FD reserves the right to select the response that they deem to be in the best interest of the Andover FD and the Town of Andover, and also reserves the right to reject any and all proposals that do not meet the best interest of the Andover FD.

INTENT OF SPECIFICATIONS

It shall be the intent of these specifications to provide a complete apparatus equipped as hereinafter and as specified. With a view to obtaining the best results and the most acceptable

apparatus for service in the Department, these specifications cover only the general requirements as to the type of construction and tests to which the apparatus must conform, together with certain details as to finish, equipment and appliances with which the successful bidder shall conform. Minor details of construction and materials where not otherwise specified are left to the discretion of the contractor, who shall be solely responsible for the design and construction for all features. The manufacturer shall provide loose equipment only when specified by the customer. The (NFPA) 1901, Standard for Automotive Fire Apparatus, unless otherwise specified as requested by the customer in these specifications, shall prevail.

The apparatus must meet all NFPA, DOT, ICC, AE, SAE, UL, TRA, FMVSS and local state Motor Vehicle Requirements.

It is required that the apparatus be manufactured to current NFPA edition standards, all NFPA equipment

Bids shall only be considered from companies that have an established reputation in the field of fire apparatus construction that have been in business and construction for a minimum of twenty-five (25) years.

The bidder of the apparatus herein specified; shall be wholly owned (100%) and managed by a Company, Corporation, and/or Parent Company that is wholly based, and permanently resides in the United States of America.

The Company, Corporation, and/or Parent Company and all assets belonging to such; shall be wholly owned and managed (100%) by the entities specified above.

The bid shall be accompanied by a set of "Contractor's Specifications" consisting of a detailed description of the apparatus being furnished under this contract which conform.

Computer runoff sheets are not acceptable as "Contractor's Specifications"..

These specifications shall indicate size, type, model and make of all component parts and equipment.

QUALITY AND WORKMANSHIP

The design of the Apparatus shall embody the latest approved automotive engineering practices.

The workmanship must be of the highest quality in its respective field. Special consideration will be given to the following points: Accessibility of the various units, which require periodic maintenance, ease of operation (including both pumping and driving) and symmetrical proportions.

Construction shall be rugged and ample safety factors shall be provided to carry loads as specified and to meet both on and off road requirements and to speed conditions as set forth under "Performance tests and requirements".

Welding shall be employed in the assembly of the apparatus in a manner that will not prevent the ready removal of any component part for service or repair, with apparatus bodies of bolt together design not being acceptable.

All steel welding shall follow American Welding Society requirements for AWS D1.1:2012 Structural Welding Code for welding steel structural assemblies. All aluminum welding shall follow American Welding Society requirements for AWS D1.2/D1.2M:2003 Structural Welding Code for any type of structure made from aluminum structural alloys. All sheet metal welding shall follow American Welding Society AWS D9.1M/D9.1:2006 Structural Welding code for Arc/Braze requirements of non-structural materials. All pressure pipe welding shall follow American Society of Mechanical Engineers ASME IX/ ASME B31:2010 requirements to the qualification of procedures in welding and brazing, in accordance with the ASME Boiler and Pressure Vessel Code and the ASME B31 Code for Pressure Piping. Flux core arc welding to use alloy rods, type 7000, American Welding Society AWS standards A5.20-E70T1

PERFORMANCE TESTS AND REQUIREMENTS

A road test shall be conducted with the apparatus fully loaded to its estimated in-service weight and shall be capable of the following performance while on dry paved roads that are in good condition and for a continuous run of ten (10) miles or more, during which time the

apparatus shall show no loss of power or overheating. The transmission drive shaft or shafts

and rear axles shall run quietly and be free from abnormal vibration or noise throughout the operating range of the apparatus. The successful bidder shall furnish a Weight Certificate showing weights on front axle, rear axles and total weight for the completed apparatus at time of delivery.

A. The apparatus shall be capable of accelerating to 35 MPH (55 km/hr) from a standing start within 25 seconds on a level concrete highway without exceeding the maximum governed RPM of the engine.

B. The apparatus, fully loaded, shall be capable of obtaining a minimum top speed of 50 MPH (80 km/hr) on a level dry concrete highway with the engine not exceeding its governed RPM (fully loaded).

C. The service brakes shall be capable of stopping a fully loaded vehicle in 35ft (10.7 m) at 20 mph (32.2 km/hr) on a level concrete highway. The air brake system shall conform to Federal Motor Vehicle Safety Standards (FMVSS) 121.

D. The apparatus, when fully loaded, shall have not less than 25 percent or more than 50 percent of the weight on the front axle, and not less than 50 percent nor more than 75 percent on the rear axle.

E. From a steady pace of 15 mph, the vehicle will accelerate to a true speed of 35 mph within 15 seconds. This will be accomplished without moving gear selector.

F. The apparatus will be able to maintain a speed of at least 20 mph on any grade up to and including 6 percent.

G. The contractor shall have the Underwriter's Laboratories, LLC conduct the tests of the apparatus as in accordance with standard practices required by the Underwriter Laboratories, LLC (Guide for the Certification of Fire Department Pumper latest edition). A copy of all tests shall accompany the Apparatus.

(For apparatus sold within Canadian ULC S515 latest revision shall prevail).

H. The contractor shall furnish copies of the Pump Manufacturer's Certification of hydrostatic test, the Engine Manufacturer current certified brake horsepower curve, and the Manufacturer's record of pumper construction details when delivered.

I. All fluid levels and applicable pressures will be brought to proper levels and noted prior to final delivery/

INFORMATION REQUIRED

The manufacturer shall supply at time of delivery, a complete operation and maintenance manual covering the completed apparatus as delivered.

A Fire Apparatus Safety Guide published by Fire Apparatus Manufacturer's Association shall be provided with the apparatus upon delivery. This manual includes essential safety information for fire fighters, fire chiefs, apparatus mechanics, and fire department safety officers. The guide is applicable to municipal, wildland, and airport firefighting apparatus manufactured on either custom or commercial chassis.

A permanent plate shall be mounted in the driver's compartment to specify the quantity and type of the following fluids used in the vehicle: Engine oil, engine coolant, and chassis transmission fluid, pump transmission lubrication fluid, pump primer fluid (if used) and drive axle lubrication fluid. The manufacture shall supply the final certification of GVWR and GAWR on a nameplate affixed to the vehicle.

A permanent plate in the driver's compartment shall be installed, specifying the seating capacity of the enclosed cab.

Signs that state "OCCUPANTS MUST BE SEATED AND BELTED WHEN APPARATUS IS IN MOTION" shall be provided and will be visible from each seated position. An accident prevention sign shall be located at the rear step area of the apparatus. It shall warn all personnel that standing on the step while apparatus is in motion shall be prohibited.

A nameplate indicating the chassis transmission shift selector position to be used when pumping shall be provided in the driving compartment and located so that it can be easily

read from the driver's position.

LIABILITY

The bidder, if their bid is accepted, shall defend any and all suits and assume all liability for the use of any patented device or article forming part of the apparatus or any appliance provided under the contract.

GENERAL CONSTRUCTION

The apparatus shall be designed with due consideration to distribution of load between the front and rear axles, so that all specified equipment, including filled water tank, a full complement of personnel and fire hose will be carried without injury to the apparatus. Weight balance and distribution shall be in accordance with the recommendations of the (NFPA) 1901, Standard for Automotive Fire Apparatus, documentation.

The apparatus shall be designed so that all recommended daily maintenance checks can be performed easily by the operator without the need for hand tools. Apparatus components that interfere with repair or removal of other major components must be attached with fasteners (cap, screws, nuts, etc.) so that the components can be removed and installed with normal hand tools. These components must not be welded or otherwise permanently secured into place.

The GAWR and GVWR of the chassis shall be adequate to carry the fully equipped apparatus including all tanks filled, the specified hose load, unequipped personnel weight, ground ladders and a miscellaneous equipment allowance per NFPA criteria. It shall be the responsibility of the purchaser to provide the contractor with the weight of equipment to be carried if it is in excess of the allowance as set forth by NFPA.

The unequipped personnel weight shall be calculated at 250 lbs. per person times the maximum number of persons to ride on the apparatus.

The height of the fully loaded vehicle's center of gravity shall not exceed the chassis manufacturer's maximum limit.

The front to rear weight distribution of the fully loaded vehicle shall be within the limits set by the chassis manufacturer. The front axle loads shall not be less than the minimum axle loads specified by the chassis manufacturer, under full loads and all other loading conditions. The difference in weight on the end of each axle, from side to side, when the vehicle is fully loaded and equipped shall not exceed 7 percent.

The apparatus shall be so designed that the various parts are readily accessible for lubrication, inspection, adjustment and repair.

Where special tools manufactured or designed by the contractor and are required to provide routine service on any component of the apparatus built or supplied by the contractor, such tools shall be provided with the apparatus,

SINGLE SOURCE MANUFACTURER

Bids shall only be accepted from a single source apparatus manufacturer.

The definition of single source manufacturer is a company that designs and manufactures their products utilizing an approach that includes complete product integration, including the apparatus chassis, cab, and body modules being constructed, assembled, and tested on company premises only.

Warranties qualified to the chassis and body design construction (excluding vender component warranties such as engine, axles, transmission, and pumps, etc.) will be from a single source manufacturer and not separated between manufacturers (i.e., body and chassis). The bidder shall provide evidence of maintaining compliance to this requirement.

FINITE ELEMENT ANALYSIS AND TESTING

Finite Element Analysis (FEA) shall be provided by the manufacturer.

Prototype bodies have been subjected to rigorous testing over varied terrains simulating different environmental conditions.

The purpose of such complex engineering methods of analysis shall be to ensure the

longevity of the design by analyzing stress levels throughout the body and incorporating the structural supports wherever necessary.

There shall have been a minimum of three (3) different load cases (per DOT, FHWA, and TTMA recommended practice) applied and analyzed to properly display the different areas and levels of stresses that will be present under the various operating conditions of the apparatus.

In addition to the FEA analysis, the core product design shall be strain gauged instrumental to ensure validation of FEA results and “Real World” drive/apparatus driving conditions.

Analysis shall also have been conducted on the mounting system for the apparatus body and pump house.

SUPPLIED INFORMATION & EXTRAS

The apparatus manufacturer shall supply two (2) hard copies of apparatus manuals with all manufactured apparatus.

The manuals shall include, but not be limited to: all component warranties, users' manuals and information for supplied products, apparatus engineering information including drawings and build prints, and whatever other pertinent information the manufacturer can supply to its customer regarding the said apparatus.

Included in the delivery of the unit, the manufacturer shall also include spare hardware and extra fasteners, paint for touch-up, information regarding washing and care procedures, as well as other recommendations for care and maintenance of the general apparatus.

The manufacturer shall also supply a manufacturer's record of apparatus construction details, including the following information:

- Owner name and address
- Apparatus manufacturer, model, and serial number
- Chassis make, model, and serial number
- GAWR of front and rear axles
- Front tire size and total rated capacity in kilograms
- Rear tire size and total rated capacity in kilograms
- Chassis weight distribution in kilograms with water (if applicable) and manufacturer mounted equipment (front and rear)
- Engine make, model, serial number, rated horsepower, related speed and no load governed speed
- Type of fuel and fuel tank capacity
- Electrical system voltage and alternator output in amps
- Battery make and model, capacity in CCA
- Paint numbers
- Weight documents from a certified scale showing actual loading on the front axle, rear axle(s), and overall vehicle (with the water tank full (if applicable) but without personnel, equipment, and hose)
- Written load analysis and results of the electrical system performance tests
- Transmission make, model, and type
- Pump to drive through the transmission (yes or no)
- Engine to pump gear ratio and transmission gear ratio used
- Pump make and model, rated capacity in gallons per minute, serial number, and number of stages
- Pump manufacturer's certification of suction capability
- Pump manufacturer's certification of hydrostatic test
- Pump manufacturer's certification of inspection and test for the fire pump
- Copy of the apparatus manufacturer's approval for stationary pumping applications
- Pump transmission make, model and serial number
- Priming device type
- Type of pump pressure control system
- The engine manufacturer's certified brake horsepower curve for the engine furnished, showing the maximum no load governed speed
- Certification of the water tank capacity

ELECTRICAL SCHEMATICS

The apparatus manufacturer shall supply one (1) set(s) as-built wiring schematics, to include all line voltage schematics with each apparatus.

WARNING AND INFORMATION LABELS

All warning and informational labels (non-vendor specific) shall be provided in compliance with (NFPA) 1901, Standard for Automotive Fire Apparatus, and installed in the appropriate locations to alert the operator of potential hazards and operating instructions.

ON-LINE CUSTOMER INTERACTION

The manufacture shall provide the capability for online access through the manufacture's website. The customer shall be able to view digital photos of their apparatus in the specified phases of construction. The following phases will be captured and displayed on the manufacture's website:

1. Chassis when available at manufacturing facility
2. Body – Prior to Paint
3. Body – Painted
4. Pump and Plumbing
5. Assembly – 80% Complete

GENERAL WARRANTY

The manufacturer shall provide a two (2) year warranty from the date of delivery. In the case of a commercial chassis being used, the warranty on the chassis, engine, transmission, tires, storage batteries, generators, electrical lamps and other devices subject to deterioration is limited to the warranty of the manufacturer thereof and adjustments for the same are to be made directly with the manufacturer by the customer.

PLUMBING WARRANTY

A Stainless Steel Plumbing/Piping warranty shall be provided by the apparatus manufacturer for products of its manufacture to be free from defects in material and workmanship, under normal use and service, for a period of ten (10) years from the date of delivery.

THIRD PARTY PUMP CERTIFICATION AND TESTING

The apparatus upon completion will be tested and certified by an independent third party testing company. The certification tests will follow the guide lines outlined in (NFPA) 1901, Standard for Automotive Fire Apparatus.

There shall be multiple tests performed by the contractor and the third party testing company when the apparatus has been completed. The manufacturer shall provide the completed Test Certificate(s) to the purchaser at time of delivery.

The fire pump shall be mounted on the apparatus and shall have a minimum rated capacity of 250 gpm (1000 L/min) at 150 psi (1000 kPa) net pump pressure.

Where the apparatus is designed for pump in-motion operations, the vehicle drive engine and drive train shall be arranged so that the pump can deliver at least 20 gpm (76 L/min) at a gauge pressure of 80 psi (550 kPa), while the fire apparatus is moving.

If the pumping system provided is rated at 3000 gpm (12,000 L/min) or less, the pump shall be capable of delivering the following:

- (1) One hundred percent of rated capacity at 150 psi (1000 kPa) net pump pressure
- (2) Seventy percent of rated capacity at 200 psi (1400 kPa) net pump pressure
- (3) Fifty percent of rated capacity at 250 psi (1700 kPa) net pump pressure

If the pumping system provided is rated at greater than 3000 gpm (12,000 L/min), the pump shall be capable of delivering the following:

- (1) One hundred percent of rated capacity at 100 psi (700 kPa) net pump pressure
- (2) Seventy percent of rated capacity at 150 psi (1000 kPa) net pump pressure
- (3) Fifty percent of rated capacity at 200 psi (1400 kPa) net pump pressure

If the fire pump has a rated capacity of 750 gpm (3000 L/min) or greater, the pump shall be tested after the pump and all its associated piping and equipment have been installed on the apparatus.

The tests shall include at least the pumping test, the pumping engine overload test, the pressure control system test, the priming devices test, and the vacuum test. A test plate shall be provided at the pump operator's panel that gives the rated discharges and pressures together with the speed of the engine as determined by the certification test for each unit, the position of the parallel/series pump as used, and the governed speed of the engine as stated by the engine manufacturer on a certified brake horsepower curve. The plate shall be completely stamped with all information at the factory and attached to the vehicle prior to shipping.

Pumping Test:

The test site shall be adjacent to a supply of clear water at least 4 feet (1.2 m) deep, with the water level not more than 10 feet (3 m) below the center of the pump intake, and close enough to allow the suction strainer to be submerged at least 2 feet (0.6 m) below the surface of the water when connected to the pump by 20 feet (6 m) of suction hose.

Tests shall be performed when conditions are as follows:

- (1) Air temperature: 0 degrees Fahrenheit to 110 degrees Fahrenheit (−18 degrees Celsius to 43 degrees Celsius)
- (2) Water temperature: 35 degrees Fahrenheit to 90 degrees Fahrenheit (2 degrees Celsius to 32 degrees Celsius).
- (3) Barometric pressure: 29 inches Hg (98.2 kPa), minimum (corrected to sea level)

Engine-driven accessories shall not be functionally disconnected or rendered inoperative during the tests.

The following devices shall be permitted to be turned off or not operating during the pump test:

- (1) Aerial hydraulic pump
- (2) Foam pump

- (3) Hydraulically driven equipment (other than hydraulically driven line voltage generator)
- (4) Winch
- (5) Windshield wipers
- (6) Four-way hazard flashers
- (7) Compressed air foam system (CAFS) compressor

All structural enclosures, such as floorboards, gratings, grilles, and heat shields, not provided with a means for opening them in service shall be kept in place during the tests.

All test gauges shall meet the requirements for Grade A gauges as defined in ASME B40.100, *Pressure Gauges and Gauge Attachments*, and shall be at least size 3 1/2 per ASME B40.100.

The pump intake gauge shall have a range of 30 in. Hg (100 kPa) vacuum to zero for a vacuum gauge, or 30 in. Hg (100 kPa) vacuum to a gauge pressure of 150 psi (1000 kPa) for a compound gauge. The discharge pressure gauge shall have a gauge pressure range of 0 psi to 400 psi (0 kPa to 2800 kPa). All pilot gauges shall have a gauge pressure range of at least 0 psi to 160 psi (0 kPa to 1100 kPa). All gauges shall be calibrated in the month preceding the tests using a dead-weight gauge tester or a master gauge meeting the requirements for Grade 3A or 4A gauges, as defined in

ASME B40.100, *Pressure Gauges and Gauge Attachments*, that has been calibrated within the preceding year.

The engine speed-measuring equipment shall consist of a nonadjustable tachometer supplied from the engine or transmission electronics, a revolution counter on a checking shaft outlet and a stopwatch, or other engine speed-measuring means that is accurate to within ± 50 rpm of actual speed.

If the apparatus is equipped with a fire pump rated at 750 gpm (3000 L/min) or greater but not greater than 3000

gpm (12,000 L/min), the pump shall be subjected to a 3 hour pumping test from draft consisting of 2 hours of continuous pumping at rated capacity at a minimum of 150 psi (1000 kPa) net pump pressure, followed by 1/2 hour of continuous pumping at 70 percent of rated capacity at a minimum of 200 psi (1400 kPa) net pump pressure and 1/2 hour of continuous pumping at 50 percent of rated capacity at a minimum of 250 psi (1700 kPa) net pump pressure and shall not be stopped until after the 2 hour test at rated capacity, unless it becomes necessary to clean the suction strainer.

Pumping Engine Overload Test:

If the pump has a rated capacity of 750 gpm (3000 L/min) or greater but not greater than 3000 gpm (12,000 L/min), the apparatus shall be subjected to an overload test consisting of pumping rated capacity at 165 psi (1100 kPa) net pump pressure for at least 10 minutes. This test shall be performed immediately following the pumping test of rated capacity at 150 psi (1000 kPa). The capacity, discharge pressure, intake pressure, and engine speed shall be recorded at least three times during the overload test.

Pressure Control System Test:

If the pump is rated at 3000 gpm (12,000 L/min) or less, the pressure control system on the pump shall be tested as follows:

- (1) The pump shall be operated at draft, delivering rated capacity at a discharge gauge pressure of 150 psi (1000 kPa).
- (2) The pressure control system shall be set in accordance with the manufacturer's instructions to maintain the discharge gauge pressure at 150 psi (1000 kPa) ± 5 percent.
- (3) All discharge valves shall be closed not more rapidly than in 3 seconds and not more slowly than in 10 seconds.
- (4) The rise in discharge pressure shall not exceed 30 psi (200 kPa) and shall be recorded.
- (5) The original conditions of pumping rated capacity at a discharge gauge pressure of 150 psi (1000 kPa) shall be reestablished

Priming System Tests:

With the apparatus set up for the pumping test, the primer shall be operated in accordance with the manufacturer's instructions until the pump has been primed and is discharging water. This test shall be permitted to be performed in connection with priming the pump for the pumping test.

The interval from the time the primer is started until the time the pump is discharging water shall be noted. The time required to prime the pump shall not exceed 30 seconds if the rated capacity is 1250 gpm (5000 L/min) or less. The time required to prime the pump shall not exceed 45 seconds if the rated capacity is 1500 gpm (6000 L/min) or more.

An additional 15 seconds shall be permitted in order to meet the requirements of 16.13.5.3 and 16.13.5.4 when the pump system includes an auxiliary 4 inches (100 mm) or larger intake pipe having a volume of 1 foot³ (0.30 m³) or more.

Vacuum Test:

The vacuum test shall consist of subjecting the interior of the pump, with all intake valves open, capped or plugged, and all discharge caps removed, to a vacuum of 22 inches/Hg (75 kPa) by means of the pump priming system.

At altitudes above 2000 feet (600 m), the vacuum attained shall be permitted to be less than 22 inches/Hg (75 kPa) by 1 inch/Hg (3.4 kPa) for each 1000 feet (305 m) of altitude above 2000 feet (610 m).

The vacuum shall not drop more than 10 inches/Hg (34 kPa) in 5 minutes.

The primer shall not be used after the 5 minute test period has begun and the engine shall not be operated at any speed greater than the governed speed during this test.

Water Tank-to-Pump Flow Test:

A water tank-to-pump flow test shall be conducted as follows:

- (1) The water tank shall be filled until it overflows
- (2) All intakes to the pump shall be closed.
- (3) The tank fill line and bypass cooling line shall be closed.
- (4) Hose lines and nozzles for discharging water at the rated tank-to-pump flow rate shall be connected to one or more discharge outlets.
- (5) The tank-to-pump valve(s) and the discharge valves leading to the hose lines and nozzles shall be fully opened.
- (6) The engine throttle shall be adjusted until the required flow rate $-0/+5$ percent is established.
- (7) The discharge pressure shall be recorded.
- (8) The discharge valves shall be closed, and the water tank refilled.
- (9) The bypass line shall be permitted to be opened temporarily, if needed, to keep the water temperature in the pump within acceptable limits.
- (10) The discharge valves shall be reopened fully, and the time noted.
- (11) If necessary, the engine throttle shall be adjusted to maintain the discharge pressure recorded as noted in 16.13.7.1(7).
- (12) When the discharge pressure drops by 10 psi (70 kPa) or more, the time shall be noted and the elapsed time from the opening of the discharge valves shall be calculated and recorded.

Volume Discharge Calculation:

The volume discharged shall be calculated by multiplying the rate of discharge in gallons per minute (liters per minute) by the time in minutes elapsed from the opening of the discharge valves until the discharge pressure drops by at least 10 psi (70 kPa).

Other means shall be permitted to be used to determine the volume of water pumped from the tank such as a totalizing flowmeter, weighing the truck before and after, or refilling the tank using a totalizing flowmeter.

The rated tank-to-pump flow rate shall be maintained until 80 percent of the rated capacity of the tank has been discharge.

Engine Speed Advancement Interlock Test

The engine speed advancement interlock system shall be tested to verify that engine speed cannot be increased at the pump operator's panel unless there is throttle-ready indication. If the apparatus is equipped with a stationary pump driven through split-shaft PTO, the test shall verify that the engine speed control at pump operator's panel cannot be advanced when either of the following conditions exists:

- (1) The chassis transmission is in neutral, the parking brake is off, and the pump shift in the driving compartment is in the road position.
- (2) The chassis transmission has been placed in the position for pumping as indicated on the label provided in the driving compartment, the parking brake is on, and the pump shift in the driving compartment is in the road position.

If the apparatus is equipped with a stationary pump driven through a transmission mounted PTO,

front-of-engine crankshaft PTO, or engine flywheel PTO, the test shall verify that the engine speed control on the pump operator's panel cannot be advanced when either of the following conditions exists:

- (1) The chassis transmission is in neutral, the parking brake is off, and the pump shift status in the driving compartment is disengaged.
- (2) The chassis transmission is in any other gear other than neutral, the parking brake is on, and the pump shift in the driving compartment is in the "Pump Engaged" position.

If the apparatus is equipped with a pump driven by the chassis engine designed for both stationary pumping and pump-in-motion, the test shall verify that the engine speed control at pump operator's panel cannot be advanced when either of the following conditions exists:

- (1) The chassis transmission is in neutral, the parking brake is on, and the pump shift status in the driving compartment is disengaged.
- (2) The chassis transmission is in any other gear other than neutral, the parking brake is on, and the pump shift in the driving compartment is in the "Pump Engaged" or the "OK to Pump In-Motion" position.

If the apparatus is equipped with a stationary pump driven through transfer case PTO, the test shall verify that the engine speed control on the pump operator's panel cannot be advanced when either of the following conditions exists:

- (1) The chassis transmission is in neutral, the transfer case is in neutral, the parking brake is off, and the pump shift in the driving compartment is in the road position.
- (2) The chassis transmission is in neutral, the transfer case is engaged, the parking brake is off, and the pump shift in the driving compartment is in the road position.
- (3) The chassis transmission has been placed in the position for pumping as indicated on the label provided in the driving compartment, the parking brake is on, and the pump shift in the driving compartment is in the road position.

LOW-VOLTAGE ELECTRICAL SYSTEM PERFORMANCE TESTING

The apparatus low-voltage electrical system will be tested and certified. Tests shall be performed when the air temperature is between 0 degrees Fahrenheit and 110 degrees Fahrenheit (-18 degrees Celsius and 43 degrees Celsius). The three tests defined in NFPA shall be performed in the order in which they appear. Before each test, the batteries shall be fully charged until the voltage stabilizes at the voltage regulator set point and the lowest charge current is maintained for 10 minutes. Failure of any of these tests shall require a repeat of the sequence.

Reserve Capacity Test:

The engine shall be started and kept running until the engine and engine compartment temperatures are stabilized at normal operating temperatures and the battery system is fully

charged.

The engine shall be shut off and the minimum continuous electrical load shall be activated for 10 minutes.

All electrical loads shall be turned off prior to attempting to restart the engine. The battery system shall then be capable of restarting the engine. Failure to restart the engine shall be considered a test failure of the battery system.

Alternator Performance Test at Idle:

The minimum continuous electrical load shall be activated with the engine running at idle speed.

The engine temperature shall be stabilized at normal operating temperature.

The battery system shall be tested to detect the presence of battery discharge current. The detection of battery discharge current shall be considered a test failure.

Alternator Performance Test at Full Load:

The total continuous electrical load shall be activated with the engine running up to the engine manufacturer's governed speed.

The test duration shall be a minimum of 2 hours.

Activation of the load management system shall be permitted during this test.

An alarm sounded by excessive battery discharge, as detected by the system required in NFPA 13.3.4, or a system voltage of less than 11.8 V dc for a 12 V nominal system or 23.6 V dc for a 24 V nominal system, for more than 120 seconds, shall be considered a test failure.

Low Voltage Alarm Test:

Following the above test, a Low Voltage Alarm Test will be performed in the manner prescribed.

With the engine shut off, the total continuous electrical load shall be activated and shall continue to be applied until the excessive battery discharge alarm activates.

The battery voltage shall be measured at the battery terminals.

The test shall be considered a failure if the alarm has not yet sounded 140 seconds after the voltage drops to 11.70V for a 12 V nominal system or 23.4 V for a 24 V nominal system.

The battery system shall then be able to restart the engine. Failure to restart the engine shall be considered a test failure.

VIDEO CONFERENCE PRE-CONSTRUCTION

The factory authorized Distributor shall be required, prior to manufacturing, to have a pre-construction conference with a factory representative and individual(s) from the Andover Fire Department to finalize all construction details.

The pre-construction shall be held via video conferencing equipment between two different locations. The factories authorized distributor shall, at his expense, provide transportation, lodging, and meals.

FINAL INSPECTION CONFERENCE

The factory authorized Distributor shall be required, during manufacturing, to have a final completion inspection conference at the site of the manufacturing facility with Three (3) individuals from the Andover Fire Department to inspect the apparatus after construction. The factories authorized distributor shall, at his expense, provide transportation, lodging, and meals. Any distance greater than 200 miles shall be by commercial air travel.

MODEL

The cab and chassis shall include design considerations for multiple emergency vehicle applications, rapid transit and maneuverability. The chassis shall be manufactured for heavy duty service with the strength and capacity to support a fully laden apparatus, one hundred (100) percent of the time.

MODEL YEAR

The chassis shall have a vehicle identification number that reflects a 2024 model year.

COUNTRY OF SERVICE

The chassis shall be put in service in the country of United States of America (USA).

The chassis will meet applicable U.S.A. federal motor vehicle safety standards per CFR Title 49 Chapter V Part 571 as clarified in the incomplete vehicle book per CFR Title 49 Chapter V Part 568 Section 4 which accompanies each chassis. The chassis manufacturer is not responsible for compliance to state, regional, or local regulations. Dealers should identify those regulations and order any necessary optional equipment from the chassis manufacturer or their OEM needed to be in compliance with those regulations

CAB AND CHASSIS LABELING LANGUAGE

The cab and chassis shall include the applicable caution, warning, and safety notice labels with text to be written in English. All applicable caution, warning, and safety notice labels shall be Innovative Controls brand. Where applicable to the location within the specific layout and label package of the cab and chassis, the labels shall include decorative chrome bezels. Designs shall include bezels that fit individual labels or packaged configurations of labels in certain common locations.

The following labels shall be Innovative Controls brand, each including a decorative chrome bezel (where applicable):

Shoreline

Air Conditioner

Cab Tilt Plate

Air Compressor Breaker

Battery Conditioner Breaker

Helmet Caution

Horn Tag

Q2B Tag

Load Center Plate

Not a Step Label

Occupancy Tag

Do Not Move

Occupants Must Be Seated

Do Not Stand

Danger Do Not Weld

Danger--Untrained Operator

DEF Fill Access (Including Additional 2907 Optional Labels)

Battery Direct

Kneeling

IFS Air Fault

Engine Brake

Retarder

LR 100 Amp Node

300 Amp EPU

100 Amp Front O/R Node

100 Amp T/T Node

100 Amp RR O/R Node

10 Amp EPU

Master Power

12 Volt Power
Pump In Drive
Windshield Washer Fluid

APPARATUS TYPE

The apparatus shall be a pumper vehicle designed for emergency service use which shall be equipped with a permanently mounted fire pump which has a minimum rated capacity of 750 gallons per minute (3000 L/min). The apparatus shall include a water tank and hose body whose primary purpose is to combat structural and associated fires.

VEHICLE TYPE

The chassis shall be manufactured for use as a straight truck type vehicle and designed for the installation of a permanently mounted apparatus behind the cab. The apparatus of the vehicle shall be supplied and installed by the apparatus manufacturer.

VEHICLE ANGLE OF APPROACH PACKAGE

The angle of approach of the apparatus shall be a minimum of 8.00 degrees.

NFPA1901 Angle of Approach definition:

“To determine the angle of approach, place a thin steel strip against the front of the tires where they touch the ground or stretch a tight string from one front tire to the other at the front where they touch the ground. Determine the lowest point (component or equipment) on the vehicle forward of the front tire that would make the smallest angle of approach. Hang a plumb bob from the lowest point and mark the point on the ground where the point of the plumb bob touches. Measure the vertical distance from the ground to the point where the plumb bob was hung (distance V). Measure the horizontal distance from the plumb bob point to the steel strip or string running from front tire to front tire (distance H). Divide the vertical distance by the horizontal distance. The ratio of V/H is the tangent of the angle of approach.

If the ratio is known, the angle of approach can be determined from a table of trigonometric functions of angles or from a math calculator. The standard requires a minimum angle of approach of 8.00 degrees: since the tangent of 8.00 degrees is 0.1405, if V divided by H is 0.1405 or larger, the angle of approach is 8.00 degrees or greater.”

AXLE CONFIGURATION

The chassis shall feature a 4 x 2 axle configuration consisting of a single rear drive axle with a single front steer axle.

GROSS AXLE WEIGHT RATINGS FRONT

The front gross axle weight rating (GAWR) of the chassis shall be 20,000 pounds.

This front gross axle weight rating shall be adequate to carry the weight of the completed apparatus including all equipment and personnel.

GROSS AXLE WEIGHT RATINGS REAR

The rear gross axle weight rating (GAWR) of the chassis shall be 27,000 pounds.

This rear gross axle weight rating shall be adequate to carry the weight of the completed apparatus including all equipment and personnel.

PUMP PROVISION

The chassis shall include provisions to mount a drive line pump in the middle of the chassis, behind the cab, more commonly known as the midship location. Chassis driveline pump

provisions shall include an interlock feature for automatic setting of the park brake when the vehicle is shifted into pump mode while the transmission is in neutral and the transmission output speed translates to less than 1 mph. When the conditions are met the driver side parking brake valve shall activate. Once shifted to road mode the condition for electric automatic brake engagement is no longer present and the driver's parking brake control valve shall function normally.

WATER & FOAM TANK CAPACITY

The chassis shall include a carrying capacity of 750 gallons (2839 liters) to 1250 gallons (4732 liters). The water and/or foam tank(s) shall be supplied and installed by the apparatus manufacturer.

CAB STYLE

The cab shall be a custom, fully enclosed model with a 10.00 inch raised roof over the driver, officer, and crew area, designed and built specifically for use as an emergency response vehicle by a company specializing in cab and chassis design for all emergency response applications. The cab shall be designed for heavy-duty service utilizing superior strength and capacity for the application of protecting the occupants of the vehicle. This style of cab shall offer up to eight (8) seating positions.

The cab shall incorporate a fully enclosed design with side wall roof supports, allowing for a spacious cab area with no partition between the front and rear sections of the cab. To provide a superior finish by reducing welds that fatigue cab metal; the roof, the rear wall and side wall panels shall be assembled using a combination of welds and proven industrial adhesives designed specifically for aluminum fabrication for construction.

The cab shall be constructed using multiple aluminum extrusions in conjunction with aluminum plate, which shall provide proven strength and the truest, flattest body surfaces ensuring less expensive paint repairs if needed. All aluminum welding shall be completed to the American Welding Society and ANSI D1.2-96 requirements for structural welding of aluminum.

All interior and exterior seams shall be sealed for optimum noise reduction and to provide the most favorable efficiency for heating and cooling retention.

The cab shall be constructed of 5052-H32 corrosion resistant aluminum plate. The cab shall incorporate tongue and groove fitted 6061-T6 0.13 & 0.19 inch thick aluminum extrusions for extreme duty situations. A single formed, one (1) piece extrusion shall be used for the "A" pillar, adding strength and rigidity to the cab as well as additional roll-over protection. The cab side walls and lower roof skin shall be 0.13 inch thick; the rear wall and raised roof skins shall be 0.09 inch thick; the front cab structure shall be 0.19 inch thick.

The exterior width of the cab shall be 94.00 inches wide with a minimum interior width of 88.00 inches. The overall cab length shall be 137.10 inches with 60.00 inches from the centerline of the front of the axle to the back of the cab.

The cab interior shall be designed to afford the maximum usable interior space and attention to ergonomics with hip and legroom while seated which exceeds industry standards. The crew cab floor shall be flat across the entire walking area for ease of movement inside the cab

The cab shall offer an interior height of 57.50 inches from the front floor to the headliner and a rear floor to headliner height of 65.00 inches in the raised roof area, at a minimum. The cab shall offer an interior measurement at the floor level from the rear of the engine

tunnel to the rear wall of the cab of 57.88 inches. All interior measurements shall include the area within the interior trimmed surfaces and not to any unfinished surface.

The cab shall include a driver and officer area with two (2) cab doors large enough for personnel in full firefighting gear. The front doors shall offer a clear opening of 40.25 inches wide X 53.50 inches high, from the cab floor to the top of the door opening. The cab shall also include a crew area with up to two (2) cab doors, also large enough for personnel in full firefighting gear. The rear doors shall offer a clear opening of 32.25 inches wide X 61.00 inches high, from the cab floor to the top of the door opening.

The cab shall incorporate a progressive two (2) step configuration from the ground to the cab floor at each door opening. The progressive steps are vertically staggered and extend the full width of each step well allowing personnel in full firefighting gear to enter and exit the cab easily and safely.

The first step for the driver and officer area shall measure approximately 11.50 inches deep X 31.13 inches wide. The intermediate step shall measure approximately 8.50 inches deep X 32.50 inches wide. The height from the first step to the intermediate step and the intermediate step to the cab floor shall not exceed 11.00 inches.

The first step for the crew area shall measure approximately 11.50 inches deep X 20.44 inches wide. The intermediate step shall measure approximately 10.25 inches deep X 22.75 inches wide. The height from the first step to the intermediate step and the intermediate step to the cab floor shall not exceed 12.80 inches.

OCCUPANT PROTECTION

An IMMI 4Front® occupant protection system shall be installed in the vehicle's cab. The system shall inflate three (3) air bags in the following locations:

- Steering wheel air bag to protect the head and neck of the driver
- Knee bolster air bag to protect the driver's legs
- Knee bolster air bag to protect the officer's legs

The air bags shall use a combination of high-pressure stored argon and oxygen with a pyrotechnic charge for initiation to inflate the bags remain inflated for several seconds. The system shall be connected to the crash detection sensor that will also activate the driver and first officer integrated belt pretensioners if it detects a frontal crash.

A RollTek™ rollover occupant protection system shall be installed in the apparatus cab. The system shall include an integrated roll sensor (IRS) master module and a slave sensor in applicable configurations.

The IRS shall be a microprocessor-controlled solid-state sensing device that utilizes vehicle-specific calibrations to detect rollovers. The IRS shall be equipped with pyrotechnic loops for connection to the protective countermeasures which shall include seat integrated side roll airbags (SRA), integrated seat belt pretensioners, and air seat pull-downs (S4S), in applicable occupant seat positions.

The IRS shall continuously monitor the truck's acceleration and angle, and upon detection of an imminent roll-over, shall activate protective countermeasures in a pre-programmed sequence. In addition, the IRS shall also act as a data recorder to record crash events for post-crash evaluation.

CAB FRONT FASCIA

The front cab fascia shall be constructed of 5052-H32 Marine Grade, 0.13 of an inch thick aluminum plate which shall be an integral part of the cab.

The cab fascia will encompass the entire front of the aluminum cab structure from the bottom

of the windshield to the bottom of the cab and shall be the "Classic" design. The front cab fascia shall include two (2) molded plastic modules on each side accommodating a total of up to four (4) Hi/Low beam headlights and two (2) turn signal lights or up to four (4) warning lights. A chrome plated molded plastic bezel shall be provided on each side around each set of four lamps.

FRONT GRILLE

The front fascia shall include a box style, 304 stainless steel front grille 44.45 inches wide X 33.50 inches high X 1.50 inches deep. The grille shall include a minimum free air intake of 732.00 square inches. The upper portion of the grille shall be hinged to provide service access behind the grille.

CAB UNDERCOAT

There shall be a rubberized undercoating applied to the underside of the cab that provides abrasion protection, sound deadening and corrosion protection.

CAB SIDE DRIP RAIL

There shall be a drip rail along the top radius of each cab side. The drip rails shall help prevent water from the cab roof running down the cab side.

CAB PAINT EXTERIOR

The cab exterior shall be painted two tone per customers specified paint colors.

CAB PAINT PROCESS/MANUFACTURER

The cab paint manufacturer shall be determined at a later date. The cab shall be painted prior to the installation of glass accessories and all other cab trim to ensure complete paint coverage and the maximum in corrosion protection of all metal surfaces.

All metal surfaces on the cab shall be mechanically etched by sanding disc to remove any surface oxidation or surface debris which may hinder the paint adhesion. Once all imperfections on the exterior surfaces are removed and sanded smooth, body fillers shall be applied to the cab on all surfaces that require a critically aesthetic finish and sanded smooth. The entire cab shall then be coated with a high quality base primer that is designed to fill any minor surface defects, provide an adhesive bond between the primer and the paint and improve the color and gloss retention of the color. The finish to this procedure shall be sanding the cab to a smooth finish followed by sealing the seams with an automotive seam sealer. The minimum thickness of the primer coat after sanding shall be 2.50 mils with a maximum thickness of 5.00 mils.

The cab shall then be painted the specific color(s) designated by the customer with an acrylic urethane type system designed to retain color and resist acid rain and most atmospheric chemicals found on an emergency scene. The paint shall have a minimum thickness of 1.00 mils with a maximum of 4 mils, followed by a clear top coat with a minimum of 2.5 mils and a maximum of 3.5 mils. The entire cab shall then be baked to speed the curing process of the coatings.

CAB PAINT PRIMARY/LOWER COLOR

The primary/lower paint color shall be Red, paint code to be provided.

CAB PAINT SECONDARY/UPPER COLOR

The secondary/upper paint color shall be White, paint code to be provided.

CAB PAINT EXTERIOR BREAKLINE

The upper and lower paint shall meet at a breakline on the cab which shall be located approximately 1.00 inch below the door windows on each side of the cab. The breakline shall curve down at the front cab corners to approximately 5.00 inches below the windshields on the front of the cab.

CAB PAINT PINSTRIPE

A 0.50 inch wide gold leaf tape with black borders shall be applied on the break line between the two different colored surfaces.

CAB PAINT WARRANTY

The cab paint warranty shall be determined once the customer chooses a paint manufacturer (1533).

CAB PAINT INTERIOR

The visible interior cab structure surfaces shall be painted with a multi-tone silver gray texture finish.

CAB ENTRY DOORS

The cab shall include four (4) entry doors, two (2) front doors and two (2) crew doors designed for ease of entering and egress when outfitted with an SCBA. The doors shall be constructed of extruded aluminum with a nominal thickness of 0.13 inch. The exterior skins shall be constructed of 0.13 inch aluminum plate.

The doors shall include a double rolled style automotive rubber seal around the perimeter of each door frame and door edge which ensures a weather tight fit.

All door hinges shall be hidden within flush mounted cab doors for a pleasing smooth appearance and perfect fit along each side of the cab. Each door hinge shall be piano style with a 0.38 inch pin and shall be constructed of stainless steel.

CAB ENTRY DOOR TYPE

All cab entry doors shall be full length in design to fully enclose the lower cab steps. Entry doors shall include Pollak mechanical plunger style switches for electrical component activation.

CAB INSULATION

The cab ceiling and walls shall include a nonwoven polyester fiber insulation. The insulation shall act as a barrier absorbing noise as well as assisting in sustaining the desired climate within the cab interior.

CAB STRUCTURAL WARRANTY

Purchaser shall receive a Cab Structure (Aluminum) Ten (10) Years or 100,000 Miles limited warranty in accordance with, and subject to, warranty certificate RFW0602. The warranty certificate is incorporated by reference into this proposal, and included with this proposal or available upon request.

CAB TEST INFORMATION

The cab shall have successfully completed the preload side impact, static roof load application and frontal impact without encroachment to the occupant survival space when tested in accordance with Section 4 of SAE J2420 COE Frontal Strength Evaluation Dynamic Loading Heavy Trucks, Section 5 of SAE J2422 Cab Roof Strength Evaluation Quasi –Static Loading Heavy Trucks and ECE R29 Uniform Provisions Concerning the Approval of Vehicles with regard to the Protection of the Occupants of the Cab of a Commercial Vehicles Annex 3 Paragraph 5.

The above tests have been witnessed by and attested to by an independent third party. The test results were recorded using cameras, high speed imagers, accelerometers and strain gauges. Documentation of the testing shall be provided upon request.

ELECTRICAL SYSTEM

The chassis shall include a single starting electrical system which shall include a 12 volt direct current multiplexing system, suppressed per SAE J551. The wiring shall be appropriate gauge cross link with 311 degree Fahrenheit insulation. All SAE wires in the chassis shall be

color coded and shall include the circuit number and function where possible. The wiring shall be protected by 275 degree Fahrenheit minimum high temperature flame retardant loom. All nodes and sealed Deutsch connectors shall be waterproof.

MULTIPLEX DISPLAY

The multiplex electrical system shall include a Weldon Vacuum Florescent Display (VFD) or equivalent display which shall be located in the switch panel with a location specific to the customer's needs. The VFD display is a two (2) line, forty (40) character display capable of showing a wide range of data from the multiplex system.

In addition to showing system errors, the VFD shall display:

Warning – Door Open

Door Location

Seat Violation

Park Brake Released

Emergency Master On

Response Mode

Emergency Master On

Scene Mode

A momentary push button shall be located on the dash which when pressed acknowledges the current message and displays the next message. If no message is present, the VFD shall default to display the Fire Department Name.

LOAD MANAGEMENT SYSTEM

The apparatus load management shall be performed by the included multiplex system. The multiplex system shall also feature the priority of sequences and shall shed electrical loads based on the priority list specifically programmed.

DATA RECORDING SYSTEM

The chassis shall have a Weldon Vehicle Data Recorder (VDR), or equivalent system installed. The system shall be designed to meet NFPA 1901 and shall be integrated with the Weldon Multiplex electrical system. The following information shall be recorded:

Vehicle Speed

Acceleration

Deceleration

Engine Speed

Engine Throttle Position

ABS Event

Seat Occupied Status

Seat Belt Status

Master Optical Warning Device Switch Position

Time

Date

Each portion of the data shall be recorded at the specified intervals and stored for the specified length of time to meet NFPA 1901 guidelines and shall be retrievable by connecting a laptop computer to the VDR system. The laptop connection shall be a panel mounted female type B USB connection point, remotely mounted in the left side foot well.

ACCESSORY POWER

The electrical distribution panel shall include two (2) power studs. The studs shall be size #10 and each of the power studs shall be circuit protected with a fuse of the specified amperage. One (1) power stud shall be capable of carrying up to a 40 amp battery direct load. One (1) power stud shall be capable of carrying up to a 15 amp ignition switched load. The two (2) power studs shall share one (1) #10 ground stud.

An OEM body connections bracket shall be installed on the chassis near the left hand battery

box. The bracket shall include one (1) set each of 200 amp master power switched and 300 amp battery direct fused power and ground studs.

AUXILIARY ACCESSORY POWER An auxiliary ten (10) position blade type fuse panel shall be installed behind the officer's seat. The fuse panel shall be protected by a 40 amp fuse. The panel shall be capable of carrying up to a maximum 40 amp battery direct load.

EXTERIOR ELECTRICAL TERMINAL COATING

All terminals exposed to the elements will be sprayed with a high visibility protective rubberized coating to prevent corrosion.

ELECTRICAL SYSTEM WARRANTY

Purchaser shall receive an Electrical System Two (2) Years or 36,000 Miles limited warranty in accordance with, and subject to, warranty certificate RFW0202. The warranty certificate is incorporated by reference into this proposal, and included with this proposal or available upon request.

ENGINE

The chassis engine shall be a Cummins X12 engine. The X12 engine shall be an in-line six (6) cylinder, four cycle diesel powered engine. The engine shall offer a rating of 500 horse power at 1900 RPM and shall be governed at 2000 RPM. The torque rating shall feature 1700 foot pounds of torque at 1000 RPM with 720 cubic inches (11.8 liter) of displacement.

The X12 engine shall feature a VGT™ Turbocharger, a high pressure common rail fuel system, fully integrated electronic controls with an electronic governor, and shall be EPA certified to meet the 2021 emissions standards using cooled exhaust gas recirculation and selective catalytic reduction technology.

The engine shall include an engine mounted combination full flow/by-pass oil filter with replaceable spin on cartridge for use with the engine lubrication system. The engine shall include Citgo brand Citgard 500, or equivalent SAE 15W40 CK-4 low ash engine oil which shall be utilized for proper engine lubrication.

A wiring harness shall be supplied ending at the back of the cab. The harness shall include a connector which shall allow an optional harness for the pump panel. The included circuits shall be provided for a tachometer, oil pressure, engine temperature, hand throttle, high idle and a PSG system. A circuit for J1939 data link shall also be provided at the back of the cab.

CAB ENGINE TUNNEL

The cab interior shall include an integrated engine tunnel constructed of 5052-H32 Marine Grade, 0.19 of an inch thick aluminum. The tunnel shall be a maximum of 41.50 inches wide X 25.50 inches high.

DIESEL PARTICULATE FILTER CONTROLS

There shall be two (2) controls for the diesel particulate filter. One (1) control shall be for regeneration and one (1) control shall be for regeneration inhibit.

ENGINE PROGRAMMING HIGH IDLE SPEED

The engine high idle control shall maintain the engine idle at approximately 1250 RPM when engaged.

ENGINE HIGH IDLE CONTROL

The vehicle shall be equipped with a high-idle speed rocker switch and an automatic high-idle speed control. It shall be pre-set so when activated, it will operate the engine at the appropriate RPM to increase alternator output. This device shall operate only when the engine is running and the transmission is in neutral with the parking brake set. When automatically engaged the high idle shall disengage when the operator depresses the brake pedal, or the transmission is placed in gear, and shall be available to manually or

automatically re-engage when the brake is released, or when the transmission is placed in neutral.

ENGINE PROGRAMMING ROAD SPEED GOVERNOR

The engine shall include programming which will govern the top speed of the vehicle.

AUXILIARY ENGINE BRAKE

A compression brake, for the six (6) cylinder engine shall be provided. A cutout relay shall be installed to disable the compression brake when in pump mode or when an ABS event occurs. The engine compression brake shall activate upon 0% accelerator when in operation mode and actuate the vehicle's brake lights.

The engine shall utilize a variable geometry turbo (VGT) as an integrated auxiliary engine brake to offer a variable rate of exhaust flow, which when activated in conjunction with the compression brake shall enhance the engine's compression braking capabilities.

AUXILIARY ENGINE BRAKE CONTROL

An engine compression brake control device shall be included. The electronic control device shall monitor various conditions and shall activate the engine brake only if all of the following conditions are simultaneously detected:

A valid gear ratio is detected.

The driver has requested or enabled engine compression brake operation.

The throttle is at a minimum engine speed position.

The electronic controller is not presently attempting to execute an electronically controlled final drive gear shift.

The compression brake shall be controlled through an on/off switch and a low/medium/high selector switch

ELECTRONIC ENGINE OIL LEVEL INDICATOR

The engine oil shall be monitored electronically and shall send a signal to activate a warning in the instrument panel when levels fall below normal. The warning shall activate in a low oil situation upon turning on the master battery and ignition switches without the engine running.

FLUID FILLS

The front of the chassis shall accommodate fluid fill for the engine oil through the grille. This area shall also accommodate a check for the engine oil. The transmission, power steering, and coolant fluid fills and checks shall be under the cab. The windshield washer fill shall be accessible through the front left side mid step.

ENGINE DRAIN PLUG

The engine shall include an original equipment manufacturer installed oil drain plug.

ENGINE WARRANTY

The Cummins engine shall be warranted for a period of five (5) years or 100,000 miles, whichever occurs first.

REMOTE THROTTLE HARNESS

An apparatus interface wiring harness for the engine and transmission pump interlocks shall be supplied with the chassis. The harness shall include a connector for connection to a chassis pump panel harness supplied by the body builder and shall terminate in the left frame rail behind the cab for connection by the body builder. The harness shall include circuits deemed for a pump panel and shall contain circuits for a hand throttle, and a multiplexed gauge.

Separate circuits shall also be included for a pump control switch, "Pump Engaged" and "OK to Pump" indicator lights, open compartment ground, start signal, park brake ground, ignition signal, master power, clean power, customer ignition, air horn solenoid switch, high idle switch and high idle indicator light. The harness shall contain interlocks that will prevent

shifting to road or pump mode unless the transmission output speed translates to less than 1 mph and the transmission is in neutral. The shift to pump mode shall also require the park brake be set.

ENGINE PROGRAMMING REMOTE THROTTLE

The engine ECM (Electronic Control Module) discrete wire remote throttle circuit shall be turned off for use with a J1939 based pump controller or when the discrete wire remote throttle controls are not required.

ENGINE PROGRAMMING IDLE SPEED

The engine low idle speed will be programmed at 700 rpm.

ENGINE AIR INTAKE

The engine air intake system shall include an ember separator. This ember separator shall be designed to protect the downstream air filter from embers using a combination of unique flat and crimped metal screens packaged in a heavy duty galvanized steel frame. This multilayered screen shall trap embers and allow them to burn out before passing through the pack.

The engine air intake system shall also include an air cleaner mounted above the radiator. This air cleaner shall utilize a replaceable dry type filter element designed to prevent dust and debris from being ingested into the engine. A service cover shall be provided on the housing, reducing the chance of contaminating the air intake system during air filter service.

The air intake system shall include a restriction indicator light in the warning light cluster on the instrument panel, which shall activate when the air cleaner element requires replacement.

ENGINE FAN DRIVE

The engine cooling system fan shall incorporate a thermostatically controlled, Horton fully variable type fan drive with SmartClutch J-1939 CAN controller.

The variable speed fan clutch only engages at the amount needed for proper cooling to facilitate improved vehicle performance, cab heating in cold climates, and fuel economy. The fan clutch design shall be fail-safe so that if the clutch drive fails the fan shall engage to prevent engine overheating due to the fan clutch failure. The fan speed shall include a J-1939 CAN clutch controller to receive signal from the engine control module to activate at variable rates of speed. Variable speeds shall be set through thermostatic and engine speed signals to run as efficiently and quietly as required to maintain temperature.

ENGINE COOLING SYSTEM

There shall be a heavy-duty aluminum cooling system designed to meet the demands of the emergency response industry. The cooling system shall have the capacity to keep the engine properly cooled under all conditions of road and pumping operations. The cooling system shall be designed and tested to meet or exceed the requirements specified by the engine and transmission manufacturer and all EPA requirements. The complete cooling system shall be mounted to isolate the entire system from vibration or stress. The individual cores of the cooling system shall be mounted in a manner to allow expansion and contraction at various rates without inducing stress into the adjoining cores.

The cooling system shall be comprised of a charge air cooler to radiator serial flow package that provides the maximum cooling capacity for the specified engine as well as serviceability. The main components shall include a surge tank, a charge air cooler bolted to the front of the radiator, recirculation shields, a shroud, a fan, and required tubing.

The radiator shall be a down-flow design constructed with aluminum cores, plastic end tanks, and a steel frame. The radiator shall be equipped with a drain cock to drain the coolant for serviceability.

The cooling system shall include a one piece injected molded polymer fan with a three (3) piece fiberglass fan shroud.

The cooling system shall be equipped with a surge tank that is capable of removing entrained air from the system. The surge tank shall be equipped with a low coolant probe and rearward

oriented sight glass to observe coolant in the system. A cold fill and observation line shall be included within the frame mounted translucent recovery bottle to monitor the level of the coolant. The surge tank shall have a dual seal cap that meets the engine manufacturer's pressure requirements and allows for expansion and recovery of coolant into a separate integral expansion chamber.

All radiator tubes shall be formed from aluminized steel tubing. Recirculation shields shall be installed where required to prevent heated air from reentering the cooling package and affecting performance.

The charge air cooler shall be a cross-flow design constructed completely of aluminum with cast tanks. All charge air cooler tubes shall be formed from aluminized steel tubing and installed with silicone hump hoses and stainless steel "constant torque" style clamps meeting the engine manufacturer's requirements.

The radiator and charge air cooler shall be removable through the bottom of the chassis.

ENGINE COOLING SYSTEM PROTECTION

The engine cooling system shall include a recirculation shield designed to act as a light duty skid plate below the radiator to provide additional protection for the engine cooling system from light impacts, stones, and road debris. The skid plate shall be painted to match the frame components.

ENGINE COOLANT

The cooling package shall include Extended Life Coolant (ELC). The use of ELC provides longer intervals between coolant changes over standard coolants providing improved performance. The coolant shall contain a 50/50 mix of ethylene glycol and de-ionized water to keep the coolant from freezing to a temperature of -34 degrees Fahrenheit. Proposals offering supplemental coolant additives (SCA) shall not be considered, as this is part of the extended life coolant makeup.

ELECTRONIC COOLANT LEVEL INDICATOR

The instrument panel shall feature a low engine coolant indicator light which shall be located in the center of the instrument panel. An audible tone alarm shall also be provided to warn of a low coolant incident.

ENGINE PUMP HEAT EXCHANGER

A single bundle type coolant to water heat exchanger shall be installed between the engine and the radiator. The heat exchanger shall be designed to prohibit water from the pump from coming in contact with the engine coolant. This shall allow the use of water from the discharge side of the pump to assist in cooling the engine.

COOLANT HOSES

The cooling system hoses shall be blue stripe heater hose with formed silicone radiator coolant hoses and formed aluminized steel tubing. The heater hose, radiator hose, and tubing shall be secured with stainless steel constant torque band clamps.

ENGINE COOLANT OVERFLOW BOTTLE

A remote engine coolant overflow expansion bottle shall be provided in the case of over filling the coolant system. The overflow bottle shall capture the expansion fluid or overflow rather than allow the fluid to drain on the ground.

ENGINE EXHAUST SYSTEM

The exhaust system shall include an end-in end-out horizontally mounted single module after treatment device, and downpipe from the charge air cooled turbo. The single module shall include four temperature sensors, diesel particulate filter (DPF), urea dosing module (UL2), and a selective catalytic reduction (SCR) catalyst to meet current EPA standards. The selective catalytic reduction catalyst utilizes a diesel exhaust fluid solution consisting of urea

and purified water to convert NOx into nitrogen, water, and trace amounts of carbon dioxide. The solution shall be mixed and injected into the system through the DPF and SCR.

The system shall utilize 0.07 inch thick stainless steel exhaust tubing between the engine turbo and the DPF. Zero leak clamps seal all system joints between the turbo and DPF.

The single module after treatment through the end of the tailpipe shall be connected with zero leak clamps. The discharge shall terminate horizontally on the right side of the vehicle ahead of the rear tires.

The exhaust system after treatment module shall be mounted below the frame in the outboard position.

DIESEL EXHAUST FLUID TANK

The exhaust system shall include a molded cross linked polyethylene tank for Diesel Exhaust Fluid (DEF). The tank shall have a capacity of six (6) usable gallons and shall be mounted on the left hand side of the chassis frame behind the batteries below the frame.

The DEF tank shall be designed with capacity for expansion in case of fluid freezing. Engine coolant which shall be thermostatically controlled, shall be run through lines in the tank to help prevent the DEF from freezing and to provide a means of thawing the fluid if it should become frozen.

The tank fill tube shall be routed under the rear of the cab with the fill neck and splash guard accessible in the top rear step.

ENGINE EXHAUST ACCESSORIES

An exhaust temperature mitigation device shall be shipped loose for installation by the body manufacturer on the vehicle. The temperature mitigation device shall lower the temperature of the exhaust by combining ambient air with the exhaust gasses at the exhaust outlet.

ENGINE EXHAUST WRAP

The exhaust tubing between the engine turbo and the diesel particulate filter (DPF) shall be wrapped with a thermal cover in order to retain the necessary heat for DPF regeneration. The exhaust wrap shall also help protect surrounding components from radiant heat which can be transferred from the exhaust.

The exhaust flex joint shall not include the thermal exhaust wrap.

EMISSIONS SYSTEMS WARRANTY

Purchaser shall receive a Regulated Emissions Systems Five (5) Years or 100,000 Miles limited warranty in accordance with, and subject to, warranty certificate RFW0140. The warranty certificate is incorporated by reference into this proposal, and included with this proposal or available upon request.

TRANSMISSION

The drive train shall include an Allison model EVS 4000 torque converting, automatic transmission which shall include electronic controls. The transmission shall feature two (2) 10-bolt PTO pads located on the converter housing.

The transmission shall include two (2) internal oil filters which shall offer Castrol TranSynd™ synthetic TES 295 transmission fluid which shall be utilized in the lubrication of the EVS transmission. An electronic oil level sensor shall be included with the readout located in the shift selector.

The transmission gear ratios shall be:

1st 3.51:1

2nd 1.91:1

3rd 1.43:1

4th 1.00:1

5th 0.74:1

6th 0.64:1 (if applicable)

Rev 4.80:1

TRANSMISSION MODE PROGRAMMING

The transmission, upon start-up, will select five (5) speeds of operation. The sixth speed over drive shall be available with the activation of the mode button on the shifting pad.

TRANSMISSION FEATURE PROGRAMMING

The Allison Gen V/VI-E transmission EVS group package number 127 shall contain the 198 vocational package in consideration of the duty of this apparatus as a pumper. This package shall incorporate an automatic neutral with selector override. This feature commands the transmission to neutral when the park brake is applied, regardless of drive range requested on the shift selector. This requires re-selecting drive range to shift out of neutral for the override. This package shall be coupled with the use of a split shaft PTO and incorporate pumping circuits. These circuits shall be used allowing the vehicle to operate in the fourth range lockup while operating the pump mode due to the 1 to 1 ratio through the transmission, therefore the output speed of the engine is the input speed to the pump. The pump output can be easily calculated by using this input speed and the drive ratio of the pump itself to rate the gallons of water the pump can provide.

A transmission interface connector shall be provided in the cab. This package shall contain the following input/output circuits to the transmission control module. The Gen V/VI-E transmission shall include prognostic diagnostic capabilities. These capabilities shall include the monitoring of the fluid life, filter change indication, and transmission clutch maintenance.

TRANSMISSION SHIFT SELECTOR

An Allison pressure sensitive range selector touch pad shall be provided and located to the right of the driver within clear view and easy reach. The shift selector shall have a graphical Vacuum Florescent Display (VFD) capable of displaying two lines of text. The shift selector shall provide mode indication and a prognostic indicator (wrench symbol) on the digital display. The prognostics monitor various operating parameters and shall alert you when a specific maintenance function is required.

ELECTRONIC TRANSMISSION OIL LEVEL INDICATOR

The transmission fluid shall be monitored electronically and shall send a signal to activate a warning in the instrument panel when levels fall below normal.

TRANSMISSION PRE-SELECT WITH AUXILIARY BRAKE

When the auxiliary brake is engaged, the transmission shall automatically shift to second gear to decrease the rate of speed assisting the secondary braking system and slowing the vehicle.

TRANSMISSION COOLING SYSTEM

The transmission shall include a water to oil cooler system located in the cooling loop between the radiator and the engine. The transmission cooling system shall meet all transmission manufacturer requirements. The transmission cooling system shall feature continuous flow of engine bypass water to maintain uninterrupted transmission cooling.

TRANSMISSION DRAIN PLUG

The transmission shall include an original equipment manufacturer installed magnetic transmission fluid drain plug.

TRANSMISSION WARRANTY

The Allison EVS series transmission shall be warranted for a period of five (5) years with unlimited mileage. Parts and labor shall be included in the warranty.

LH PTO

A PTO shall be installed on the transmission by the OEM.

LH PTO MODEL

A ten (10) bolt Chelsea model 280-GSFJP-B8RK heavy duty transmission driven PTO shall

be installed. The clutched shifted PTO is designed specifically for the Allison world transmission and provides an intermittent and continuous torque rating of 265 lb. ft.

PTO LOCATION

The transmission shall have two (2) power take off (PTO) mounting locations, one (1) in the 8:00 o'clock position and one (1) in the 1:00 o'clock position

LH PTO CONTROL

A pre-wire shall be provided for a customer mounted left hand power take off which shall be controlled by the transmission. The power take off shall be activated by a locking on/off rocker switch which contains an integral light which shall illuminate upon a positive engagement of the power take off. This switch shall be located on dash.

Required operating conditions for enabling this function are:

- Throttle position is low
- Engine speed is within customer modifiable constant limits
- Output speed is within customer modifiable constant limits

Park brake set

DRIVELINE

All drivelines shall be heavy duty metal tube and equipped with MSI 1810 series universal joints. The shafts shall be dynamically balanced prior to installation to alleviate future vibration. In areas of the driveline where a slip shaft is required, the splined slip joint shall be coated with Glide Coat®. The drivelines shall include Meritor brand u-joints with thrust washers.

MIDSHIP PUMP / GEARBOX

A temporary jackshaft driveline shall be installed by the chassis manufacturer to accommodate the mid-ship split shaft pump as specified by the apparatus manufacturer.

MIDSHIP PUMP / GEARBOX MODEL

The midship pump/gearbox provisions shall be for a Hale DSD forward pump.

MIDSHIP PUMP GEARBOX DROP

The Hale pump gearbox shall have an "L" (long) drop length.

MIDSHIP PUMP RATIO

The ratio for the midship pump shall be 2.28:1 (23).

MIDSHIP PUMP LOCATION C/L SUCTION TO C/L REAR AXLE

The midship pump shall be located so the dimension from the centerline of the suction to the centerline of the rear axle is 97.00 inches.

FUEL FILTER/WATER SEPARATOR

The fuel system shall have a Racor GreenMAX 6600R fuel filter/water separator as a primary filter. The fuel filter shall have a drain valve and a see-through cover to allow visual inspection of fuel and filter condition. The Racor 6600R shall meet engine requirements for particulate size, collection capacity, removal efficiency, and water removal efficiency. The filter shall be capable of handling a maximum flow rate of 150 gallons per hour.

A secondary fuel filter shall be included as approved by the engine manufacturer.

An instrument panel lamp and audible alarm which indicates when water is present in the fuel-water separator shall also be included.

FUEL LINES

The fuel system supply and return lines installed from the fuel tank to the engine shall be black textile braided lines which are reinforced with braided high tensile steel wire. The fuel lines shall be connected with reusable steel fittings.

FUEL SHUTOFF VALVE

A fuel shutoff valve shall be installed in the fuel draw line at the primary fuel filter to allow the fuel filter to be changed without loss of fuel to the fuel pump.

A second fuel shutoff valve shall be installed in the fuel draw line, near the fuel tank to allow maintenance to be performed with minimal loss of fuel.

ELECTRIC FUEL PRIMER

Integral to the engine assembly is an electric lift pump that serves the purpose of pre-filter fuel priming.

FUEL TANK

The fuel tank shall have a capacity of fifty (50) gallons and shall measure 35.00 inches in width X 15.00 inches in height X 24.00 inches in length.

The baffled tank shall have a vent port to facilitate venting to the top of the fill neck for rapid filling without "blow-back" and a roll over ball check vent for temperature related fuel expansion and draw.

The tank is designed with dual draw tubes and sender flanges. The tank shall have 2.00 inch NPT fill ports for right or left hand fill. A 0.50 inch NPT drain plug shall be centered in the bottom of the tank.

The fuel tank shall be mounted below the frame, behind the rear axle. Two (2) three-piece strap hanger assemblies with "U" straps bolted midway on the fuel tank front and rear shall be utilized to allow the tank to be easily lowered and removed for service purposes. Rubber isolating pads shall be provided between the tank and the upper tank mounting brackets. Strap mounting studs through the rail, hidden behind the body shall not be acceptable.

FUEL TANK MATERIAL AND FINISH

The fuel tank shall be constructed of 12 gauge stainless steel. The exterior of the tank shall be powder coated black and then painted to match the frame components.

All powder coatings, primers and paint shall be compatible with all metals, pretreatments and primers used. The cross hatch adhesion test per ASTM D3359 Method B, results to be 5B minimum. The pencil hardness test per ASTM D3363 shall have a final post-cured pencil hardness of H-2H. The direct impact resistance test per ASTM D2794, results to be 5B minimum.

Any proposals offering painted fuel tanks with variations from the above process shall not be accepted. The film thickness of vendor supplied parts shall also be sufficient to meet the performance standards as stated above.

FUEL TANK STRAP MATERIAL

The fuel tank straps shall be constructed of #304 stainless steel. The fuel tank straps shall be powder coated black and then painted to match the frame components if possible.

FUEL TANK FILL PORT

The fuel tank fill ports shall be offset with the left fill port located in the rearward position and the right fill port located in the middle position on the fuel tank.

FUEL TANK SERVICEABILITY PROVISIONS

The chassis fuel lines shall have additional length provided so the tank can be easily lowered and removed for service purposes. The additional 8.00 feet of length shall be located above the fuel tank and shall be coiled and secured. The fuel line fittings shall be pointed towards the right side (curbside) of the chassis.

FUEL TANK DRAIN PLUG

A 0.5 inch NPT magnetic drain plug shall be centered in the bottom of the fuel tank.

FRONT AXLE

The front axle shall be a Meritor Easy Steer Non drive front axle, model number MFS-20.

The axle shall include a 3.74 inch drop and a 71.00 inch king pin intersection (KPI). The axle shall include a conventional style hub with a standard knuckle.

FRONT AXLE WARRANTY

The front axle shall be warranted by Meritor for five (5) years with unlimited miles under the general service application. Details of the Meritor warranty are provided on the PDF document attached to this option.

FRONT WHEEL BEARING LUBRICATION

The front axle wheel bearings shall be lubricated with oil. The oil level can be visually checked via clear inspection windows in the front axle hubs.

FRONT SHOCK ABSORBERS

Two (2) Bilstein inert, nitrogen gas filled shock absorbers shall be provided and installed as part of the front suspension system. The shocks shall be a monotubular design and fabricated using a special extrusion method, utilizing a single blank of steel without a welded seam, achieving an extremely tight peak-to-valley tolerance and maintains consistent wall thickness. The monotubular design shall provide superior strength while maximizing heat dissipation and shock life.

The ride afforded through the use of a gas shock is more consistent and shall not deteriorate with heat, the same way a conventional oil filled hydraulic shock would.

The Bilstein front shocks shall include a digressive working piston assembly allowing independent tuning of the compression and rebound damping forces to provide optimum ride and comfort without compromise. The working piston design shall feature fewer parts than most conventional twin tube and "road sensing" shock designs and shall contribute to the durability and long life of the Bilstein shock absorbers.

Proposals offering the use of conventional twin tube or "road sensing" designed shocks shall not be considered.

FRONT SUSPENSION

The front suspension shall include a ten (10) leaf spring pack in which the longest leaf measures 54.00 inch long and 4.00 inches wide and shall include a military double wrapped front eye. Both spring eyes shall have a case hardened threaded bushing installed with lubrication counter bore and lubrication land off cross bore with grease fitting. The spring capacity shall be rated at 21,500 pounds.

STEERING COLUMN/ WHEEL

The cab shall include a Douglas Autotech steering column which shall include a seven (7) position tilt, a 2.25 inch telescopic adjustment, and an 18.00 inch, four (4) spoke steering wheel located at the driver's position. The steering wheel shall be covered with black polyurethane foam padding.

The steering column shall contain a horn button, self-canceling turn signal switch, four-way hazard switch and headlamp dimmer switch.

ELECTRONIC POWER STEERING FLUID LEVEL INDICATOR

The power steering fluid shall be monitored electronically and shall send a signal to activate an audible alarm and visual warning in the instrument panel when fluid level falls below normal.

POWER STEERING PUMP

The hydraulic power steering pump shall be a TRW PS and shall be gear driven from the engine. The pump shall be a balanced, positive displacement, sliding vane type. The power steering system shall include an oil to air passive cooler.

FRONT AXLE CRAMP ANGLE

The chassis shall have a front axle cramp angle of 48-degrees to the left and 44-degrees to the right.

POWER STEERING GEAR

The power steering gear shall be a TRW model TAS 65 with an assist cylinder.

CHASSIS ALIGNMENT

The chassis frame rails shall be measured to insure the length is correct and cross checked to make sure they run parallel and are square to each other. The front and rear axles shall be laser aligned. The front tires and wheels shall be aligned and toe-in set on the front tires by the chassis manufacturer.

REAR AXLE

The rear axle shall be a Meritor model RS-25-160 single drive axle. The axle shall include precision forged, single reduction differential gearing, and shall have a fire service rated capacity of 27,000 pounds.

The axle shall be built of superior construction and quality components to provide the rugged dependability needed to stand up to the fire industry's demands. The axle shall include rectangular shaped, hot-formed housing with a standard wall thickness of 0.63 of an inch for extra strength and rigidity and a rigid differential case for high axle strength and reduced maintenance.

The axle shall have heavy-duty Hypoid gearing for longer life, greater strength and quieter operation. Industry-standard wheel ends for compatibility with both disc and drum brakes, and unitized oil seal technology to keep lubricant in and help prevent contaminant damage will be used.

REAR AXLE DIFFERENTIAL LUBRICATION

The rear axle differential shall be lubricated with oil.

REAR AXLE WARRANTY

The rear axle shall be warranted by Meritor for five (5) years with unlimited miles under the general service application. Details of the Meritor warranty are provided on the PDF document attached to this option.

REAR WHEEL BEARING LUBRICATION

The rear axle wheel bearings shall be lubricated with oil.

REAR AXLE DIFFERENTIAL CONTROL

A driver controlled differential lock shall be installed on the rear axle. This feature shall allow the main differential to be locked and unlocked when encountering poor road or highway conditions, where maximum traction is needed, for use at speeds no greater than 25 MPH. The differential lock shall be controlled by a locking rocker switch on the switch panel. The light on the switch shall illuminate with positive engagement of the differential control.

VEHICLE TOP SPEED

The top speed of the vehicle shall be approximately 68 MPH +/-2 MPH at governed engine RPM.

REAR SUSPENSION

The single rear axle shall feature a Reyco 79KB vari-rate, self-leveling captive slipper type conventional multi-leaf spring suspension, with 57.50 inch X 3.00 inch springs. One (1) adjustable and one (1) fixed torque rod shall be provided.

The rear suspension capacity shall be rated from 21,000 to 31,500 pounds.

TIRE INTERMITTENT SERVICE RATING

The chassis shall be rated using Intermittent Service ratings provided to the emergency

vehicle market by the tire manufacturers as the basis for determining the maximum vehicle load and speed.

FRONT TIRE

The front tires shall be Michelin 425/65R22.5 "L" tubeless radial XFE regional tread.

The front tire stamped load capacity shall be 22,800 pounds per axle with a nominal speed rating of 65 miles per hour when properly inflated to 120 pounds per square inch.

The Michelin Intermittent Service Rating maximum load capacity shall be 24,396 pounds per axle with a maximum speed of 65 miles per hour when properly inflated to 120 pounds per square inch.

The Michelin Intermittent Service Rating maximum speed capacity shall be 22,800 pounds per axle with a speed rating of 75 miles per hour when properly inflated to 120 pounds per square inch.

The Michelin Intermittent Service Rating limits the operation of the emergency vehicle to no more than fifty (50) miles of continuous operation under maximum recommended payload, or without stopping for at least twenty (20) minutes. The emergency vehicle must reduce its speed to no more than 50 MPH after the first fifty (50) miles of travel.

REAR TIRE

The rear tires shall be Michelin 12R-22.5 16PR "H" tubeless radial XDN2 all-weather tread.

The rear tire stamped load capacity shall be 27,120 pounds per axle with a nominal speed rating of 75 miles per hour when properly inflated to 120 pounds per square inch.

The Michelin Intermittent Service Rating maximum load capacity shall be 29,020 pounds per axle with a maximum speed of 75 miles per hour when properly inflated to 120 pounds per square inch.

The Michelin Intermittent Service Rating maximum speed capacity shall match the nominal speed rating.

The Michelin Intermittent Service Rating limits the operation of the emergency vehicle to no more than fifty (50) miles of continuous operation under maximum recommended payload, or without stopping for at least twenty (20) minutes. The emergency vehicle must reduce its

speed to no more than 50 MPH after the first fifty (50) miles of travel.

REAR AXLE RATIO

The rear axle ratio shall be 5.38:1.

TIRE PRESSURE INDICATOR

There shall be electronic chrome LED valve caps shipped loose for installation by the OEM which shall illuminate with a red LED when tire pressure drops 8psi provided. The valve caps are self-calibrating and set to the pressure of the tire upon installation.

FRONT WHEEL The front wheels shall be Alcoa hub piloted, 22.50 inch X 12.25 inch aluminum wheels featuring a mirror polish on the outer face. The hub piloted mounting system shall provide easy installation and shall include two-piece flange nuts.

REAR WHEEL

The outer rear wheels shall be Alcoa hub piloted, 22.50 inch X 8.25 inch aluminum wheels with a mirror polished outer surface. The inner rear wheels shall be Alcoa hub piloted, 22.50 inch X 8.25 inch aluminum wheels with bright machine finish. The hub piloted mounting system shall provide easy installation and shall include two-piece flange nuts.

BALANCE WHEELS AND TIRES

All of the wheels and tires, including any spare wheels and tire assemblies, shall include Counteract brand balancing beads.

WHEEL TRIM

The front wheels shall include stainless steel lug nut covers and stainless steel baby moons shipped loose with the chassis for installation by the apparatus builder. The baby moons shall have cutouts for oil seal viewing when applicable.

The rear wheels shall include stainless steel lug nut covers and band mounted spring clip stainless steel high hats shipped loose with the chassis for installation by the apparatus builder. The lug nut covers, baby moons, and high hats shall be RealWheels® brand constructed of 304L grade, non-corrosive stainless steel with a mirror finish. Each wheel trim component shall meet D.O.T. certification.

TIRE CHAINS

Onspot brand six (6) strand automatic ice chains shall be installed on the rear axle of the chassis to provide instant traction while traveling on ice and snow at speeds below 35 MPH.

TIRE CHAINS ACTIVATION

The tire chain system shall be activated by a locking switch on the dash to deter accidental activation. The light on the switch shall illuminate when the tire chains are engaged. The tire chains shall be interlocked with the transmission and shall engage only if the vehicle is traveling 30 MPH or less. After traveling over 30 MPH, the vehicle must be reduced to a speed below 5 MPH for the tire chains to be engaged or re-engaged.

BRAKE SYSTEM

A rapid build-up air brake system shall be provided. The air brakes shall include, at a minimum, a two (2) air tank, three (3) reservoir system with a total of 4152 cubic inch of air capacity. A floor mounted treadle valve shall be mounted inside the cab for graduated control of applying and releasing the brakes. An inversion valve shall be installed to provide a service brake application in the unlikely event of primary air supply loss. All air reservoirs provided on the chassis shall be labeled for identification. The rear axle spring brakes shall automatically apply in any situation when the air pressure falls below 25 PSI and shall include a mechanical means for releasing the spring brakes when necessary. An audible alarm shall designate when the system air pressure is below 60 PSI.

A four (4) sensor, four (4) modulator anti-lock braking system (ABS) shall be installed on the front and rear axles in order to prevent the brakes from locking or skidding while braking during hard stops or on icy or wet surfaces. This in turn shall allow the driver to maintain steering control under heavy braking and in most instances, shorten the braking distance. The electronic monitoring system shall incorporate diagonal circuitry which shall monitor wheel speed during braking through a sensor and tone ring on each wheel. A dash mounted ABS lamp shall be provided to notify the driver of a system malfunction. The ABS system shall automatically disengage the auxiliary braking system device when required. The speedometer screen shall be capable of reporting all active defaults using PID/SID and FMI standards. Additional safety shall be accommodated through Automatic Traction Control (ATC) which shall be installed on the single rear axle. The ATC system shall apply the ABS when the drive wheels lose traction. The system shall scale the electronic engine throttle back to prevent wheel spin while accelerating on ice or wet surfaces.

A momentary rocker style switch shall be provided and properly labeled "mud/snow". When the switch is pressed once, the system shall allow a momentary wheel slip to obtain traction under extreme mud and snow conditions. During this condition the ATC light and the light on the rocker switch shall blink continuously notifying the driver of activation. Pressing the switch again shall deactivate the mud/snow feature.

The Electronic Stability Control (ESC) unit is a functional extension of the electronic braking system. It is able to detect any skidding of the vehicle about its vertical axis as well as any rollover tendency. The control unit comprises an angular-speed sensor that measures the vehicle's motion about the vertical axis, caused, for instance, by cornering or by skidding on a slippery road surface. An acceleration sensor measures the vehicle's lateral acceleration. The Controller Area Network (CAN) bus provides information on the steering angle. On the basis of lateral acceleration and steering angle, an integrated microcontroller calculates a theoretical angular speed for the stable vehicle condition.

FRONT BRAKES

The front brakes shall be Meritor EX225 Disc Plus disc brakes with 17.00 inch vented rotors.

REAR BRAKES

The rear brakes shall be Meritor 16.50 inch X 7.00 inch S-cam drum type. The brakes shall feature a cast iron shoe.

PARK BRAKE

Upon application of the push-pull valve in the cab, the rear brakes will engage via mechanical spring force. This is accomplished by dual chamber rear brakes, satisfying the FMVSS parking brake requirements.

PARK BRAKE CONTROL

A Meritor-Wabco manual hand control push-pull style valve shall operate the parking brake. The parking brake actuation valve shall be mounted to the left side of the engine tunnel integrated into the transmission shift pod console within easy access of the driver.

REAR BRAKE SLACK ADJUSTERS

The rear brakes shall include Meritor automatic slack adjusters installed on the axle which features a simple, durable design offering reduced weight. The automatic slack adjusters shall feature a manual adjusting nut which cannot inadvertently be backed off and threaded grease fittings for easy serviceability.

AIR DRYER

The brake system shall include a Wabco System Saver 1200 air dryer with an integral 100 watt heater with a Metri-Pack sealed connector. The air dryer incorporates an internal turbo cutoff valve that closes the path between the air compressor and air dryer purge valve during the compressor "unload" cycle. The turbo cutoff valve allows purging of moisture and contaminants without the loss of turbo boost pressure. The air dryer shall be located on the

right hand frame rail forward of the front wheel behind the right hand cab step.

FRONT BRAKE CHAMBERS

The front brakes shall be provided with MGM type 24 long stroke brake chambers.

REAR BRAKE CHAMBERS

The rear axle shall include TSE 30/36 brake chambers which shall convert the energy of compressed air into mechanical force and motion. This shall actuate the brake camshaft, which in turn shall operate the foundational brake mechanism forcing the brake shoes against the brake drum. The TSE Type 36 brake chamber has a 36.00 square inch effective area.

AIR COMPRESSOR

The air compressor provided for the engine shall be a naturally aspirated Wabco® SS440 single cylinder pass-through drive type compressor which shall be capable of producing 26.0 CFM at 1200 engine RPMs. The compressor shall include an aluminum cylinder head which shall improve cooling, reduce weight and decrease carbon formation.

AIR GOVERNOR

An air governor shall be provided to control the cut-in and cut-out pressures of the engine mounted air compressor. The governor shall be calibrated to meet FMVSS requirements. The air governor shall be located on the air dryer bracket.

MOISTURE EJECTORS

Manual pet-cock type drain valves shall be installed on all reservoirs of the air supply system.

AIR SUPPLY LINES

The air system on the chassis shall be plumbed with color coded reinforced nylon tubing air lines. The primary (rear) brake line shall be green, the secondary (front) brake line red, the parking brake line orange and the auxiliary (outlet) will be blue.

Push to connect type fittings shall be used on the nylon tubing. All drop hoses shall include fiber reinforced neoprene covered hoses.

AIR INLET CONNECTION

A Kussmaul air automatic eject connection for the shoreline air inlet shall be supplied.

AIR INLET/ AUTO EJECT CONNECTION COVER

The air auto eject connection shall be yellow in color.

AIR INLET LOCATION

The air inlet shall be installed on the left hand side of the cab above the wheel well in the forward position.

AIR INLET/ OUTLET FITTING TYPE

The air connector supplied shall be a 0.25 inch size Tru-Flate Interchange style manual connection which is compatible with Milton 'T' style, Myers 0.25 inch Automotive style and Parker 0.25 inch 10 Series connectors.

REAR AIR TANK MOUNTING

If a combination of wheel base, air tank quantity, or other requirements necessitate the location of one or more air tanks to be mounted rear of the fuel tank, these tank(s) will be mounted perpendicular to frame.

FRONT RECEIVER HITCH

The chassis shall have a 9,500 pound Class III receiver hitch mounted in the center under the front bumper. The receiver shall be flush with the front face of the bumper.

WHEELBASE

The chassis wheelbase shall be 175.50 inches.

REAR OVERHANG

The chassis rear overhang shall be 50.50 inches.

FRAME

The frame shall consist of double rails running parallel to each other with cross members forming a ladder style frame. The frame rails shall be formed in the shape of a "C" channel, with the outer rail measuring 10.25 inches high X 3.50 inches deep upper and lower flanges X 0.38 inches thick with an inner channel of 9.44 inches high X 3.13 inches deep and 0.38 inches thick. Each rail shall be constructed of 110,000 psi minimum yield high strength low alloy steel. Each double rail section shall be rated by a Resistance Bending Moment (RBM) minimum of 3,213,100 inch pounds and have a minimum section modulus of 29.21 cubic inches. The frame shall measure 35.00 inches in width.

Proposals calculating the frame strength using the "box method" shall not be considered.

Proposals including heat treated rails shall not be considered. Heat treating frame rails produces rails that are not uniform in their mechanical properties throughout the length of the rail. Rails made of high strength, low alloy steel are already at the required yield strength prior to forming the rail. A minimum of seven (7) fully gusseted 0.25 inch thick cross members shall be installed. The inclusion of the body mounting, or bumper mounting shall not be considered as a cross member. The cross members shall be attached using zinc coated grade 8 fasteners. The bolt heads shall be flanged type, held in place by distorted thread flanged lock nuts. Each cross member shall be mounted to the frame rails utilizing a minimum of 0.25 inch thick gusset reinforcement plates at all corners balancing the area of force throughout the entire frame. .

Any proposals not including additional reinforcement for each cross member shall not be considered.

All relief areas shall be cut in with a minimum 2.00 inch radius at intersection points with the edges ground to a smooth finish to prevent a stress concentration point.

REAR TOW DEVICE

The frame rails shall contain (6) holes per frame in a pattern specified by the OEM for mounting Spartan ERV tow eyes at the rear of the frame at a location defined by the OEM.

FRAME PAINT

The frame rails shall be hot dip galvanized and powder coated prior to assembly and attachment of any components. The components that shall be galvanized shall include:

- Main frame "C" channel or channels

The frame parts which are not galvanized shall be powder coated prior to any attachment of components. Parts which shall be powder coated shall include but are not limited to:

- Steering gear bracket
- Front splayed rails and fish plates
- Bumper extensions
- Cross members
- Cross member gussets
- Fuel tank mounting brackets
- Fuel tank straps (unless material/finish is specified in 3130 subcat)
- Air tanks (unless color coded tanks are specified in 3205 subcat)
- Air tank mounting brackets
- Exhaust mounting brackets

- Air cleaner skid plate
- Radiator skid plate
- Battery supports, battery trays and battery covers

Other non-galvanized under carriage components which are received from the suppliers with coatings already applied shall include but are not limited to:

- Suspension components
- Front and rear axles

All powder coatings, primers and paint used on the non-galvanized components shall be compatible with all metals, pretreatments and primers used. The cross hatch adhesion test per ASTM D3359 shall not have a fail of more than ten (10) squares. The pencil hardness test per ASTM D3363 shall have a final post-cured pencil hardness of H-2H. The direct impact resistance test per ASTM D2794 shall have an impact resistance of 120.00 inches per pound at 2 mils.

The chassis under carriage consisting of frame, axles, driveline running gear, air tanks and other assorted chassis mounted components shall then be painted gloss black. Paint shall be applied prior to airline and electrical wiring installation.

FRAME ASSEMBLY STRUCTURAL

Purchaser shall receive a Frame Assembly Structural Fifty (50) Years or 250,000 Miles limited warranty in accordance with, and subject to, warranty certificate RFW0305. The warranty certificate is incorporated by reference into this proposal, and included with this proposal or available upon request.

FRAME RAIL CORROSION

Purchaser shall receive a Frame Rail Corrosion (Zinc Plate and Powder Coat) Twenty Five (25) Years or 150,000 Miles limited warranty in accordance with, and subject to, warranty certificate RFW0316. The warranty certificate is incorporated by reference into this proposal, and included with this proposal or available upon request.

FRAME COMPONENTS CORROSION

Purchaser shall receive a Frame Components Corrosion (Powder Coat) Three (3) Years or 48,000 Miles limited warranty in accordance with, and subject to, warranty certificate RFW0313. The warranty certificate is incorporated by reference into this proposal, and included with this proposal or available upon request.

FRONT BUMPER

The chassis shall be equipped with a severe duty front bumper constructed from structural steel channel. The bumper material shall be 0.38 thick ASTM A36 steel which shall measure 12.00 inches high with a 3.05 inch flange and shall be 99.00 inches wide with angled front corners.

The bumper shall be primed and painted as specified.

FRONT BUMPER EXTENSION LENGTH

The front bumper shall be extended approximately 18.00 inches ahead of the cab.

FRONT BUMPER PAINT

The front bumper shall be painted the same as the lower cab color.

FRONT BUMPER SUCTION PROVISION

The bumper apron shall include a 5.00 inch stainless steel pipe intended for use as a suction intake for the pump. The suction pipe shall be routed from the right hand front bumper area to the area rear of the front axle near the back of the cab.

The front of the suction pipe shall be designed to extend 2.00 inches horizontally through the

face of the bumper on the right hand side.

The forward end of the suction pipe shall be finished with a 5.00 inch National Pipe Thread (NPT). The rear of the suction shall include a Victaulic groove for connecting to the pump plumbing. The suction pipe shall also include a 0.50 inch NPT port intended as a primer assist connection.

The apparatus manufacturer shall plumb the suction pipe to the pump and shall provide all valves as required.

FRONT BUMPER APRON

The 18.00 inch extended front bumper shall include an apron constructed of 0.19 inch thick embossed aluminum tread plate.

The apron shall be installed between the bumper and the front face of the cab affixed using stainless steel bolts attaching the apron to the top bumper flange.

MECHANICAL SIREN

The front bumper shall include an electro mechanical Federal Q2B™ siren, which shall be streamlined, chrome-plated and shall produce 123 decibels of sound at 10.00 feet. The Q2B™ siren produces a distinctive warning sound that is recognizable at long distances. A unique clutch design provides a longer coast down sound while reducing the amp draw to 100 amps. The siren shall measure 10.50 inches wide X 10.00 inches high X 14.00 inches deep. The siren shall include mounting hardware designed to recess or flush mount.

MECHANICAL SIREN LOCATION

The siren shall be recess mounted on the left side of the front fascia of the bumper approximately in the center of the flat surface between the bumper radius and the frame rail.

MECHANICAL SIREN ACCESSORIES

The front of the siren shall include (2) stainless steel flat bars approximately 1.00 inch wide by 19.00 inches long. Each bar shall be placed vertically on the right and left side of the siren face wrapping around towards the back of the siren into the bumper extension offering protection to the Q2B siren.

AIR HORN

The front bumper shall include two (2) Hadley brand E-Tone air horns which shall measure 18.00 inches long with a 6.00 inch round flare. The air horns shall be trumpet style with a chrome finish on the exterior and a painted finish deep inside the trumpet.

AIR HORN LOCATION

The air horns shall be recess mounted in the front bumper fascia between the frame rails in the right and left outboard positions.

AIR HORN RESERVOIR

One (1) air reservoir, with a 1200 cubic inch capacity, shall be installed on the chassis to act as a supply tank for operating air horns. The reservoir shall be isolated with a 90 PSI pressure protection valve on the reservoir supply side to prevent depletion of the air to the air brake system.

ELECTRONIC SIREN SPEAKER

There shall be one (1) Cast Products Inc. model SA4301, 100 watt speaker provided. The speaker shall measure 6.20 inches tall X 7.36 inches wide X 3.06 inches deep. The speaker shall include a flat mounting flange which shall be polished aluminum.

ELECTRONIC SIREN SPEAKER LOCATION

The electronic siren speaker shall be located on the front bumper face in the center position between the frame rails.

CAB TILT SYSTEM

The entire cab shall be capable of tilting approximately 45-degrees to allow for easy maintenance of the engine and transmission. The cab tilt pump assembly shall be located on the right side of the chassis above the battery box.

The electric-over-hydraulic lift system shall include an ignition interlock and red cab lock down indicator lamp on the tilt control which shall illuminate when holding the "Down" button to indicate safe road operation.

It shall be necessary to activate the master battery switch and set the parking brake in order to tilt the cab. As a third precaution the ignition switch must be turned off to complete the cab tilt interlock safety circuit.

Two (2) spring-loaded hydraulic hold down hooks located outboard of the frame shall be installed to hold the cab securely to the frame. Once the hold-down hooks are set in place, it shall take the application of pressure from the hydraulic cab tilt lift pump to release the hooks

Two (2) cab tilt cylinders shall be provided with velocity fuses in each cylinder port. The cab tilt pivots shall be 1.90 inch ball and be anchored to frame brackets with 1.25 inch diameter studs.

A steel safety channel assembly, painted safety yellow shall be installed on the right side cab lift cylinder to prevent accidental cab lowering. The safety channel assembly shall fall over the lift cylinder when the cab is in the fully tilted position. A cable release system shall also be provided to retract the safety channel assembly from the lift cylinder to allow the lowering of the cab.

CAB TILT AUXILIARY PUMP

A manual cab tilt pump module shall be attached to the cab tilt pump housing.

CAB TILT LIMIT SWITCH

A cab tilt limit switch shall be installed. The switch will effectively limit the travel of the cab when being tilted. The limit adjustment of the switch shall be preset by the chassis manufacturer to prevent damage to the cab or any bumper mounted option mounted in the cab tilt arc. Further adjustment to the limit by the apparatus manufacturer shall be available to accommodate additional equipment.

CAB TILT CONTROL RECEPTACLE

The cab tilt control cable shall include a receptacle which shall be temporarily located on the right hand chassis rail rear of the cab to provide a place to plug in the cab tilt remote control pendant. The tilt pump shall include 8.00 feet of cable with a six (6) pin Deutsch receptacle with a cap. The remote control pendant shall include 20.00 feet of cable with a mating Deutsch connector. The remote control pendant shall be shipped loose with the chassis.

CAB TILT LOCK DOWN INDICATOR

The cab dash shall include a message located within the dual air pressure gauge which shall alert the driver when the cab is unlocked and ajar. The alert message shall cease to be displayed when the cab is in the fully lowered position and the hold down hooks are secured and locked to the cab mounts.

In addition to the alert message an audible alarm shall sound when the cab is unlocked and ajar with the parking brake released.

CAB WINDSHIELD

The cab windshield shall have a surface area of 2825.00 square inches and be of a two (2) piece wraparound design for maximum visibility.

The glass utilized for the windshield shall include standard automotive tint. The left and right windshield shall be fully interchangeable thereby minimizing stocking and replacement costs. Each windshield shall be installed using black self locking window rubber.

GLASS FRONT DOOR

The front cab doors shall include a window which is 27.00 inches in width X 26.00 inches in height. These windows shall have the capability to roll down completely into the door housing. This shall be accomplished using electric actuation. The left and right front door windows shall be controlled using a switch on each respective side inner door panel. The driver's door shall include a switch for each powered door window in the cab. There shall be an irregular shaped fixed window which shall measure 2.50 inches wide at the top, 8.00 inches wide at the bottom X 26.00 inches in height, more commonly known as "cozy glass" ahead of the front door roll down windows. The windows shall be mounted within the frame of the front doors trimmed with a black anodized ring on the exterior.

GLASS TINT FRONT DOOR

The windows located in the left and right front doors shall have a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

GLASS REAR DOOR RH

The rear right hand side crew door shall include a window which is 27.00 inches in width X 26.00 inches in height. The window shall be a powered type and shall be controlled by a switch on the door panel ledge and on the driver's control panel.

GLASS TINT REAR DOOR RIGHT HAND The window located in the right hand side rear door shall include a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

GLASS REAR DOOR LH

The rear left hand side crew door shall include a window which is 27.00 inches in width X 26.00 inches in height. The window shall be a powered type and shall be controlled by a switch on the door panel ledge and on the driver's control panel.

GLASS TINT REAR DOOR LEFT HAND

The window located in the left hand side rear door shall include a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

GLASS SIDE MID RH

The cab shall include a window on the right side behind the front and ahead of the crew door which shall measure 16.00 inches wide X 26.00 inches high. This window shall be fixed within this space and shall be rectangular in shape. The window shall be mounted using self locking window rubber. The glass utilized for this window shall include a green automotive tint unless otherwise noted.

GLASS TINT SIDE MID RIGHT HAND

The window located on the right hand side of the cab between the front and rear doors shall include a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

GLASS SIDE MID LH

The cab shall include a window on the left side behind the front door and ahead of the crew door and above the wheel well which shall measure 16.00 inches wide X 26.00 inches high. This window shall be fixed within this space and shall be rectangular in shape. The window shall be mounted using self locking window rubber. The glass utilized for this window shall include a green automotive tint unless otherwise noted.

GLASS TINT SIDE MID LEFT HAND

The window located on the left hand side of the cab between the front and rear doors shall include a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

CLIMATE CONTROL

A ceiling mounted combination defroster and cabin heating and air conditioning system shall be located above the engine tunnel area. The system covers and plenums shall be of severe duty design made of aluminum which shall be coated with a customer specified interior paint. The design of the system's covers shall provide quick access to washable air intake filters as well as easy access to other serviceable items.

Six (6) adjustable louvers shall provide comfort for the front seat occupants and ten (10) adjustable louvers shall provide comfort for the rear crew occupants. The plenum shall be shortened to terminate in the mid crew area on cabs with 10.00 inch raised roofs and greater. This shortened plenum shall allow for the customer to utilize the upper rear center wall for compartmentation, equipment, or apparatus operations.

Separate front and rear blower motors shall be of brushless design and shall be controlled independently. It shall be capable of reducing the interior cabin air temperature from 122° F (+/- 3° F) to 80° F in thirty minutes with 50% relative humidity and full solar load as described in SAE J2646.

The system shall also provide heater pull up performance which meets or exceeds the performance requirements of SAE J1612 as well as defrost performance that meets or exceeds the performance requirements of SAE J381.

A gravity drain system shall be provided that is capable of evacuating condensate from the vehicle while on a slope of up to a 13% grade in any direction.

The air conditioning system plumbing shall be a mixture of custom bent zinc coated steel fittings and Aeroquip flexible hose with Aeroquip EZ-Clip fittings.

The overhead heater/defroster plumbing shall include an electronic flow control valve that re-directs hot coolant away from the evaporator, via a bypass loop, as the temperature control is moved toward the cold position.

Any component which needs to be accessed to perform system troubleshooting shall be accessible by one person using basic hand tools. Regularly serviced items shall be replaceable by one person using basic hand tools.

CLIMATE CONTROL DRAIN

The climate control system shall include a gravity drain for water management. The gravity drain shall remove condensation from the air conditioning system without additional mechanical assistance.

CLIMATE CONTROL ACTIVATION

The heating, defrosting and air conditioning controls shall be in the center dash driver's switch panel, in a position which is easily accessible to the driver. The climate control shall be activated by a rotary switch.

HVAC OVERHEAD COVER PAINT

The overhead HVAC cover shall be painted with a multi-tone silver gray texture finish.

A/C CONDENSER LOCATION

A roof mounted A/C condenser shall be installed centered on the cab forward of the raised roof against the slope rise.

A/C COMPRESSOR

The air-conditioning compressor shall be a belt driven, engine mounted compressor. The compressor shall be compatible with R134-a refrigerant.

UNDER CAB INSULATION

The underside of the cab tunnel surrounding the engine shall be lined with multi-layer insulation, engineered for application inside diesel engine compartments.

The insulation shall act as a noise barrier, absorbing noise thus keeping the decibel level in the cab well within NFPA recommendations. As an additional benefit, the insulation shall assist in sustaining the desired temperature within the cab interior.

The engine tunnel insulation shall measure approximately 0.30 inch thick including a multi-layer foil faced glass cloth and polyester fiber layer. The foil surface acts as protection against heat, moisture and other contaminants. The insulation shall meet or exceed FMVSS 302 flammability test.

The insulation shall be cut precisely to fit each section and sealed for additional heat and sound deflection. The insulation shall be held in place by acrylic pressure sensitive adhesive.

INTERIOR TRIM FLOOR

The floor of the cab shall be covered with a multi-layer mat consisting of 0.25 inch thick sound absorbing closed cell foam with a 0.06 inch thick non-slip vinyl surface with a pebble grain finish. The covering shall be held in place by a pressure sensitive adhesive and aluminum trim molding. All exposed seams shall be sealed with silicone caulk matching the color of the floor mat to reduce the chance of moisture and debris retention.

INTERIOR TRIM

The cab interior shall include trim on the front ceiling, rear crew ceiling, and the cab walls. It shall be easily removable to assist in maintenance. The trim shall be constructed of insulated vinyl over a hard board backing.

REAR WALL INTERIOR TRIM

The rear wall of the cab shall be trimmed with vinyl.

HEADER TRIM

The cab interior shall feature header trim over the driver and officer dash constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum.

TRIM CENTER DASH

The main center dash area shall be constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum plate. There shall be four (4) holes located on the top of the dash near each outer edge of the electrical access cover for ventilation. The center dash electrical access cover shall include a gas cylinder stay which shall hold the cover open during maintenance.

TRIM LH DASH

The left hand dash shall be constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum plate for a perfect fit around the instrument panel. For increased occupant protection the extreme duty left hand dash utilizes patent pending break away technology to reduce rigidity in the event of a frontal crash. The left hand dash shall offer lower vertical surface area to the left and right of the steering column to accommodate control panels.

TRIM RH DASH

The right hand dash shall be constructed of 5052-H32 Marine Grade, 0.13 of an inch thick aluminum plate and shall include a glove compartment with a hinged door and a Mobile Data Terminal (MDT) provision. The glove compartment size will measure 14.00 inches wide X 4.50 inches high X 5.88 inches deep. The MDT provision shall be provided above the glove compartment.

ENGINE TUNNEL TRIM

The cab engine tunnel shall be covered with a multi-layer mat consisting of 0.25 inch closed cell foam with a 0.06 inch thick non-slip vinyl surface with a pebble grain finish. The mat shall be held in place by pressure sensitive adhesive. The engine tunnel mat shall be trimmed with anodized aluminum stair nosing trim for an aesthetically pleasing appearance.

ENGINE TUNNEL ACCESSORIES

The engine tunnel shall include an aluminum plate for mounting accessories such as brackets for flashlights, etc. The plate shall be mounted above the engine tunnel with 0.50 inch thick spacers so wires can be routed between the plate and the engine tunnel. The mounting surface

shall be located as far forward on the engine cover as possible and be as large as possible between the radius edges of the tunnel. The mounting plate shall be 0.38 of an inch thick and shall be coated the same as the interior metal surfaces of the cab.

The engine tunnel shall also feature a fabricated aluminum console which shall include a large storage bin with dividers and a map compartment. There shall be two (2) cup holders included in the console. The console shall be installed on top of the engine tunnel accessory plate and located as far rearward on the engine tunnel as possible.

POWER POINT DASH MOUNT

The cab interior shall include (2) Blue Sea dual universal serial bus (USB) charging receptacles in the cab dash switch panel to provide a power source for USB chargeable electrical equipment. The USB port shall be capable of a 5 Volt-4.8 amp total output. The receptacles shall be wired battery direct.

STEP TRIM

Each cab entry door shall include a three step entry. The first step closest to the ground shall be constructed of SAE 304 stainless steel with embossed perforations and diamond shaped cutout. The perforations and cutouts shall allow water and other debris to flow through rather than becoming trapped within the stepping surface. The step shall feature a splash guard to reduce water and debris from splashing in to the step. The splash guard shall have drainage holes beneath the back of the step to allow debris and water to flow through rather than becoming trapped within the stepping surface. The stainless steel material shall have a number 8 mirror finish. The lower step shall be mounted to a frame which is integral with the construction of the cab for rigidity and strength. The middle step shall be integral with the cab construction and shall be trimmed with a Flex-Tred® adhesive grit surface material.

UNDER CAB ACCESS DOOR

The cab shall include an aluminum access door in the left crew step riser painted to match the cab interior paint with a push and turn latch. The under cab access door shall provide access to the diesel exhaust fluid fill.

INTERIOR DOOR TRIM

The interior trim on the doors of the cab shall consist of an aluminum panel constructed of Marine Grade 5052-H32 0.13 of an inch thick aluminum plate. The door panels shall include a painted finish.

DOOR TRIM CUSTOMER NAMEPLATE

The interior door trim on the front doors shall include a customer nameplate which states the vehicle was custom built for their Department

CAB DOOR TRIM REFLECTIVE

The interior of each door shall include high visibility reflective tape. A white reflective tape shall be provided vertically along the rear outer edge of the door. The lowest portion of each door skin shall include a reflective tape chevron with red and white stripes.. The chevron tape shall measure 6.00 inches in height.

INTERIOR GRAB HANDLE "A" PILLAR

There shall be two (2) rubber covered 11.00 inch grab handles installed inside the cab, one on each "A" post at the left and right door openings. The left handle shall be located 7.88 inches above the bottom of the door window opening and the right handle shall be located 2.88 inches above the bottom of the door window opening. The handles shall assist personnel in entering and exiting the cab.

INTERIOR GRAB HANDLE FRONT DOOR

Each front door shall include one (1) ergonomically contoured 9.00 inch cast aluminum handle mounted horizontally on the interior door panels. The handles shall feature a textured

black powder coat finish to assist personnel entering and exiting the cab.

INTERIOR GRAB HANDLE REAR DOOR

A black powder coated cast aluminum assist handle shall be provided on the inside of each rear crew door. A 30.00 inch long handle shall extend horizontally the width of the window just above the window sill. The handle shall assist personnel in exiting and entering the cab.

INTERIOR REAR WALL COMPARTMENT

The cab shall include a compartment located in the center of the rear wall of the cab. This compartment shall measure 48.00 inches high X 32.00 inches wide X 18.00 inches deep. The compartment shall be accessible from the interior of the cab through a ROM Series IV roll up style door.

The compartment shall include two (2) aluminum shelves which shall be secured using Unistrut® channel on two (2) sides of the interior walls of the compartment. The shelves shall feature a 1.00 inch tall lip around the edges.

INTERIOR REAR WALL COMPARTMENT INTERIOR FINISH

The interior of the interior rear wall compartment shall have a DA sanded finish.

INTERIOR REAR WALL COMPARTMENT LIGHTING

There shall be one (1) On-scene brand Access LED strip light installed to illuminate the interior compartment at the rear wall inside the crew area of the cab. The strip light shall be activated automatically by opening the compartment door.

INTERIOR SOFT TRIM COLOR

The cab interior soft trim surfaces shall be gray in color.

INTERIOR TRIM SUNVISOR

The header shall include two (2) sun visors, one each side forward of the driver and officer seating positions above the windshield. Each sun visor shall be constructed of Masonite and covered with padded vinyl trim.

INTERIOR FLOOR MAT COLOR

The cab interior floor mat shall be gray in color.

CAB PAINT INTERIOR DOOR TRIM

The inner door panel surfaces shall be painted with multi-tone silver gray texture finish.

HEADER TRIM INTERIOR PAINT

The metal surfaces in the header area shall be coated with multi-tone silver gray texture finish.

TRIM CENTER DASH INTERIOR PAINT

The entire center dash shall be coated with multi-tone silver gray texture finish. Any accessory pods attached to the dash shall also be painted this color.

TRIM LH DASH INTERIOR PAINT

The left hand dash shall be painted with a multi-tone silver gray texture finish.

TRIM RIGHT HAND DASH INTERIOR PAINT

The right hand dash shall be painted with multi-tone silver gray texture finish.

ENGINE TUNNEL ACCESSORIES PAINTThe engine tunnel accessories shall be painted with multi-tone silver gray texture finish.

DASH PANEL GROUP

The main center dash area shall include three (3) removable panels located one (1) to the right of the driver position, one (1) in the center of the dash and one (1) to the left of the officer position. The center panel shall be within comfortable reach of both the driver and officer.

SWITCHES CENTER PANEL

The center dash panel shall include twelve (12) rocker switch positions in a six (6) over six (6) switch configuration in the left portion of the panel.

A rocker switch with a blank legend installed directly above shall be provided for any position without a switch and legend designated by a specific option. The non-specified switches shall be two-position, black switches with a green indicator light. Each blank switch legend can be custom engraved by the body manufacturer. All switch legends shall have backlighting provided.

SWITCHES LEFT PANEL

The left dash panel shall include ten (10) switches. There shall be six (6) switches across the top of the panel and four (4) across the bottom of the panel offset left. Five (5) of the top row of switches shall be rocker type and the left one (1) shall be the headlight switch. Two (2) of the lower row of switches shall be rocker type and the left two (2) shall be the windshield wiper/washer control switch and instrument lamp dimmer switch

A rocker switch with a blank legend installed directly above shall be provided for any position not designated by a specific option. The non-designated switches shall be two-position, black switches with a green indicator light. Each blank switch legend can be custom engraved by the body manufacturer. All switch legends shall have backlighting provided.

SWITCHES RIGHT PANEL

The right dash panel shall include three (3) rocker switch positions in a single row configuration.

A rocker switch with a blank legend installed directly above shall be provided for any position without a switch and legend designated by a specific option. The non-specified switches shall be two-position, black switches with a green indicator light. Each blank switch legend can be custom engraved by the body manufacturer. All switch legends shall have backlighting provided.

SEAT BELT WARNING

A Weldon seat belt warning system, integrated with the Vehicle Data Recorder system, shall be installed for each seat within the cab. The system shall activate a digital seat position indicator with a seat position legend and integrated audible alarm in the switch panel.

The warning system shall activate when any seat is occupied with a minimum of 60 pounds and the corresponding seat belt remains unfastened. The warning system shall also activate when any seat is occupied and the corresponding seat belt was fastened in an incorrect sequence. Once activated, the visual indicators and applicable audible alarm shall remain active until all occupied seats have the seat belts fastened.

SWITCHES RIGHT PANEL

The right dash panel shall include three (3) rocker switch positions in a single row configuration.

A rocker switch with a blank legend installed directly above shall be provided for any position without a switch and legend designated by a specific option. The non-specified switches shall be two-position, black switches with a green indicator light. Each blank switch legend can be custom engraved by the body manufacturer. All switch legends shall have backlighting provided.

SEAT BELT WARNING

A Weldon seat belt warning system, integrated with the Vehicle Data Recorder system, shall be installed for each seat within the cab. The system shall activate a digital seat position indicator with a seat position legend and integrated audible alarm in the switch panel.

The warning system shall activate when any seat is occupied with a minimum of 60 pounds

and the corresponding seat belt remains unfastened. The warning system shall also activate when any seat is occupied and the corresponding seat belt was fastened in an incorrect sequence. Once activated, the visual indicators and applicable audible alarm shall remain active until all occupied seats have the seat belts fastened.

SEAT MATERIAL

The Bostrom Firefighter seats shall include a covering of extra high strength, wear resistant fabric made of durable low seam Durawear Plus™ ballistic polyester. A PVC coating shall be bonded to the back side of the material to help protect the seats from UV rays and from being saturated or contaminated by fluids. Durawear Plus™ meets or exceeds specification of the common trade name Imperial 1800. The material meets FMVSS 302 flammability requirements.

If applicable, Theatre style seats located in the cab shall be high strength, wear resistant fabric made of durable ballistic polyester. A PVC coating shall be bonded to the back side of the material to help protect the seats from UV rays and from being saturated or contaminated by fluids. Common trade names for this material are Imperial 1200 and Durawear.

SEAT COLOR

All seats supplied with the chassis shall be gray in color. All seats shall include red seat belts.

SEAT DRIVER

The driver's seat shall be an H.O. Bostrom 500 Series Firefighter Sierra model seat. The seat shall feature eight-way electric positioning. The eight positions shall include up and down, fore and aft with 8.00 inches of travel, back angle adjustment and seat rake adjustment. The seat shall feature integral springs to isolate shock.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt, automatic retractor and buckle as an integral part of the seat assembly. The ABTS feature shall also include the RiteHite™ shoulder adjustment feature to provide enhanced comfort and safety by allowing customized seat belt fit.

The minimum vertical dimension from the seat H-point to the ceiling for this belted seating position shall be 35.00 inches measured with the seat height adjusted to the lowest position of travel.

This model of seat shall have successfully completed the static load tests set forth by FMVSS 207, 209, and 210 in effect at the time of manufacture. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity.

The materials used in construction of the seat shall also have successfully completed testing with regard to the flammability of materials used in the occupant compartments of motor

vehicles as outlined in FMVSS 302, of which dictates the allowable burning rate of materials in the occupant compartments of motor vehicles.

SEAT BACK DRIVER

The driver's seat shall include a standard seat back incorporating the all belts to seat feature (ABTS). The seat back shall feature a contoured head rest.

SEAT MOUNTING DRIVER

The driver's seat shall be installed in an ergonomic position in relation to the cab dash.

OCCUPANT PROTECTION DRIVER

The driver's position shall be equipped with the IMMI 4Front and RollTek™ Systems which shall secure belted occupants and increase the survivable space within the cab. The 4Front and RollTek™ Systems shall selectively deploy integrated systems to protect against injuries in qualifying frontal impact, and rollover events.

The Driver's seating area protection shall include:

- Drivers airbag **DAB** - inflates a steering wheel airbag to protect the head and neck of the driver.
 - Driver's knee airbag **DKAB** - inflating knee bolster airbags to protect the knees.
 - Integrated roll sensor **IRS** - detects an imminent rollover, activates protective devices and records crash events.
 - Integrated belt pretension **IBP** - device for mechanical and/or electrical seats tightens the seat belt, securing driver in seat and positions driver for contact with seat integrated head cushion side roll airbag.
- Inflatable head cushion seat integrated side roll airbag **SRA** - protects driver's head/neck and shields driver from dangerous surfaces.

SEAT OFFICER

The officer's seat shall be a H.O. Bostrom 500 Series Sierra seat model. The seat shall feature a tapered and padded seat, and cushion. The seat shall be mounted in a fixed position.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant. The ABTS feature shall also include the RiteHite™ shoulder adjustment feature to provide enhanced comfort and safety by allowing customized seat belt fit.

The minimum vertical dimension from the seat H-point to the ceiling for this belted seating position shall be 35.00 inches.

This model of seat shall have successfully completed the static load tests by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have successfully completed the dynamic sled testing using FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

SEAT BACK OFFICER

The officer's seat shall feature a SecureAll™ SCBA locking system which shall be one bracket model and store most U.S. and International SCBA brands and sizes while in transit

or for storage within the seat back. The bracket shall be easily adjustable for all SCBA brands and cylinder diameters. All adjustment points shall utilize similar hardware and adjustments shall be made with one tool.

The bracket shall be adjustable to compensate for different cylinder lengths without the use of tools. The adjustment shall be made by raising a lever and moving the top clamp vertically.

The bracket system shall be free of straps and clamps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the SCBA tank in place for a safe and comfortable fit in the seat back cavity. The SCBA unit simply needs to be pushed against the pivot arm to engage the patented auto- locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The SecureAll™ shall include a release handle which shall be integrated into the seat cushion for quick and easy release. This shall eliminate the need for straps or pull cords to interfere with other SCBA equipment.

The seat back shall include a removable padded cover which shall be provided over the SCBA cavity

SEAT MOUNTING OFFICER

The officer's seat shall be installed in an ergonomic position in relation to the cab dash.

OCCUPANT PROTECTION OFFICER

The officer's position shall be equipped with the IMMI 4Front and RollTek™ Systems which shall secure belted occupants and increase the survivable space within the cab. The 4Front and RollTek™ Systems shall selectively deploy integrated systems to protect against injuries in qualifying frontal impact, and rollover events.

The Officer's seating area protection shall include:

- Officer's knee airbag **OKAB** - inflating knee bolster airbags to protect the knees.
- Integrated roll sensor **IRS** - detects an imminent rollover, activates protective devices and records crash events.
- Integrated belt pretension **IBP** - device for mechanical and/or electrical seats tightens the seat belt, securing officer in seat and positioning officer for contact with seat integrated head cushion side roll airbag.
- Inflatable head cushion seat integrated side roll airbag **SRA** - protects officer's head/neck and shields officer from dangerous surfaces.

POWER SEAT WIRING

The power seat or seats installed in the cab shall be wired directly to battery power.

SEAT BELT ORIENTATION CREW

The crew position seat belts shall follow the standard orientation which extends from the outboard shoulder extending to the inboard hip.

SEAT REAR FACING OUTER LOCATION

The crew area shall include two (2) rear facing crew seats, which include one (1) located directly behind the left side front seat and one (1) located directly behind the right side front seat.

SEAT CREW REAR FACING OUTER

The crew area shall include a seat in the rear facing outboard position which shall be a H.O. Bostrom 500 Series Firefighter model seat. The seat shall feature a tapered and padded seat, and cushion. The seat shall be mounted in a fixed position.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt and automatic retractor as an

integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant. The ABTS feature shall also include the RiteHite™ shoulder adjustment feature to provide enhanced comfort and safety by allowing customized seat belt fit.

The minimum vertical dimension from the seat H-point to the ceiling for this belted seating position shall be 35.00 inches. This model of seat shall have successfully completed the static load tests by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have successfully completed the dynamic sled testing using FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

SEAT BACK REAR FACING OUTER

The rear facing outboard seat shall feature a Bostrom SecureAll™ self contained breathing apparatus (SCBA) locking system which shall store most U.S. and International SCBA brands and bottle sizes while in transit or for storage within the seat back. The bracket shall be easily adjustable for all SCBA brands and cylinder diameters. All adjustment points shall utilize similar hardware and adjustments shall be made with one tool.

The bracket shall be adjustable to compensate for different cylinder lengths without the use of tools. The adjustment shall be made by raising a lever and moving the top clamp vertically.

The bracket system shall be free of straps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the SCBA tank in place for a safe and comfortable fit in the seat back cavity. The SCBA unit simply needs to be pushed against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The SecureAll™ shall include a release handle which shall be integrated into the center of the bottom seat cushion for easy access and to eliminate hooking the release handle with clothing or other equipment.

The seat back shall include a removable padded cover which shall be provided over the SCBA cavity.

SEAT MOUNTING REAR FACING OUTER

The rear facing outer seats shall offer special mounting positions which shall be 2.00 inches towards the rear wall offering additional space between the front seats and the outer rear facing seats.

OCCUPANT PROTECTION RFO

The rear facing outer seat position(s) shall be equipped with the RollTek™ System which shall secure belted occupants and increase the survivable space within the cab. The RollTek™ System shall deploy integrated systems to protect against injuries in rollover events.

The rear facing outer seat position(s) protection shall include:

Integrated roll sensor **IRS** - detects an imminent rollover, activates protective devices and records crash events

Integrated belt pretension **IBP** - device for flip-up (non-theatre) and fixed mechanical seats tightens the seat belt, securing occupant in seat and positioning occupant for contact with seat integrated head cushion side roll airbag.

Inflatable head cushion seat integrated side roll airbag **SRA** - protects occupant's head/neck

and shields occupant from dangerous surfaces.

SEAT FORWARD FACING OUTER LOCATION

The crew area shall include two (2) forward facing outboard seats, which include one (1) located next to the outer wall of the cab on the left side of the cab and one (1) located next to the outer wall on the right side of the cab.

SEAT CREW FORWARD FACING OUTER

The crew area shall include a seat in the forward facing outer position which shall be a theatre style series. The seat shall feature a padded seat cushion which shall be hinged and attached to the wall providing optimum space savings. The seat shall remain in the stored position until occupied.

The minimum vertical dimension from the seat H-point to the ceiling for each belted seating position shall be 35.00 inches.

The buckle portion of the seat belt shall be mounted on a rigid or semi-rigid stalk such that the buckle remains positioned in an accessible location. The seat belt assembly anchorages shall conform to the Federal Safety Standard (FMVSS) No. 210, "Seat belt assembly anchorages".

This model of seat shall have successfully completed the static load tests by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have successfully completed the dynamic sled testing using FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

SEAT BACK FORWARD FACING OUTER

The crew area shall include a seat in the forward facing outer position which shall be a theatre style seat. The rear wall padded trim shall act as the backrest for each seat.

There shall be a red, three-point shoulder harness with lap belt and an automatic retractor attached to the cab and available to the seat. The buckle portion of the seat belt shall be mounted on a rigid or semi-rigid stalk such that the buckle remains positioned in an accessible location. The seat belt assembly anchorages shall conform to the Federal Safety Standard (FMVSS) No. 210, "Seat belt assembly anchorages".

SEAT MOUNTING FORWARD FACING OUTER

The forward facing outer seat shall be mounted in the furthest outboard position facing the front of the cab.

OCCUPANT PROTECTION FFO

The forward facing outer seat positions shall be equipped with the RollTek™ rollover occupant protection system which shall secure occupants, increase the survivable space within the cab and protect against head/neck injuries in the event of a roll over accident. The system shall function using a microprocessor-controlled, solid-state sensing device which, when the system detects a side roll shall provide instantaneous occupant protection (less than 0.3 seconds from trigger to total deployment) by automatically initiating the following sequence:

1. The seat belt shall tighten around the occupant.

System Components Shall Include:

Integrated Roll Sensor **IRS** - detects an imminent rollover, activates protective devices and records crash events.

Integrated Belt Pretension **IBP** with flip-up (non theatre) and fixed mechanical seats -

tightens the seat belt around occupant, securing occupant in seat.

Integrated Gas Pretension **IGP** with flip-up theatre style seats - tightens the seat belt around occupant, securing occupant in seat.

CAB FRONT UNDERSEAT STORAGE ACCESS

The left and right under seat storage areas shall have a solid aluminum hinged door with non-locking latch.

SEAT COMPARTMENT DOOR FINISH

All underseat storage compartment access doors shall have a multi-tone silver gray texture finish.

WINDSHIELD WIPER SYSTEM

The cab shall include a triple arm linkage wiper system which shall clear the windshield of water, ice and debris. There shall be two (2) windshield wipers; each shall be affixed to a radial arm. The wiper motor shall be activated by an intermittent wiper control located within easy reach of the driver's position.

ELECTRONIC WINDSHIELD FLUID LEVEL INDICATOR

The windshield washer fluid level shall be monitored electronically. When the washer fluid level becomes low the yellow "Check Message Center" indicator light on the instrument panel shall illuminate and the message center in the dual air pressure gauge shall display a "Check Washer Fluid Level" message.

CAB DOOR HARDWARE

The cab entry doors shall be equipped with exterior pull handles, suitable for use while wearing firefighter gloves. The handles shall be made of a fiber reinforced plastic composite with a black matt finish.

The interior exit door handles shall be flush paddle type with a black finish, which are incorporated into the upper door panel.

All cab entry doors shall include locks which are keyed alike. The door locks shall be designed to prevent accidental lockout.

DOOR LOCKS

Each cab entry door shall include a manually operated door lock. Each door lock may be actuated from the inside of the cab by means of a red knob located on the paddle handle of the respective door or by using a TriMark key from the exterior. The door locks are designed to prevent accidental lock out.

GRAB HANDLES

The cab shall include one (1) 18.00 inch knurled, anti-slip, one-piece exterior assist handle behind each cab door. The grab handle shall be made of SAE 304 stainless steel and be 1.25 inch diameter to enable non-slip assistance with a gloved hand.

REARVIEW MIRRORS

Retrac Aerodynamic West Coast style dual vision mirror heads model 613305 shall be provided and installed on each of the front cab doors.

The mirrors shall be mounted via 1.00 inch diameter tubular stainless steel arms to provide a rigid mounting to reduce mirror vibration.

The mirrors shall measure 8.00 inches wide X 19.00 inches high and shall include an integral convex mirrors installed in the mirror head below the flat glass to provide a wider field of vision. The flat and convex mirrors shall be motorized with remote horizontal and vertical adjustment. The control switches shall be mounted within easy reach of the driver. The flat and convex mirrors shall be heated for defrosting in severe cold weather conditions.

The mirrors shall be constructed of a vacuum formed chrome plated ABS plastic housing that is corrosion resistant and shall include the finest quality non-glare glass.

REARVIEW MIRROR HEAT SWITCH

The heat for the rearview mirrors shall be controlled through a rocker switch in the mirror control panel on the left side dash.

CAB FENDER

Full width wheel well liners shall be installed on the extruded cab to limit road splash and enable easier cleaning. Fender shall consist of an inner liner 16.00 inches wide made of ABS composite and an outer fenderette 5.00 inches wide made of SAE 304 polished stainless steel.

MUD FLAPS FRONT

The front wheel wells shall have mud flaps installed on them. The mud flaps shall extend from the outer edge of the wheel well to the inner edge of the wheel well to provide additional protection from road spray.

IGNITION

A master battery system with a keyless start ignition system shall be provided. There shall be a three-position rocker switch with off, battery, and ignition positions as well as a stainless-steel etched engine start push-button. The engine start button shall include an illuminated LED halo ring. Both switches shall be mounted to the left of the steering wheel on the dash. The engine start switch shall only operate when the master battery and ignition switch is in the "ignition" position.

BATTERY

The single start electrical system shall include six (6) Harris BCI 31 925 CCA batteries with a 210 minute reserve capacity and 4/0 welding type dual path starter cables per SAE J541.

BATTERY TRAY

The batteries shall be installed within two (2) stainless steel battery trays located on the left side and right side of the chassis, securely bolted to the frame rails. The battery trays shall be coated with the same material as the frame.

The battery trays shall include drain holes in the bottom for sufficient drainage of water. A durable, non-conducting, interlocking mat made by Dri-Dek shall be installed in the bottom of the trays to allow for air flow and help prevent moisture build up. The batteries shall be held in place by non-conducting phenolic resin hold down boards.

BATTERY BOX COVER

Each battery box shall include a stainless steel cover which protects the top of the batteries. Each cover shall include flush latches which shall keep the cover secure as well as a black powder coated handle for convenience when opening.

BATTERY CABLE

The starting system shall include cables which shall be protected by 275 degree F. minimum high temperature flame retardant loom, sealed at the ends with heat shrink and sealant.

BATTERY JUMPER STUD

The starting system shall include battery jumper studs. These studs shall be located in the forward most portion of the driver's side lower step, 8.00 inches apart. The studs shall allow the vehicle to be jump started, charged, or the cab to be raised in an emergency in the event of battery failure.

ALTERNATOR

The charging system shall include a 320 amp Leece-Neville 12 volt alternator. The alternator shall include a self-exciting integral regulator.

STARTER MOTOR

The single start electrical system shall include a Delco brand starter motor.

BATTERY CONDITIONER

A Kussmaul Auto Charge 40 LPC battery conditioner shall be supplied. The battery conditioner shall provide a 40 amp output for the chassis batteries and a 15 amp output circuit for accessory loads. The battery conditioner shall be mounted in the cab in the LH rear facing outer seating position.

BATTERY CONDITIONER DISPLAY

A Kussmaul battery conditioner display shall be supplied. The battery conditioner display shall be mounted in the cab, viewable through the cab mid side window behind the left front door.

CAB/CHASSIS ELECTRICAL OUTLET

There shall be a 120V 20A power pre-wired into the cab to a junction box behind the driver's seat. 12/3 wiring terminating in the junction box shall be routed to behind the cab on the chassis frame rails with a 15.00 feet long coil for connection to apparatus 120V power supply.

ELECTRICAL INLET LOCATION

An electrical inlet shall be installed on the left hand side of cab over the wheel well in the rearward position.

ELECTRICAL INLET

A Kussmaul 20 amp super auto-eject electrical receptacle shall be supplied. It shall automatically eject the plug when the starter button is depressed. A single item or an addition of multiple items must not exceed the rating of the electric inlet that it's connected to.

ELECTRICAL INLET CONNECTION

The electrical inlet shall be connected to the battery conditioner.

ELECTRICAL INLET COLOR

The electrical inlet connection shall include a red cover.

HEADLIGHTS

The cab front shall include four (4) rectangular LED headlamps with separate high and low beams mounted in bright chrome bezels. Each lamp shall include a heating system that de-ices the headlight.

HEADLIGHT LOCATION

The headlights shall be located on the front fascia of the cab directly below the front warning lights.

FRONT TURN SIGNALS

The front fascia shall include two (2) Whelen model 600 4.00 inch X 6.00 inch programmable amber LED turn signals which shall be installed in a polished aluminum radius mount housing above and outboard of the front warning and head lamps.

SIDE TURN/MARKER LIGHTS

The sides of the cab shall include two (2) Tecniq S170 LED side marker lights which shall be provided just behind the front cab radius corners. The lights shall be amber with chrome bezels.

MARKER AND ICC LIGHTS

In accordance with FMVSS, there shall be five (5) marker lamps on the front of the vehicle

designating identification and clearance. There shall be five (5) face mounted lights integrated into the scene light.

HEADLIGHT AND MARKER LIGHT ACTIVATION

The headlights and marker lights shall be controlled through a rocker switch within easy reach of the driver. There shall be a dimmer switch within easy reach of the driver to adjust the brightness of the dash lights. The headlamps shall be equipped with the "Daytime Running" light feature, which shall illuminate the headlights when the ignition switch is in the "On" position and the parking brake is released.

LIGHTBAR SWITCH

The light bar shall be controlled by a rocker switch located on the switch panel. This switch shall be clearly labeled for identification.

INTERIOR OVERHEAD LIGHTS

The cab shall include a LED dome lamp located over each door. The lights shall include push switches on each lamp to activate both the clear and red portions of the light individually.

INTERIOR OVERHEAD LIGHTS ACTIVATION

The clear portion of each lamp shall be activated by opening the respective door.

LIGHTBAR PROVISION

There shall be one (1) light bar installed on the cab roof. The light bar shall be provided and installed by the chassis manufacturer. The light bar installation shall include a lowered mounting that shall place the light bar just above the junction box and wiring to a control switch on the cab dash.

CAB FRONT LIGHTBAR MODEL

The cab shall be provided with one (1) Whelen model F4N72 light bar. The light bar shall be 72.00 inches in length and feature eighteen (18) customizable pods.

FRONT SCENE LIGHTS

The front of the cab shall include one (1) HiViz model FireTech FT-B-72-ML-W LED scene light installed on the brow of the cab. The light shall feature (5) five integrated marker lights. The housing shall be powder coated white.

FRONT SCENE LIGHT LOCATION

There shall be one (1) scene light mounted center on the front brow of the cab.

FRONT SCENE LIGHTS ACTIVATION

The front scene lighting shall be activated by individual rocker switches for each of the three separate scene lighting circuits. Each circuit shall be activated independently and shall include rocker switches labeled "Front Scene", "Front Flood", and "Front Spotlight".

SIDE SCENE LIGHTS

The cab shall include two (2) Whelen model Pioneer PCH2 semi-recess mount lights installed one (1) on each side of the cab.

Each 150 watt lamp head shall incorporate a 12 volt DC Super-LED combination flood/spot light installed in a die-cast aluminum housing. Each lamp head shall use a collimator/metalized redux spot/flood reflector assembly with Proclera™ silicone optics and a clear non-optic polycarbonate lens. The lens/reflector assembly shall utilize a liquid injected molded silicone gasket to be resistant to water, moisture, dust, and other environmental conditions. The PCH2 shall be vibration resistant. The Pioneer PC boards shall be conformal coated for additional protection. Each combination flood light lamp head shall draw 13.0 amps in spotlight mode and generate 17,750 lumens total. Each lamp head shall measure 4.25 inches in height X 14.00 inches in width. Each lamp head shall be mounted within a semi-

recess housing featuring a chrome flange which shall measure 7.92 inches in height X 17.17 inches in width. The lamp heads and brackets shall be powder coated white.

SIDE SCENE LIGHT LOCATION

The scene lighting located on the left and right sides of the cab shall be mounted rearward of the cab "B" pillar in the 10.00 inch raised roof portion of the cab between the front and rear crew doors.

SIDE SCENE ACTIVATION

The scene lights shall be activated by two (2) rocker switches located in the switch panel, one (1) for each light, and by opening the respective side cab doors.

GROUND LIGHTS

Each door shall include a Tecniq T44 LED ground light mounted to the underside of the cab step below each door. The lights shall include a polycarbonate lens, a housing which is vibration welded and LEDs which shall be shock mounted for extended life.

GROUND LIGHTS

The ground lighting shall be activated when the parking brake is set, by the opening of the door on the respective cab side, and a rocker switch in the dash panel.

LOWER CAB STEP LIGHTS

The middle step located at each door shall include a Tecniq T44 LED light which shall activate with the opening of the respective door. The lights shall include a polycarbonate lens, a housing which is vibration welded and LEDs which shall be shock mounted for extended life.

INTERMEDIATE STEP LIGHTS

The intermediate step well area at the front doors shall include a TecNiq D06 LED light within a chrome housing. The front egress step lights shall provide visibility to the step well area for the first step exiting the vehicle. The Egress step lights shall activate with entry step lighting.

ENGINE COMPARTMENT LIGHT

There shall be a LED NFPA compliant light mounted under the engine tunnel for area work lighting on the engine. The light shall activate automatically when the cab is tilted.

DO NOT MOVE APPARATUS LIGHT

The front headliner of the cab shall include a flashing red TecNiq K50 LED light clearly labeled "Do Not Move Apparatus". In addition to the flashing red light, an audible alarm shall be included which shall sound while the light is activated.

The flashing red light shall be located centered left to right for greatest visibility.

The light and alarm shall be interlocked for activation when either a cab door is not firmly closed, or an apparatus compartment door is not closed, and the parking brake is released.

MASTER WARNING SWITCH

A master switch shall be included in the main rocker switch panel. The switch shall be a rocker type, red in color and labeled "Master" for identification. The switch shall feature control over all devices wired through it. Any warning device switch left in the "ON" position shall automatically power up when the master switch is activated.

HEADLIGHT FLASHER

An alternating high beam headlight flashing system shall be installed into the high beam headlight circuit which shall allow the high beams to flash alternately from left to right. Deliberate operator selection of high beams will override the flashing function until low beams are again selected. Per NFPA, these clear flashing lights will also be disabled "On

Scene” when the park brake is applied.

HEADLIGHT FLASHER SWITCH

The flashing headlights shall be activated through a rocker switch on the switch panel. The rocker switch shall be clearly labeled for identification.

INBOARD FRONT WARNING LIGHTS

The cab front fascia shall include two (2) Whelen 600 series Super LED front warning lights in the left and right inboard positions. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors. The lights shall be mounted to the front fascia of the cab within a chrome bezel.

INBOARD FRONT WARNING LIGHTS COLOR

The warning lights mounted on the cab front fascia in the inboard positions shall be red.

OUTBOARD FRONT WARNING LIGHTS

The cab front fascia shall include two (2) Whelen 600 series Super LED front warning lights in the left and right outboard positions. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors. The lights shall be mounted to the front fascia of the cab within a chrome bezel.

OUTBOARD FRONT WARNING LIGHTS COLOR

The warning lights mounted on the cab front fascia in the outboard position shall be red.

FRONT WARNING SWITCH

The front warning lights shall be controlled via rocker switch on the panel. This switch shall be clearly labeled for identification.

INTERSECTION WARNING LIGHTS

The chassis shall include two (2) Whelen 600 series Super LED intersection warning lights, one (1) each side. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors.

INTERSECTION WARNING LIGHTS COLOR

The intersection lights shall be red.

INTERSECTION WARNING LIGHTS LOCATION

The intersection lights shall be mounted on the side of the bumper in the rearward position.

SIDE WARNING LIGHTS

The cab sides shall include two (2) Whelen 600 series Super LED warning lights, one (1) on each side. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors. The lights shall be mounted to the sides of the cab within a chrome bezel.

SIDE WARNING LIGHTS COLOR

The warning lights located on the side of the cab shall be red.

SIDE WARNING LIGHTS LOCATION The warning lights on the side of the cab shall be mounted over the front wheel well directly over the center of the front axle.

SIDE AND INTERSECTOR WARNING SWITCH

The side and intersector warning lights shall be controlled by a rocker switch on the switch panel. This switch shall be clearly labeled for identification.

REAR WARNING LIGHTS

The cab shall include a Whelen TAM65 Traffic Advisor Kit provided by Spartan. The kit shall include the Traffic Advisor with the standard fifteen (15) feet of cable and a Whelen TACTL5 Traffic Advisor control head.

The Whelen TACTL5 Traffic Advisor control head shall be installed and wired on the center dash lid.

The power to the control head shall be ignition switched and activation shall be dependent upon the state of the controllers switched position upon ignition.

Wiring provisions shall be provided and routed to the rear of the frame for the Whelen traffic advisor which shall be shipped loose for OEM installation.

INTERIOR DOOR OPEN WARNING LIGHTS

The interior of each door shall include one (1) red 4.00 inch diameter Tecniq T40 LED warning light located on the door panel. Each light shall activate with a flashing pattern when the door is in the open position to serve as a warning to oncoming traffic.

SIREN CONTROL HEAD

A Whelen 295HFS2 electronic siren control head with remote amplifier shall be provided and flush mounted in the switch panel with a location specific to the customer's needs. The siren shall feature 200-watt output, hands free mode and shall be in "standby" mode awaiting instruction. The siren shall offer radio broadcast, public address, wail, yelp, or piercer tones and hands free operation which shall allow the operator to turn the siren on and off from the horn ring if a horn/siren selector switch option is also selected.

STEERING WHEEL HORN BUTTON SELECTOR SWITCH

A rocker switch shall be installed in the switch panel between the driver and officer to allow control of either the electric horn or the air horn from the steering wheel horn button.

AUDIBLE WARNING LH FOOT SWITCH

Two (2) foot actuated switches shall be supplied for installation in the front section of the cab for driver actuation. One (1) switch shall be wired to actuate the air horn(s) and one (1) switch the mechanical siren(s).

AIR HORN FOOT SWITCH LH

The air horn foot switch shall be a Linemaster model 491-S.

AIR HORN FOOT SWITCH LH LOCATION

The air horn foot switch shall be located on the left hand side accessible to the driver between the steering column and the door.

AIR HORN FOOT SWITCH LH POSITION

The air horn foot switch shall be positioned inboard of any other foot switch, if applicable

MECHANICAL SIREN FOOT SWITCH LH

The mechanical siren foot switch shall be a Linemaster model 491-S.

MECHANICAL SIREN FOOT SWITCH LH LOCATION

The mechanical siren foot switch shall be located on the left hand side accessible to the driver between the steering column and the door.

MECHANICAL SIREN FOOT SWITCH LH POSITION

The mechanical siren foot switch shall be positioned outboard of any other foot switch, if applicable.

AUDIBLE WARNING LH FOOT SWITCH BRACKET

A 30.00 degree angled foot switch bracket, wide enough to accommodate (2) foot switches, shall be installed outboard of the steering column for specified driver accessible foot switch activations.

AUDIBLE WARNING RH FOOT SWITCH

Two (2) foot actuated switches shall be supplied for installation in the front section of the cab for officer actuation. One (1) switch shall be wired to actuate the air horn(s) and one (1) switch the mechanical siren(s).

AIR HORN FOOT SWITCH RH

The air horn foot switch shall be a Linemaster model 491-S.

AIR HORN FOOT SWITCH RH LOCATION

The air horn foot switch shall be temporarily tied up with a coiled wire drop at the firewall inboard for installation by the customer on the right hand side accessible to the officer.

MECHANICAL SIREN FOOT SWITCH RH

The mechanical siren foot switch shall be a Linemaster model 491-S.

MECHANICAL SIREN FOOT SWITCH RH LOCATION

The mechanical siren foot switch shall be temporarily tied up with a coiled wire drop at the firewall inboard for installation by the customer on the right hand side accessible to the officer.

AUDIBLE WARNING RH FOOT SWITCH BRACKET

An individual 30.00 degree angled bracket shall be shipped loose with the chassis for installation of each officer accessible foot switch by the customer.

MECHANICAL SIREN BRAKE/AUXILIARY ACTIVATION

A red momentary siren brake rocker switch shall be provided in the switch panel on the dash.

MECHANICAL SIREN INTERLOCK

The siren shall only be active when master warning switch is on to prevent accidental engagement.

BACK-UP ALARM

An ECCO model 575 backup alarm shall be installed at the rear of the chassis with an output level of 107 dB. The alarm shall automatically activate when the transmission is placed in reverse.

INSTRUMENTATION

An ergonomically designed instrument panel shall be provided. Each gauge shall be backlit with LED lamps. Stepper motor movements shall drive all gauges. The instrumentation system shall be multiplexed and shall receive ABS, engine, and transmission information over the J1939 data bus to reduce redundant sensors and wiring.

A twenty eight (28) icon lightbar message center with integral LCD odometer/trip odometer shall be included. The odometer shall display up to 999,999.9 miles. The trip odometer shall display 9,999.9 miles. The LCD message center screen shall be capable of custom configuration by the users for displaying certain vehicle status and diagnostic functions.

The instrument panel shall contain the following gauges:

One (1) three-movement gauge displaying vehicle speed, fuel level, and Diesel Exhaust Fluid (DEF) level. The primary scale on the speedometer shall read from 0 to 100 MPH, and the secondary scale on the speedometer shall read from 0 to 160 KM/H. The scale on the fuel and DEF level gauges shall read from empty to full as a fraction of full tank capacity. Red indicator lights in the gauge and an audible alarm shall indicate low fuel or low DEF at 1/8th tank level. One (1) three-movement gauge displaying engine RPM, and primary and secondary air system pressures shall be included. The scale on the tachometer shall read from 0 to 3000 RPM. The scale on the air pressure gauges shall read from 0 to 150 pounds per square inch (PSI) with a red line zone indicating critical levels of air pressure. Red indicator lights in the gauge and an audible alarm shall indicate low air pressure.

One (1) four-movement gauge displaying engine oil pressure, coolant temperature, voltmeter, and transmission temperature shall be included. The scale on the engine oil pressure gauge shall read from 0 to 100 pounds PSI with a red line zone indicating critical levels of oil pressure. A red indicator light in the gauge and audible alarm shall indicate low engine oil pressure. The scale on the coolant temperature gauge shall read from 100 to 250 degrees Fahrenheit (°F) with a red line zone indicating critical coolant temperatures. A red indicator light in the gauge and audible alarm shall indicate high coolant temperature. The scale on the voltmeter shall read from 9 to 18 volts with a red line zone indicating critical levels of battery voltage. A red indicator light in the gauge and an audible alarm shall indicate high or low system voltage. The low voltage alarm shall indicate when the system voltage has dropped below 11.8 volts for more than 120 seconds in accordance with the requirements of NFPA 1901. The scale on the transmission temperature gauge shall read from 100 to 300 degrees °F with a red line zone indicating critical temperatures. A red indicator light in the gauge and an audible alarm shall indicate a high transmission temperature.

The light bar portion of the message center shall include twenty-eight (28) LED backlit indicators. The lightbar shall be split with fourteen (14) indicators on each side of the LCD message screen. The lightbar shall contain the following indicators and produce the following audible alarms when supplied in conjunction with applicable configurations:

RED INDICATORS

Stop Engine - indicates critical engine fault

Air Filter Restricted - indicates excessive engine air intake restriction

Park Brake - indicates parking brake is set

Seat Belt - indicates a seat is occupied and corresponding seat belt remains unfastened

Low Coolant - indicates critically low engine coolant

Cab Tilt Lock - indicates the cab tilt system locks are not engaged.

AMBER INDICATORS

Malfunction Indicator Lamp (MIL) - indicates an engine emission control system fault

Check Engine - indicates engine fault

Check Transmission - indicates transmission fault

Anti-Lock Brake System (ABS) - indicates anti-lock brake system fault

High exhaust system temperature – indicates elevated exhaust temperatures

Water in Fuel - indicates presence of water in fuel filter

Wait to Start - indicates active engine air preheat cycle

Windshield Washer Fluid – indicates washer fluid is low

DPF restriction - indicates a restriction of the diesel particulate filter

Regen Inhibit-indicates regeneration of the DPF has been inhibited by the operator

Range Inhibit - indicates a transmission operation is prevented and requested shift request may not occur.

SRS - indicates a problem in the supplemental restraint system
Check Message - indicates a vehicle status or diagnostic message on the LCD display requiring attention.

GREEN INDICATORS

Left and Right turn signal indicators

ATC - indicates low wheel traction for automatic traction control equipped vehicles, also indicates mud/snow mode is active for ATC system

High Idle - indicates engine high idle is active.

Cruise Control - indicates cruise control is enabled

OK to Pump - indicates the pump is engaged and conditions have been met for pump operations

Pump Engaged - indicates the pump transmission is currently in pump gear

Auxiliary Brake - indicates secondary braking device is active

BLUE INDICATORS

High Beam indicator

AUDIBLE ALARMS

Air Filter Restriction

Cab Tilt Lock

Check Engine

Check Transmission

Open Door/Compartment

High Coolant Temperature

High or Low System Voltage

High Transmission Temperature

Low Coolant Level

Low DEF Level

Low Engine Oil Pressure

Low Fuel

Seatbelt Indicator

Stop Engine

Water in Fuel

Extended Left/Right Turn Signal On

ABS System Fault

BACKLIGHTING COLOR

The instrumentation gauges and the switch panel legends shall be backlit using red LED backlighting.

CAMERA REAR

One (1) Audiovox Voyager heavy duty box shaped HD camera shall be shipped loose for OEM installation in the body to afford the driver a clear view to the rear of the vehicle.

The camera system shall include a one-way communication device that shall be an integral part of the rear camera for the use of voice commands directly to the driver. The rear camera display shall activate when the vehicle's transmission is placed in reverse.

CAMERA DISPLAY

The camera system shall be wired to a 7.00 inch flip down HD monitor which shall include a color display and day and night brightness modes installed above the driver position.

COMMUNICATION ANTENNA

An antenna base, for use with an NMO type antenna, shall be mounted on the left hand front corner of the cab roof so not to interfere with light bars or other roof mounted equipment installed by chassis builder. The antenna base shall be an Antenex model MABVT8 made for either a 0.38 inch or 0.75 inch receiving hole in the antenna and shall include 17 foot of RG58 A/U cable with no connector at the radio end of the cable. The antenna base design

provides the most corrosion resistance and best power transfer available from a high temperature brass construction and gold plated contact design. The antenna base shall be chassis builder supplied.

COMMUNICATION ANTENNA CABLE ROUTING

The antenna cable shall be routed from the antenna base mounted on the roof to the area behind and underneath the right hand front seat.

AUXILIARY COMMUNICATION ANTENNA

An auxiliary antenna base, for use with an NMO type antenna, shall be installed on the cab. The antenna base shall be an Antenex model MABVT8 and shall include 17.00 foot of RG58 A/U cable with no connector at the radio end of the cable. The antenna shall be mounted on the right hand front corner of the cab roof so not to interfere with light bars or other roof mounted equipment installed by chassis builder. The antenna base shall be chassis builder supplied.

AUXILIARY COMMUNICATION ANTENNA CABLE ROUTING

The auxiliary antenna cable shall be routed from the antenna base mounted on the roof to the area behind and underneath the right hand front seat.

TWO-WAY RADIOS

A radio wire conduit with a pull wire included shall be installed and routed from behind the dash to under the officer's seat for radio installation by the customer. The officer's under seat storage area shall include an access hole for the conduit cut into the rear face of the seat box. The hole shall be approximately 1.00 inch from the bottom and 1.00 from the inner wall of the seat box.

CAB EXTERIOR PROTECTION

The cab face shall have a removable plastic film installed over the painted surfaces to protect the paint finish during transport to the body manufacturer.

FIRE EXTINGUISHER

A 2.50 pound D.O.T approved fire extinguisher with BC rating shall be shipped loose with the cab.

DOOR KEYS

The cab and chassis shall include a total of four (4) door keys for the manual door locks.

CHASSIS OPERATION MANUAL

There shall be two (2) digital copies of the chassis operation manual provided with the chassis. The digital data shall include a parts list specific to the chassis model.

ENGINE AND TRANSMISSION OPERATION MANUALS

The following manuals specific to the engine and transmission models ordered will be included with the chassis in the ship loose items:

- (1) Hard copy of the Engine Operation and Maintenance manual with digital copy
- (1) Digital copy of the Transmission Operator's manual
- (1) Digital copy of the Engine Owner's manual

CAB/CHASSIS AS BUILT WIRING DIAGRAMS

The cab and chassis shall include two (2) digital copies of wiring schematics and option wiring diagrams.

EXHAUST HEAT SHIELD

There shall be an exhaust heat shield added to the chassis provided exhaust. The shield shall terminate past the front compartment and shall incorporate a heavy duty spray on insulation

under R1. With this shield, the temperature of the front compartment shall not exceed the ambient temperature.

The heat shield shall be attached to the underside of the body utilizing a flexible bracket.

REAR FACING STORAGE BOX

There shall be one (1) rear facing storage box, fabricated out of .125 inch (3.18 mm) smooth aluminum installed behind the engine tunnel in the chassis cab.

The height of the compartment shall match the height of the engine tunnel and the width shall be as wide as possible between the rear facing outer seat risers x 15.00 inches (381 mm) front to back at the base and contoured to match the engine tunnel

The interior of the compartment shall feature a natural aluminum finish.

Vertically mounted Unistrut shall be installed inside the EMS storage compartment to accommodate the installation of shelving in the upper half of the compartment.

There shall be a 1.00 inch high lip included around the top perimeter of the EMS compartment specified to retain equipment stored on top of the compartment by the Fire Department.

EMS COMPARTMENT NETTING

A cargo net, black in color, shall be provided and installed on the opening of the EMS compartment. The cargo net enclosure shall be secured along the lower edge. The net shall drop out of the way for easy cabinet access.

The cargo net covering the EMS compartment shall include side push clip style fasteners along the top of the cabinet for ease of entry.

EMS COMPARTMENT LIGHTING

One (1) LED Tube light model #RX-15T16-5050 shall be installed in accordance with the compartment height to offer the best lighting in the EMS cabinet.

EMS COMPARTMENT LIGHTING ACTIVATION

The light(s) in each compartment shall be activated by a rocker switch inside the EMS compartment.

EMS COMPARTMENT SHELF

There shall be one (1) shelf in the cab EMS compartment. The shelf shall be fabricated of .188 inch (4.76 mm) thick aluminum sheet material with the outside and inside edges flanged up to prevent equipment from sliding off. The shelf shall be as wide as possible to allow proper attachment to unistrut channels and shall be adjustable up and down.

The shelf shall feature a natural finish.

EMS COMPARTMENT(S) EXTERIOR FINISH

The exterior of the EMS compartment(s) specified shall feature a painted finish/color equivalent to the chassis interior unless specified otherwise.

CHASSIS REQUIRED LABELING

Signs that state "Occupants must be seated and belted when apparatus is in motion" shall be provided.

They shall be visible from each seating position.

There shall be a lubrication plate mounted inside the cab listing the type and grade of lubrication used in the following areas on the apparatus and chassis:

- Engine oil
- Engine Coolant
- Transmission Fluid
- Pump Transmission Lubrication Fluid
- Drive Axle Lubrication Fluid
- Generator Lubrication Fluid (where applicable)
- Tire Pressures

APPARATUS INFORMATION LABEL

There shall be a high-visibility label installed in a location clearly detectable to the driver while in the seated position.

The label shall indicate the following specified information.

Overall Height (feet and inches)

Overall Length (feet and inches)

Overall GVWR (tons or metric tons)

CAB TILT CONTROL

There shall be a cab tilt pendant control with a quick-connect coupler provided and installed on the right side of the apparatus. The pendant shall be located directly on the bottom sill of the pump compartment.

There shall also be a cab tilt instruction plate located as close as possible to the control pendant for ease of operation.

AIR TANK DRAIN LINES (extended)

There shall be manual pull air tank drain lines provided with the apparatus. The air drain lines shall be extended to the outer edge of the apparatus to facilitate draining moisture from the chassis air tanks to a single location for all drains and shall be actuated by a key ring. A label shall be affixed indicating "Air Tank Drain".

HEAT EXCHANGER

The supplementary heat exchanger cooling system shall be provided and installed to the discharge side of the fire pump through to the engine compartment without intermixing, for absorption of excess heat.

The heat exchanger shall be adequate in size to maintain safe operating temperature of the coolant in the pump drive engine and not in excess of the engine manufacturer's temperature rating, under all pumping condition

Appropriate drains shall be provided to allow draining the heat exchanger to prevent damage from freezing.

HELMET RESTRAINTS

Six (6) Ziamatic UHH-1 Universal Helmet Holders shall be provided and shipped loose with the apparatus.

MUD FLAPS

Heavy-duty black rubber mud flaps with manufactures logo shall be provided behind the rear wheels. The mud flaps shall be bolted in place.

PUMP COMPARTMENT

The complete apparatus pump compartment shall be constructed of a combination of structural tubing and formed sheet metal. The same materials used in the body shall be utilized in the construction of the pump compartment. The structure shall be welded utilizing the same A.W.S. Certified welding procedure as used on the structural body module. These processes shall ensure the quality of structural stability of the pump compartment module.

The pump compartment module shall be separated from the apparatus body with a gap. This gap is necessary to accommodate the flexing of the chassis frame rails that are encountered while the vehicle is in transit so that harmful torsional forces are not transmitted into the structural framework.

MODULE MOUNTING

The entire pump module assembly shall be mounted so that it "floats" above the chassis frame rails with vibration isolators. The body substructure shall be mounted above the frame to allow independent flexing to occur between the body and the chassis. The assembly shall be mounted to the chassis frame rails with steel reinforced mounting brackets. The brackets shall be mounted to the side of the chassis frame flanges.

There shall be no welding to the chassis frame rail sides, web or flanges, or drilling of holes in the top or bottom frame flanges between axles. All body to chassis connections shall be bolted so that in the event of an accident, the body shall be easily removable from the chassis for repair or replacement.

Due to the constant vibration and twisting action that occurs in chassis frame rails and suspension, the torsion mounting system is required to minimize the possibility of premature body structural failures.

PUMP COMPARTMENT WORK LIGHT

One (1) Weldon LED work light model #2631-0000-30 shall be installed in the pump compartment module to illuminate the piping and plumbing components.

The light shall be activated by a weather resistant toggle switch installed inside the pump compartment.

SIDE OPERATOR CONTROL PANEL

The pump operators control panel shall be completely enclosed and located in the forward lower area of the L1 body compartment, to protect against road debris and weather elements. When the width of the L1 compartment allows, a fixed divider shall be installed rearward of the operator's panel to separate the panel from the rear section of the compartment with a permanent vertical partition.

The pump operator's panel shall be constructed of smooth aluminum and finish painted. The layout of the pump operator's control panel shall be positioned at a height easily accessible from ground level and ergonomically efficient to provide user-friendly operation.

The panel shall accommodate all operational controls for maintaining and monitoring pump and engine system operations and foam controls (if applicable) shall be located on the panel, for additional ease of operation and visibility. When the apparatus is equipped with compressed air foam capabilities, a lower access panel with sight glass window shall be installed directly below the main operators control panel to provide an unobstructed view of the oil level in the hydraulic fluid reservoir. The access panel shall utilize push button type latches for ease of removal and service.

All valve controls shall be immediately adjacent to its respective gauge and properly identified and color coded for ease of use. All markings shall be permanent in nature.

VALVE CONTROL - T-HANDLE PULL ASSEMBLY

Unless specified otherwise, the discharge valves shall be controlled from an Innovative Controls side mount valve control assembly. The ergonomically designed handle shall be chrome-plated with recessed areas for name plate and color code. A .75 inch (19.5 mm) diameter hardcoat anodized aluminum control rod and housing shall, together with a stainless spring steel locking mechanism, eliminate valve drift. Teflon impregnated bronze bushings in both ends of the rod housing shall minimize rod deflection, never need lubrication, and ensure consistent long-term operation. The control assembly shall include a decorative chrome-plated panel-mounting bezel. The valve operating mechanism will indicate the position of the valve at all times.

PANEL LIGHTS

Adequate illumination shall be provided for controls, switches, critical instructions, gauges, and instruments necessary for the proper operation of the apparatus and its equipment.

The pump operator's panel shall be illuminated by means of a brushed stainless steel shielded light assembly with two (2) Whelen PSCOMPH Super-LED strip lights above the operator's panel in the L1 compartment.

There shall also be a minimum of one (1) Whelen PSCOMPH Super-LED strip light installed on each side of the pump compartment to illuminate the speedlay hose bed area. The light shall be mounted directly to the pump compartment tubular frame structure, directly above the speedlay hose beds, on the inboard side of the frame structure.

In addition, there shall be an LED Grote style #60571 clear Surface Mount series light provided and installed on the pump house panel. One (1) each side of the apparatus.

PUMP PANEL LIGHT ACTIVATION

One (1) pump panel light at the operator's panel shall be illuminated at the time the pump is ready to pump and it is "OK TO PUMP". The Pump shift has been completed and the chassis automatic transmission is engaged.

The remaining lights shall be controlled by a switch located on the side operator's panel.

The operator's panel light(s) in the L1 compartment shall be activated by the above activation and the L1 compartment door switch.

SPEEDLAY HOSE BEDS

Two (2) speed lay hose beds stacked side by side shall be provided. The speedlays shall be mounted in mid-section portion of the pump compartment module directly above the pump to facilitate safe hose reloading and deployment.

BLACK POLY SPEEDLAY TRAYS

The speedlay trays shall be made of .50-inch black poly material.

Each tray shall have vertical and horizontal hand holds for ease of handling. Slots shall be provided in the floor of the tray for hose drainage.

SPARE SET OF SPEEDLAY TRAYS

There shall be one (1) spare set of removable speedlay hose bed trays provided and shipped loose with the apparatus. The speedlay trays shall be made of .50-inch black poly material. Each tray shall have vertical and horizontal hand holds for ease of handling. Slots shall be provided in the floor of the tray for hose drainage.

PUMP COMPARTMENT WIDTH

The width of the pump compartment (front to back) shall be 25.00-inches (.64 m).

PUMP COMPARTMENT ACCESS W/SPEEDLAY

Ease of access to the pump and plumbing shall be provided through the front of the pump compartment module by raising the cab to allow service and maintenance. The pump shall be positioned such that maintenance and overhaul work can be performed above the frame, and under the tilted cab.

A removable access panel shall be provided and installed on the forward portion of the back wall in the R1 compartment for additional plumbing and valve maintenance. The panel shall be secured with push button type latches.

BRUSHED STAINLESS STEEL SIDE PANELS

The pump side panels on the lower left and lower right sides shall be constructed of 14 gauge brushed stainless steel. Each panel shall consist of a removable lower panel fastened with mechanical fasteners. Both panels shall be removable for access to the pump for serviceability.

PUMP HOUSE STRUCTURE OVERLAY

The tubular structure shall be DA finish on each side of the pump compartment.

This option is for aluminum structure only.

RUNNING BOARDS

The pump compartment running boards shall be made of a structural tubular framework. The tubular frame supports all loads by transmitting the loads through the pump compartment structure directly to the chassis frame rails.

The running boards shall be independent of the apparatus body and shall be integrated to the pump compartment structure only, eliminating any pump compartment to body interference. This is essential in keeping a truly 'modular' configuration. Slip-resistant abrasive adhesive materials shall be applied to the top surface of the running board framework to provide a suitable stepping surface where applicable.

EMBOSSSED ALUMINUM DIAMOND PLATE OVERLAYS

The side running boards shall have a .188 inch (4.76 mm) embossed aluminum diamond plate overlays installed. The stepping areas shall be as large as possible, overlapping the perimeter of the running board structure.

LEFT SIDE SLIDE OUT PLATFORM

There shall be an OnScene brand slide out platform installed under the left side pump compartment running board. The platform shall be as wide as possible to fit the pump compartment and shall be approximately 16.00 inches (406.40 mm) deep when extended. The platform shall lock into place while in the extended and stowed positions. The platform surface shall be constructed of .188 inch (4.76 mm) embossed aluminum diamond plate material to provide a slip resistant stepping surface.

There shall be a reinforcement channel on the back of the step.

If the slide out step is not properly stowed and the parking brake is released, it shall activate the hazard light in the cab to alert the crew.

RIGHT SIDE SLIDE OUT PLATFORM

There shall be an OnScene brand slide out platform installed under the left side pump compartment running board. The platform shall be as wide as possible to fit the pump compartment and shall be between 12.00 inches (304.80 mm) and 16.00 inches (406.40 mm) deep when extended pending exhaust configuration.

The platform shall lock into place while in the extended and stowed positions. The platform surface shall be constructed of .188 inch (4.76 mm) embossed aluminum diamond plate material to provide a slip resistant stepping surface.

There shall be a reinforcement channel on the back of the step.

If the slide out step is not properly stowed and the parking brake is released, it shall activate the hazard light in the cab to alert the crew.

PRESSURE GOVERNOR, MONITORING, and MASTER PRESSURE DISPLAY

Fire Research "InControl 400" Series pressure governor and monitoring display kit shall be installed. The kit shall include a control module, intake pressure sensor, discharge pressure sensor, and cables. The control module case shall be waterproof and have dimensions not to exceed 5 1/2" high by 10 1/2" wide by 2" deep. The control knob shall be 2" in diameter with no mechanical stops, have a serrated grip, and a red idle push button in the center. It shall not extend more than 1 3/4" from the front of the control module. Inputs for monitored information shall be from a J1939 databus or independent sensors. Outputs for engine control shall be on the J1939 databus or engine specific wiring.

The following continuous displays shall be provided:

Pump discharge; shown with four daylight bright LED digits more than 1/2" high

Pump Intake; shown with four daylight bright LED digits more than 1/2" high

Pressure / RPM setting; shown on a dot matrix message display

Pressure and RPM operating mode LEDs

Throttle ready LED

Engine RPM; shown with four daylight bright LED digits more than 1/2" high

Check engine and stop engine warning LEDs

Oil pressure; shown on a dual color (green/red) LED bar graph display

Engine coolant temperature; shown on a dual color (green/red) LED bar graph display

Transmission Temperature: shown on a dual color (green/red) LED bar graph display

Battery voltage; shown on a dual color (green/red) LED bar graph display.

The dot-matrix message display shall show diagnostic and warning messages as they occur. It shall show monitored apparatus information, stored data, and program options when selected by the operator. All LED intensity shall be automatically adjusted for day and nighttime operation.

The program shall store the accumulated operating hours for the pump and engine to be displayed with the push of a button. It shall monitor inputs and support audible and visual warning alarms for the following conditions:

High Battery Voltage
Low Battery Voltage (Engine Off)
Low Battery Voltage (Engine Running)
High Transmission Temperature
Low Engine Oil Pressure
High Engine Coolant Temperature
Out of Water (visual alarm only)
No Engine Response (visual alarm only).

The program features shall be accessed via push buttons and a control knob located on the front of the control panel. There shall be a USB port located at the rear of the control module to upload future firmware enhancements.

Inputs to the control panel from the pump discharge and intake pressure sensors shall be electrical. The discharge pressure display shall show pressures from 0 to 600 psi. The intake pressure display shall show pressures from -30 in. Hg to 600 psi.

The governor shall operate in two control modes, pressure and RPM. No discharge pressure or engine RPM variation shall occur when switching between modes. A throttle ready LED shall light when the interlock signal is recognized. The governor shall start in pressure mode and set the engine RPM to idle. In pressure mode the governor shall automatically regulate the discharge pressure at the level set by the operator. In RPM mode the governor shall maintain the engine RPM at the level set by the operator except in the event of a discharge pressure increase. The governor shall limit a discharge pressure increase in RPM mode to a maximum of 30 psi.

Other safety features shall include recognition of no water conditions with an automatic programmed response and a push button to return the engine to idle.

INTAKE PRESSURE RELIEF VALVE

A Task Force Tips model #A18XX pressure relief valve shall be provided. The valve shall have an easy to read adjustment range from 90 to 300 PSI with easy to read 90, 125, 150, 200, 250, 300 psi settings and an "OFF" position. Pressure adjustment can be made utilizing a ¼" hex key, 9/16" socket or 14mm socket.

For corrosion resistance the cast aluminum valve shall be a hardcoat anodized with a powder coat interior and exterior finish. The valve shall meet (NFPA) 1901, Standard for Automotive Fire Apparatus, requirements for pump inlet relief valves. The unit shall be covered by a five year warranty. The valve shall be preset at 125 PSI (860 kPa) suction inlet pressure, unless otherwise shop noted. The valve shall be installed inside the pump compartment where it will be easily accessible for future adjustment. The excess water shall be plumbed to the atmosphere and shall dump on the opposite side of the pump operator.

For normal pumping operations, the relief valve shall not be capped and there shall be a placard stating "DO NOT CAP" installed.

MASTER GAUGES

Class 1 4.50 inch (115 mm) gauges shall be supplied for the master intake and master discharge gauges.

The gauges shall be model LFP410.

GAUGE SCALE

The master intake gauge shall be marked for a reading from -30 to 400 PSI and the master discharge shall be marked for reading a discharge pressure of 0 to 400 PSI.

GAUGE FACE COLOR

Each gauge shall have black markings on a white face.

TESTING PORTS

Test port connections for pressure and vacuum shall be provided at the pump operator's panel. One (1) shall be connected to the intake side of the pump, and the other to the discharge manifold side of the pump.

Each port shall have 0.25 inch (6.35 mm) standard pipe thread connection and be manufactured of non-corrosive polished stainless steel or brass plugs.

TANK LEVEL GAUGE

Fire Research TankVision Pro model WLA400-A00 tank indicator kit shall be installed. The kit shall include an electronic indicator module, a pressure sensor, and a 20.00 foot sensor cable. The indicator shall show the volume of water in the tank on nine (9) easy to see super bright RGB LEDs. A wide view lens over the LEDs shall provide for a viewing angle of 180 degrees. The indicator case shall be waterproof, manufactured of Polycarbonate/Nylon material, and have a distinctive blue label.

The program features shall be accessed from the front of the indicator module. The program shall support self-diagnostics capabilities, self-calibration, six (6) programmable colored light patterns to display tank volume, adjustable brightness control levels and a datalink to connect remote indicators. Low water warnings shall include flashing LEDs at 1/4 tank, down chasing LEDs when the tank is almost empty. The indicator shall have an output for an audio alarm, warning indicator signal, valve/actuator control signal and an input for a silence button.

The indicator shall receive an input signal from an electronic pressure sensor. The sensor shall be mounted from the outside of the water tank near the bottom. No probe shall be placed on the interior of the tank. Wiring shall be weather resistant and have automotive type plug-in connectors.

AIR HORN BUTTON

There shall be an air horn activation red push button provided and installed on the pump operator's gauge panel.

The air horn button shall be of weather resistance type and labeled "AIR HORN".

PUMP COMPARTMENT UPPER STORAGE AREA

There shall be a transverse storage compartment provided in the upper section of the pump house compartment above the speedlay area. The approximate interior dimensions of this usable storage area shall be as wide as practical by 33.25 inches high by 94.00 inches deep. The compartment shall be constructed of .125 inch (3.18 mm) smooth aluminum and allow access through either side. The compartment face shall be overlayed with material to match the pump house overlay. The underside of the compartment overhanging the pump panels shall be overlayed with this same material.

The interior shall be designed as transverse with the compartment floor lined with black ABS plastic for ease of stowing and un-stowing of equipment.

The compartment shall include provisions for storing the following equipment:

Individual storage slot for one (1) Stokes basket.

The slot shall have clear inside dimensions of 9.00 inches (228.60 mm) wide by 86.00 inches (2184.40 mm) long with a minimum height of 26.00 inches (660.40 mm). The storage compartment shall be centered to the length (side to side) of the pump compartment unless specified otherwise. The stokes baskets shall be removable without disturbing the storage of other items.

The remaining area shall be used for storage of long handled tools.

PUMP COMPARTMENT UPPER STORAGE DOORS

The upper storage shall include horizontally hinged flat panel doors secured with D ring latch and shall include a gas shock hold open device. Each door shall incorporate a 10.00 inch nylon strap that is attached with a footman loop. The doors shall be painted to match upper body job color.

If the door is not properly closed and the parking brake is released, it shall activate the hazard light in the cab to alert the crew.

MIDSHIP PUMP

The pump shall have the capacity of 1500 gallons per minute, measured in U.S. Gallons. The pump shall be a Hale Fire Pump, DSD single stage.

PUMP ASSEMBLY

The entire pump shall be assembled and tested at the pump manufacturer's factory. The pump shall be driven by a drive line from the truck transmission. The engine shall provide sufficient horsepower and RPM to enable pump to meet and exceed its rated performance.

The entire pump shall be hydrostatically tested to a pressure of 600 PSI. The pump shall be fully tested at the pump manufacturer's factory to the performance spots as outlined by (NFPA) 1901, Standard for Automotive Fire Apparatus. Pump shall be free from objectionable pulsation and vibration.

The pump body and related parts shall be of fine grain alloy cast iron, with a minimum tensile strength of 30,000 PSI (2069 bar). All metal moving parts in contact with water shall be of high quality bronze or stainless steel. Pump utilizing castings made of lower tensile strength cast iron not acceptable.

Pump body shall be vertically split on a single plane for easy removal of entire impeller assembly including clearance rings.

Pump shaft to be rigidly supported by two bearings for minimum deflection. The bearings shall be heavy-duty, deep groove ball bearings in the gearbox, and they shall be splash lubricated. Shaft seal comes standard with face-type, self-adjusting corrosion- and wear-resistant mechanical seals.

The pump impeller shall be hard, fine grain bronze of the mixed flow design; accurately machines, hand-ground and individually balanced. The vanes of the impeller intake eye shall be hand ground and polished to a sharp edge and be of sufficient size and design to provide ample reserve capacity utilizing minimum horsepower.

Impeller clearance rings shall be bronze, easily renewable without replacing impeller or pump volute body.

The pump shaft shall be heat-treated, electric furnace, corrosion resistant stainless steel.

Pump shaft must be sealed with double-lip oil seal to keep road dirt and water out of gearbox.

GEAR BOX

Pump gearbox shall be of sufficient size to withstand up to 16,000 lbs. ft. of torque of the engine. The drive unit shall be designed of ample capacity for lubrication reserve and to maintain the proper operating temperature.

The gearbox drive shafts shall be of heat-treated chrome nickel steel and at least 2.75 inches in diameter, on both the input and output drive shafts. They shall withstand the full torque of the engine.

All gears, drive and pump, shall be of highest quality electric furnace chrome nickel steel. Bores shall be ground to size and teeth integrated and hardened, to give an extremely accurate gear for long life, smooth, quiet running, and higher load carrying capability. An accurately cut spur design shall be provided to eliminate all possible end thrust.

The pump ratio shall be selected by the apparatus manufacturer to give maximum performance with the engine and transmission selected.

If the gearbox is equipped with a power shift, the shifting mechanism shall be a heat treated, hard anodized aluminum power cylinder, with stainless steel shaft. An in-cab control for rapid shift shall be provided that locks in road or pump.

For automatic transmissions, three green warning lights shall be provided to indicate to the operator(s) when the pump has completed the shift from Road to Pump position. Two green lights to be located in the truck driving compartment and one green light on pump operator's panel adjacent to the throttle control. For manual transmissions, one green warning light will be provided for the driving compartment. All lights to have appropriate identification/instruction plates.

PUMP WARRANTY

Hale Products Inc. shall provide a limited manufacturer's pump warranty to be free from defects in material and workmanship, under normal use and service, for a period of two (2) years parts and labor and parts only for years three (3) through five (5), from the date placed

into service.

MECHANICAL PUMP SEAL

A mechanical seal shall be supplied on the inboard side of the pump. The mechanical seal must be two (2) inches in diameter and shall be spring-loaded, maintenance-free and self-adjusting. Mechanical seal construction shall be a carbon sealing ring, stainless steel coil spring, Viton rubber cup, and a tungsten carbide seat.

PUMP SHIFT

The drive unit shall be provided with an air pump shift system. The control valve shall be a spring loaded guard lever that locks in "Road" or "Pump" mode.

To the left of the pump shift control, there shall be two indicator lights to show the position of the pump when the control is moved to "Pump" position. A green light shall be energized when the pump shift has been completed and shall be labeled "PUMP ENGAGED"; a second green light shall be labeled "OK TO PUMP" energized when both the pump shift has been completed and the chassis automatic transmission is engaged.

A third green indicator light shall be installed adjacent to the throttle on the pump operator's panel. This light shall be labeled "Throttle Ready".

In addition to this indicator light, an additional indication shall be provided to the pump operator at the panel when the pump is ready to pump. This additional indication shall be that one (1) of the operator's panel illumination lights will only activate when the "OK TO PUMP" indicator is lit.

AIR PUMP SHIFT LOCATION

The pump shift shall be mounted in the "best fit" location as determined by the apparatus manufacture.

AIR PRIMER SYSTEM

The priming system shall be a Trident Emergency Products compressed air powered high efficiency, multi-stage, venturi based Air Prime System.

All wetted metallic parts of the priming system are to be of brass and stainless steel construction. A single panel mounted control will activate the priming pump and open the priming valve to the pump.

The priming components shall be mounted above the highest priming point on the suction side of the pump to permit air removal and allow for drainage. The primer shall also automatically drain when the panel control actuator is not in operation. The inlet side of the primer shall include a brass 'wye' type strainer with removable stainless steel fine mesh strainer to prevent entry of debris into the primer body.

The system shall employ an 80 PSI (5.5 bar) pressure protection valve, located on the chassis auxiliary air tank.

The primer shall be covered by a five (5) year parts warranty.

PRIMER CONTROL

There shall be a push button control to actuate the primer control valve.

There shall be a primer control for each of the locations listed below:

PRIMER CONTROL LOCATION

A priming valve shall be connected to prime the main pump body.

PRIMER CONTROL LOCATION

A priming valve shall be connected to prime the front intake, forward of the intake valve. The plumbing shall include connections to all high points in the plumbing.

DISCHARGE AND INLET MANIFOLDS

A pump manifold inlet shall be provided on the pump as required for the layout. The inlet(s) shall protrude up to 2.00 inches (50 mm) away from the side panels and maintain a low connection height.

A discharge manifold shall also be added to the pressure side of the pump to feed the specified discharge waterways.

MAIN PUMP INLET-LEFT SIDE

A 6.00 inch (150 mm) pump manifold inlet shall be provided on the left side of the pump. The inlet shall protrude up to 2.00 inches (50 mm) away from the side panel and maintain a low connection height.

The main pump inlet shall have National Standard Threads and includes a removable screen designed to provide cathodic protection for reducing deterioration in the pump.

6" CHROME PLATED BRONZE CAP

There shall be one (1) 6.00 inch (150 mm) long handled chrome plated cap installed on the Steamer Inlet.

The cap shall be National Standard Thread.

MAIN PUMP INLET-RIGHT SIDE

A 6.00 inch (150 mm) pump manifold inlet shall be provided on the right side of the pump. The inlet shall protrude up to 2.00 inches (50 mm) away from the side panel and maintain a low connection height.

The main pump inlet shall have National Standard Threads and includes a removable screen designed to provide cathodic protection for reducing deterioration in the pump.

6" CHROME PLATED BRONZE CAP

There shall be one (1) 6.00 inch (150 mm) long handled chrome plated cap installed on the Steamer Inlet.

The cap shall be National Standard Thread.

MASTER DRAIN VALVE

A Trident manifold type drain valve shall be installed in the pump compartment. All pump drains shall be connected to the master drain valve. The drain valve shall be controlled from the left side lower pump house sill. The control shall be a hand wheel knob marked "open" and "closed". The drain shall be located such that it shall not interfere with pumping operations or function such as soft suction hoses, etc. nor shall it protrude past the outer edge of the apparatus, to prevent damage to the valve. In some cases, it is necessary to locate the master drain in a secondary location to ensure proper draining. If no lower or vertical sill exists, the drain shall be located below the bottom outside edge of the hose body near the forward most corner on the driver's side hose body. The drain shall not protrude past the outer edge of the body, thus preventing damage to the valve.

THERMAL RELIEF VALVE

A Hale TRV-120-L thermal protection device shall be installed on the apparatus pump to monitor pump water temperature and open to relieve water to cool the pump.

The thermal protection devices shall be set to relieve water when the temperature of the pump exceeds 120 degrees Fahrenheit (49 degrees Celsius).

The components of the thermal protection device shall be manufactured of brass and stainless steel and be compatible with most foam concentrates. The thermal protection device shall have 1-1/4 inch NPT threads for easy adaptability to existing pump discharge openings. The discharge line shall be 3/8 inch diameter tubing vented to atmosphere or back to the booster tank. The thermal protection device shall have a hydrostatic test rating of 600 PSI (41.3 bar).

A warning light and audible alarm shall be installed on the pump panel to alert the operator that the relief valve is open. The relief valve shall discharge out below the running board.

PUMP COOLING LINE

There shall be a .38 inch (9.5 mm) line running from the pump to the water tank to assist in keeping the pump

PUMP ANODES

Two (2) pump anodes shall be installed in the pumping system, one (1) on the discharge side and one (1) on the suction side, to prevent damage from galvanic corrosion within the pump system.

STAINLESS STEEL PLUMBING

All auxiliary suction and discharge plumbing related fittings, and manifolds shall be fabricated with a minimum of 3.00 inch (77 mm), or greater as required by design, schedule 10 stainless steel pipe; brass or high pressure flexible piping with stainless steel couplings. Galvanized components and/or iron pipe shall NOT be accepted to ensure long life of the plumbing system without corrosion or deterioration of the waterway system. Where waterway transitions are critical (elbows, tees, etc.), no threaded fittings shall be allowed to promote the smooth transition of water flow to minimize friction loss and turbulence. All piping components and valves shall be non-painted, unless otherwise specified. All piping welds shall be wire brushed and cleaned for inspection and appearance.

The high pressure flexible piping shall be black SBR synthetic rubber hose with 700 PSI working pressure and 1200 PSI burst pressure for flexible piping sizes 1.50 inches (38 mm) through 4.00 inches (100 mm). Sizes .75 inch (19 mm), 1.00 inch (25 mm) and 5.00 inches (125 mm) are rated at 250 PSI working pressure and 1000 PSI burst pressure. All sizes are rated at 30 in HG vacuum. Reinforcement consists of two plies of high tensile strength tire cord for all sizes and helix wire installed in sizes 1.00 inch (25 mm) through 5.00 inches (125 mm) for maximum performance in tight bend applications. The material has a temperature rating of -40 degrees Fahrenheit to +210 degrees Fahrenheit water from overheating. A valve shall be installed on the operator's panel.

The stainless steel full flow couplings are precision machined from high tensile strength stainless steel. All female couplings are brass. Mechanical grooved and male .75 inch (19 mm) and 1.00 inch (25 mm) couplings are brass. A high tensile strength stainless steel

ferrule with serrations on the I.D. is utilized to assure maximum holding power when fastening couplings to hose.

PUMP HOUSE LINE PROTECTION

All drain lines for the discharges, suctions, ABS discharge gauge lines and any other appropriate connections in the pump house area shall have a protective cover provided on the lines in the required areas of the lines to prevent the lines from rubbing on any other components in the pump house area. All drain lines, ABS lines, high pressure discharge lines and electrical wiring in the pump house area shall be properly and neatly routed, wire tied, and rubber coated "P" clamped, to keep the items secured.

DRAIN VALVES

An Innovative Controls 3/4" quarter turn drain valve shall be included on each discharge, gated intake, and steamer valve (if applicable). A side stem, long stroke chrome plated lift handle shall be provided on the drain valve to facilitate use with a gloved hand. The drain valve shall have an ergonomically designed handle with a recessed verbiage tag area easily read by the operator before opening. The drain valve shall be connected to the valve with a flexible hose that is routed in such a manner as to assure complete drainage to below the apparatus.

FRONT SUCTION

There shall be an auxiliary steamer inlet located on front of the apparatus.

INTAKE VALVE

A 5.00 inch (125 mm) Akron Brass 7000 series electrically actuated "Butterfly" valve with quarter turn air bleeder valve shall be plumbed to the water supply side of the intake valve (with a .75 inch NPT port) to help evacuate air from the system and avoid cavitation of the pump. A manual override control shall be provided to actuate the manual overrides on the apparatus. The override control shall be installed in an easily accessible location.

STYLE 9333 VALVE CONTROLLER

The controller shall be an Akron Brass Style 9333 Navigator Pro™ 2.0 Valve Controller. The electric controls must be of true position feedback design, requiring no clutches in the motor or current limiting. The unit must be completely sealed with momentary open, close as well as an optional one touch full open feature to operate the actuator. Two additional buttons shall be available to be used for preset selection, preset activation and menu navigation. The controller must have up to three preset locations that can be user set and easily recalled upon each use. The unit must be capable of being used in conjunction with at least two additional displays to control one valve. The unit must provide position indication through a full color backlit LCD display. The display shall be a full color LCD display with a backlight. It shall have manual adjustment of the brightness as well as an auto-dimming option. The unit must carry a five year warranty.

INTAKE PRESSURE RELIEF VALVE

A Task Force Tips model #A18 pressure relief valve with a range of adjustment from 90 to 300 PSI shall be installed inside pump compartment piped to the suction side of the

pump.

The valve shall be preset at 125 PSI (860 kPa) suction inlet pressure. The valve shall be installed inside the pump compartment where it will be easily accessible for future adjustment. The excess water shall be plumbed to the atmosphere and shall dump on the opposite side of the pump operator. For normal pumping operations, the relief valve shall not be capped and there shall be a placard installed stating "DO NOT CAP".

INTAKE PLUMBING

The plumbing shall consist of 5.00 inch (125 mm) stainless steel piping.

SUCTION/INTAKE TERMINATION

The termination shall include the following components:

One (1) 5.00 inch (125 mm) NPT X 5.00 inch (125 mm) NST 90 degree swiveling elbow

One (1) 5.00 inch (125 mm) NST long handled vented chrome cap

DRAINS

The suction shall be plumbed with manually operated drains in the lowest point(s) of the piping. Two (2) drains shall be installed on each front suction pipe. One (1) drain will be located forward of the front wheel, and one (1) drain will be located rearward of the front wheel. The drains shall be located on the bottom sides of the front suction pipe.

SUCTION LOCATION

The front suction shall be located through the front bumper outboard of the right hand side frame rail.

LEFT SIDE INLET

There shall be one (1) gated suction inlet with .75 inch (19mm) bleeder installed on the left side of the apparatus with the following specified components.

INTAKE VALVE

A 2.50 inch (65 mm) Akron Brass 8000 series rack and sector actuated valve with a push pull control at the valve.

INTAKE VALVE CONTROL

The intake shall be controlled from a rack and sector actuator having an ergonomically designed T-handle. The handle shall be chrome-plated with name plate insertion recess area.

INTAKE PLUMBING

The plumbing shall consist of 2.50 inch (65 mm) piping and shall incorporate a manual drain control installed below the pump area for ease of access.

SUCTION/INTAKE TERMINATION

The termination shall include the following components:

One (1) 2.50 inch (65 mm) NST swivel female straight adapter with screen

One (1) 2.50 inch (65 mm) self-venting plug, secured by a chain

LEFT SIDE DISCHARGE

There shall be one (1) gated discharge installed on the left side of the apparatus with the

following specified components.

DISCHARGE VALVE

A 2.50 inch (65 mm) Akron Brass 8000 series rack and sector actuated valve with a stainless steel ball.

DISCHARGE VALVE CONTROL

The discharge shall be controlled from a rack and sector actuator having an ergonomically designed T-handle. The handle shall be chrome-plated with name plate insertion recess area.

DISCHARGE PLUMBING

The plumbing shall consist of 2.50 inch (65 mm) piping and shall incorporate a manual drain control installed below the pump area for ease of access.

DISCHARGE TERMINATION

The discharge termination shall include the following components:

- One (1) 2.50 inch (65 mm) Male NST adapter
- One (1) 2.50 inch (65 mm) NST female by male swivel with 45 degree elbow
- One (1) 2.50 inch (65 mm) female by 1.50 inch (38 mm) male reducer
- One (1) 1.50 inch (38 mm) female self-venting cap, secured by a chain

RIGHT SIDE DISCHARGE

There shall be one (1) gated discharge installed on the right side of the apparatus with the following specified components.

DISCHARGE VALVE

A 2.50 inch (65 mm) Akron Brass 8000 series swing-out valve with a stainless steel ball.

DISCHARGE VALVE CONTROL

The discharge shall be controlled from the pump operator's panel location.

DISCHARGE PLUMBING

The plumbing shall consist of 2.50 inch (65 mm) piping and shall incorporate a manual drain control installed below the pump area for ease of access.

DISCHARGE TERMINATION

The discharge termination shall include the following components:

- One (1) 2.50 inch (65 mm) Male NST adapter
- One (1) 2.50 inch (65 mm) NST female by male swivel with 45 degree elbow
- One (1) 2.50 inch (65 mm) female by 1.50 inch (38 mm) male reducer
- One (1) 1.50 inch (38 mm) female self-venting cap, secured by a chain

RIGHT SIDE MASTER DISCHARGE

There shall be one (1) master discharge installed on the right side of the apparatus provided with the following specified components.

DISCHARGE VALVE

A 4.00 inch (100 mm) Akron Brass 8000 series valve with a 3.00 inch handwheel control

and position indicator.

DISCHARGE PLUMBING

The plumbing shall consist of 4.00 inch (100 mm) piping and shall incorporate a manual drain control installed below the pump area for ease of access.

DISCHARGE TERMINATION

The discharge termination shall include the following components:

One (1) 4.00 inch (100 mm) NST adapter

One (1) 4.00 inch (100 mm) NST female by 4.00 inch (100 mm) Storz with 30 degree elbow

One (1) 4.00 inch (100 mm) Storz cap, secured by a chain

LEFT REAR DISCHARGE

There shall be one (1) gated discharge installed on the left rear of the apparatus with the following specified components.

DISCHARGE VALVE

A 2.50 inch (65 mm) Akron Brass 8000 series swing-out valve with a stainless steel ball.

DISCHARGE VALVE CONTROL

The discharge shall be controlled from the pump operator's panel location.

DISCHARGE PLUMBING

The plumbing shall consist of 2.50 inch (65 mm) piping and shall incorporate a manual drain control installed below the pump area for ease of access.

Discharge shall be located high on the left side, directly under the hose bed if possible.

DISCHARGE TERMINATION

The discharge termination shall include the following components:

One (1) 2.50 inch (65 mm) Male NST adapter

One (1) 2.50 inch (65 mm) NST female swivel by male with 45 degree polished elbow

One (1) 2.50 inch (65 mm) female self-venting cap, secured by a chain

RIGHT REAR DISCHARGE

There shall be one (1) gated discharge installed on the right rear of the apparatus with the following specified components.

DISCHARGE VALVE

A 2.50 inch (65 mm) Akron Brass 8000 series swing-out valve with a stainless steel ball.

DISCHARGE VALVE CONTROL

The discharge shall be controlled from the pump operator's panel location.

DISCHARGE PLUMBING

The plumbing shall consist of 2.50 inch (65 mm) piping and shall incorporate a manual drain control installed below the pump area for ease of access.

DISCHARGE TERMINATION

The discharge termination shall include the following components:

One (1) 2.50 inch (65 mm) Male NST adapter

One (1) 2.50 inch (65 mm) NST female swivel by male with 45 degree polished elbow

One (1) 2.50 inch (65 mm) female self-venting cap, secured by a chain

PUMP COMPARTMENT SPEEDLAYS

The speedlay hose beds shall be constructed as an integral part of the pump compartment tubular structure with aluminum slotted flooring provided for hose area drainage.

Stainless steel scuff plates shall be installed at the bottom and at the vertical edges of the crosslay openings to protect the hose and hose ends.

A removable speedlay hose bed tray shall be provided for each bay specified.

Chiksan swivels shall be installed above each plumbed speedlay hose bed to allow removal of the speedlay trays and accessible enough for hose couplings to be tightened on to chiksans. Chiksan swivels shall swing from left to right to allow attached hose to be deployed from either side.

1 3/4" SPEEDLAY

A speedlay with the following specified components shall be provided for up to 250 feet (76.2 m) of 1.75 inch (44.4 mm) hose.

There shall be a total of two (2) provided.

DISCHARGE VALVE

A 2.00 inch (50 mm) Akron Brass 8000 series swing-out valve with a stainless steel ball.

DISCHARGE VALVE CONTROL

The discharge shall be controlled from the pump operator's panel location.

DISCHARGE PLUMBING

The plumbing shall consist of 2.00 inch (50 mm) piping and shall incorporate a manual drain control installed below the pump area for ease of access.

DISCHARGE TERMINATION

The discharge termination shall include the following components:

One (1) 2.00 inch (50 mm) NPT x 1.50 inch (38 mm) NST brass chiksan swivel

D&S CARGO NETTING COVERS SPEEDLAY ENDS

The speedlay hose bed area shall have individual D&S Brand custom cargo netting end covers provided and installed for each bay opening on both sides of the apparatus. The cargo netting shall be secured on the bottom edge with extrusion and with side push style clips at the top for ease of entry.

SPEEDLAY COVER COLOR

The speedlay hose bed covers shall be red in color

BOOSTER REEL

There shall be an electric rewind booster reel with automatic brake installed on the apparatus. The booster reel shall have a capacity to handle 1.00-inch diameter (25.4 mm) booster hose.

There shall be a manual rewind device provided. A manual crank shall be mounted adjacent to booster reel.

NIEDNER BOOSTER HOSE

The reel shall come equipped with 200 feet (60 m) of 800 psi (55 BAR) Niedner booster hose.

The hose shall be provided in two (2) 100 foot (30 m) lengths with hardcoat aluminum couplings.

REEL FINISH

The hose reel specified shall be steel and painted the standard red utilized by Hannay.

HOSE REEL VALVE

The reel shall be plumbed to the pump with a 1.00 inch (25.40 mm) quarter turn Akron brass 8000 series ball valve and 1.00 inch (25.40 mm) high pressure hose and couplings. The valve shall be controlled from the operator's panel.

REWIND ACTIVATION

An electric rewind switch shall be located adjacent to the booster reel. The switch shall have a weather resistant rubber cover and a label indicating its function.

The switch shall be labeled "HOSE REEL".

HOSE REEL LOCATION

The hose reel shall be mounted as high as possible and centered on the rear wall of the Rear Center, B-1 compartment.

HOSE REEL ROLLERS

There shall be a four-way roller assembly provided and installed directly to the reel.

Two (2) additional stainless steel hose roller guides shall be provided and installed, one (1) on either side of the compartment door openings. The rollers shall allow free hose deployment and retraction while preventing sharp edges from cutting or damaging the hose.

HOSE REEL BLOW OUT

There shall be an air "blowout" system provided and installed on the apparatus. The air blow out system shall be connected to the chassis air brake system. A check valve shall be installed between the chassis system and the reel blow out system. A ¼ turn manual control valve shall be installed on the pump operator's panel for the air blow out system. The valve shall be labeled "REEL BLOW OUT".

BOOSTER REEL GAUGE

There shall be a pressure gauge supplied for the Booster Reel as specified below.

DISCHARGE GAUGES

A Class 1 2.50 inch (90 mm) gauge shall be supplied for reading the pressure of each discharge greater than 1.50 inches (38 mm) in diameter, unless otherwise specified.

The gauge shall be a model LFP200.

GAUGE SCALE

Each gauge shall be marked for reading a pressure range of 0-400 PSI.

GAUGE FACE COLOR

Each gauge shall have black markings on a white face.

BEZELS FOR 2.5" DISCHARGE GAUGES

Highly-polished stainless steel Innovative Control bezels shall be provided around each of the 2.50 inch (65 mm) discharge pressure gauges to prevent corrosion and protect lenses and gauge cases. The gauges shall be installed into decorative chrome-plated mounting bezels that incorporate valve identifying verbiage and/or color labels.

APPARATUS PLUMBING LABELING

Innovative Controls verbiage tag bezels shall be installed. The bezel assemblies will be used to identify apparatus components. These tags shall be designed and manufactured to withstand the specified apparatus service environment and shall be backed by a warranty equal to that of the exterior paint and finish. The verbiage tag bezel assemblies shall include a chrome-plated panel-mount bezel with durable easy-to-read UV resistant polycarbonate inserts featuring the specified verbiage and color coding. These UV resistant polycarbonate verbiage and color inserts shall be subsurface screen printed to eliminate the possibility of wear and protect the inks from fading. Both the insert labels and bezel shall be backed with 3M permanent adhesive, which meets UL969 and NFPA standards.

PLUMBING LABELS

The plumbing labels, where applicable, shall be full color in place of the standard grey. Color code tag sheet to be provided during the preconstruction meeting.

TANK TO PUMP LINE

The connection between the tank and the pump shall be capable of the flow recommendations as set forth in (NFPA) 1901, Standard for Automotive Fire Apparatus, latest revision and shall be tested to those standards when the pump is being certified. One (1) non-collapsible flexible hose and valve shall be incorporated into the tank to pump plumbing to allow movement in the line as the chassis flexes to avoid damage during normal road operation. Four (4) inch stainless steel schedule 10 piping shall be used to complete the connection from the tank to pump valve to the water tank.

TANK TO PUMP CHECK VALVE

There shall be a tank to pump check valve, conforming to NFPA standard requirements to prevent water from back flowing at an excessive rate if the pump is being supplied from a pressurized source. The check valve shall be mounted as an integral part of the pump suction extension. A hole up to .25 inch (6.00 mm) is allowable in the check valve to release steam or other pressure buildup so that the void between the valve and check valve may drain of water that could be subject to freezing.

TANK TO PUMP VALVE

A 3.00 inch (77 mm) Akron Brass 8000 series swing-out valve with a stainless steel ball.

VALVE CONTROL

The valve shall be controlled from the pump operator's panel location.

TANK FILL LINE

One (1) 2.00 inch (50.80 mm) tank fill/recirculating line shall be installed from the pump directly to the booster tank.

TANK FILL VALVE

A 2.00 inch (50 mm) Akron Brass 8000 series swing-out valve with a stainless steel ball.

VALVE CONTROL

The valve shall be controlled from the pump operator's panel location.

Frame Body - ALUMINUM

The apparatus body shall be a frame design, which serves as an incredibly durable, structural body framework. This framework acts as a series of beams and columns that support and protect the body and its contents. The space frame design provides maximum torsional resistance and load capabilities. The entire space frame structure shall be welded together utilizing an A.W.S. Certified welding procedure. The space frame design shall also be required because it provides energy absorbing impact zones in the structure, thus providing increased safety to the rest of the apparatus and personnel on board.

Documented proof

of this extra safety shall be required upon request. The body structure shall consist entirely of closed section members, except where the body is mounted to the chassis. Closed section members (such as square, rectangular, triangular, or round tubes) are required because they provide maximum strength and torsion rigidity. This solid tubular structural style of design ultimately adds longevity to the body structure by eliminating flex and twists in material, creating less stress and fatigue. Body designs that use independent sub-frames will not be acceptable.

BODY STRUCTURE MEMBERS

The body shall have triangular shaped structural members in certain areas of the body. This shape is required to prevent loss of useable compartment space. Other body structure members shall be square or rectangular. Each structural member will have a nominal outside dimension of 2.50 inches (63.50 mm) in at least one direction. The body shall be

designed for maximum strength to weight ratio, therefore the gauge of sheet metal and structural members varies from .125 inches (3.18 mm) to .250 inches (6.35 mm) throughout, dependent on the design requirement.

BODY MATERIAL TYPE

All body structural members shall be Aluminum 6061-T6 alloy material. All .125 inch (3.18 mm) sheet material shall be Aluminum Alloy 5052-H32, and .250 inch (6.35 mm) sheet materials shall be Aluminum Alloy 3003. These alloys are required because it provides optimum all-around performance for strength, manufacturing properties, and corrosion resistance.

ECK® ANTI-CORROSION PROCESS

Absolutely no dissimilar metals shall be used in the body and its supporting substructure without being separated by Eck®, which prevents corrosion by providing a barrier between dissimilar metals, sealing out moisture and absorbing energy created by a dissimilar metal reaction.

FRONT BODY COMPARTMENT WALLS

The front compartment walls of both forward most compartments shall be sheet finished. No overlay material shall be visible from the interior of the compartments.

REAR BODY COMPARTMENT WALLS

The rear compartment walls of both rearward most compartments shall be sheet finished. No overlay material shall be visible from the interior of the compartments. Access panels from the rear walls shall be strategically placed to ensure access to the rear taillight clusters for any servicing that may be completed.

COMPARTMENT TOP

The top of the compartments shall be an integral portion of the body. No overlay material shall be visible from the interior of the compartments.

COMPARTMENT FLOORS

The body compartments shall be enclosed with aluminum sheet metal as specified above. The compartment floors shall have a 1.00 inch (25.40 mm) lip downward at the door opening side of the compartment. This lip shall integrate with a structural member on the bottom edge and form a “sweep-out” compartment. This design shall also allow for a structural flush fitting door frame and a complete door/weather seal.

COMPARTMENT LOAD CAPACITY

Each compartment shall have a minimum of one additional structural compartment floor support centered on the underside of the compartment floor. This additional member shall be integral with the rest of the body structure. Each compartment must be designed, and 3rd party analyzed to carry a working load of:

Full depth side compartment: 1,000 lbs (453.59 kg) per compartment

Half depth side compartment: 750 lbs (340.19 kg) per compartment

Rear center compartment: 1,500 lbs (680.39 kg)

EXTERIOR HOSE BED WALLS

The exterior hose bed walls shall be an integral portion of the body. The wall shall give a

smooth exterior look and finish with no vertical supports tubing visible from the exterior of the truck.

FASTENERS

All bolts and nuts used in the finish construction of the apparatus shall be coated stainless steel which helps prevent dissimilar metal electrolytic reaction and corrosion. Any bolt extending into a compartment or into the hose bed area shall have an acorn nut attached or be protected in such manner where sharp edges are avoided.

FINITE ELEMENT ANALYSIS

The proposed body design must have completed a review and analysis by a legitimate 3rd party engineering firm. At a minimum, the 3rd party must have conducted a computer model finite element analysis of the proposed design. The analysis is to include real world working load scenarios. Analysis to cover both static and dynamic situations must be completed. The purpose of the finite element analysis is to ensure proper design of the apparatus body, and that it is capable of carrying the typical fire apparatus loads and those specified by NFPA for equipment. The analysis process must conclude that the body structure is properly designed and manufactured to provide longevity under normal conditions. The 3rd party must also validate the manufacturing processes are consistent with the design and analysis performed. Proof of having completed this testing must be submitted with the bid.

PAINT SPECIFICATIONS

All bright metal fittings, if unavailable in stainless steel, shall be heavily chrome plated. Critical body and sub-frame area which cannot be primed after assembly shall be pre-painted.

All welded metal surfaces shall be ground to a smooth surface prior to a degreasing and high pressure, high temperature phosphatizing process. The entire surface shall be sprayed with a non-chromate sealing compound to prevent formulation of stains or flash rust on previously phosphatized parts.

The paint applied to the apparatus shall be Akzo Nobel, Sikkens brand, LVBT650 basecoat, applied throughout a multi-step process including at least two coats of each color and clear coat finish

The coating shall be an infra-red, baked air dried. The coatings shall provide full gloss finished suitable for application by high-pressure airless or conventional low pressure air atomizing spray. The coatings shall not contain lead, cadmium or arsenic. The polyisocyanate component shall consist of only aliphatic isocyanates, with no portion being aromatic isocyanates in character. The solvents used in all components and products shall not contain ethylene glycol mono-ethyl ethers or their acetates (commercially recognized as cello solves), nor shall they contain any chlorinated hydrocarbons. The products shall have no adverse effects on the health or nor present any unusual hazard to personnel when used according to manufacturer's recommendations for handling and proper protective safety equipment, and for its intended use. The coating system, as supplied and recommended for application, shall meet all applicable federal, state and local laws and regulations now in force or at any time during the courses of the bid. The manufacturer shall supply (upon request) for each product and component of the system, a properly complete OSHA "Safety Data Sheet".

The following documents of the issue in effect on the date of the invitation to quote form a part of this document to the extent specified herein:

Federal Standards: Number 141A and 141B paint, varnish, lacquer and related material: methods of inspection, sampling, and testing.

Military Standard: MIL-C 83486B Coating, Urethane, Aliphatic Isocyanates, for Aerospace applications.

Industry Methods and Standards: ASTM Method of Analysis (American Society for testing and Materials).

BMS 10-72A (Boeing Material Specifications).

The entire exterior body structure (excluding roll-up doors) shall receive the primer coats and the finish coats. The apparatus body will be painted in a down draft type paint booth to reduce dust, dirt or impurities in the finish paint. The painted surfaces shall have a finish with no runs, sags, craters, pinholes or other defects. The coating will meet the following test performance properties as a minimum standard.

BODY PAINT COLOR

The apparatus body shall be painted red, paint code to be provided.

SUPERLINER COMPARTMENT FINISH

The compartment interiors shall be coated with Superliner.

COMPARTMENT FINISH COLOR

The Superliner Color shall be Medium Gray.

UNDERCOATING

The underside of the apparatus body shall be cleaned and prepared for the application of a sprayed on automotive type undercoating for added corrosion resistance. The undercoating is to be of a quick dry rubberized, solvent based coating that is (black) in color. Resists rust and abrasion as it seals out dust and moisture. The application does not include any additional underbody, chassis or body cavity components.

STRUCTURAL BODY WARRANTY

A structural Aluminum body warranty shall be provided by the apparatus manufacturer for products of its manufacture to be free from defects in material and workmanship under normal use and service for a period of ten (10) years.

PAINT WARRANTY

A Prorated Paint Warranty shall be provided by the apparatus manufacturer for products of its manufacture to be free from defects in material and workmanship, under normal use and service, for a period of ten (10) years.

DIAMOND PLATE FRONT OVERLAYS

The entire front face of the apparatus body shall have aluminum diamond plate overlays installed.

RAW ALUMINUM REAR OVERLAYS

The entire rear face of the apparatus body shall have raw aluminum overlays installed for

the installation of chevron striping. All overlay materials shall be coated with 3M adhesive sealant on the back portion to provide an insulating barrier between dissimilar metals.

FRONT CORNER TRIM 1/8" ALUMINUM DIAMOND PLATE

The front of the apparatus body, vertical wall overlay shall be integrated with a 1/8" aluminum diamond plate 1.00 inch x 1.00 inch corner trim pieces for edge protection.

The vertical edge trim piece shall extend from the top to bottom and shall be fastened at a minimum of three locations, top, middle, and bottom.

REAR CORNER TRIM 1/8" ALUMINUM DIAMOND PLATE

The rear face of the apparatus body, vertical wall overlays shall be installed with a .125 inch aluminum diamond plate 1.00 inch by 1.00 inch corner trim piece, for edge protection. The vertical edge trim piece shall extend from the top to bottom and shall be fastened at a minimum of three locations, top, middle, and bottom. The vertical edge trim piece that is protecting the chevron striping surface or that is utilized for the purpose of striping, shall be secured utilizing fasteners only.

BODY MOUNTING SYSTEM

The entire body module assembly shall be mounted so that it "floats" above the chassis frame rails with torsion isolator assemblies to reduce the vibration and stress providing an extremely durable body mounting system. The body substructure shall be mounted above the frame to allow independent flexing to occur between the body and the chassis. Each assembly shall be mounted to the chassis frame rails with steel, gusseted mounting brackets. Each bracket shall be powder coated for corrosion resistance. Each body mount bracket shall be mounted to the side chassis frame flange with two 5/8"-UNC Grade 5 HHCS. Each assembly shall have a two-part rubber vibration isolator. The isolator shall be of a specific durometer to carry the necessary loads of the apparatus body, equipment, tank, water, and hose. The quantity of mounts utilized shall correspond directly to the anticipated weight being supported. Certain assemblies shall also incorporate a torsion spring. Helical coil springs shall be incorporated into specific mounts in tandem with the rubber isolators to minimize the stress absorbed by the body caused from chassis frame rail flexing. There shall be no welding to the chassis frame rail sides, web or flanges, or drilling of holes in the top or bottom frame flanges between axles. All body to chassis connections shall be bolted so that in the event of an accident, the body shall be easily removable from the truck chassis for repair or replacement.

Because of the constant vibration and twisting action that occurs in chassis frame rails and suspension, the torsion mounting system is required to minimize the possibility of premature body structural failures. The body mounting system shall have a lifetime warranty.

BODY STRUCTURE WIDTH

The width of the apparatus body from the outside of the left compartments to the outside of the right compartments shall be 99.00 inch (2.51 m) excluding any attached peripherals such as rub rails, fenderettes, grab handles, etc.

COMPARTMENT VENTILATION

To allow for proper air circulation & flow, each compartment shall have a venting route.

The venting locations shall be determined by best-fit for each body configuration. Chrome covered plate vents shall be installed appropriately on the compartment interior walls.

COMPARTMENTATION

The following compartments shall be supplied on the apparatus:

Compartment "L1"

There shall be one (1) full height compartment ahead of the rear wheels on the left side of the apparatus. The approximate interior dimensions of this compartment shall be 52.50 inches (1333.50 mm) wide by 69.00 inches (1752.60 mm) high with a lower depth of 25.50 inches (647.70 mm) and an upper depth of 12.50 inches (317.50 mm). The framed opening shall measure approximately 50.00 inches (1270.00 mm) wide by 65.00 inches (1651.00 mm) high. The compartment will have approximately 39.24 cubic feet (1.11 cu m) of space.

Compartment "L2"

There shall be one (1) compartment located directly over the rear wheels on the left side of the apparatus.

The approximate interior dimensions of this compartment shall be 62.00 inches (1574.80 mm) wide by 35.00 inches (889.00 mm) high with a depth of 12.50 inches (317.50 mm). The framed opening shall measure approximately 62.00 inches (1574.80 mm) wide by 31.00 inches (787.40 mm) high. The compartment will have approximately 15.70 cubic feet (0.44 cu m) of space.

Compartment "L3"

There shall be one (1) full height compartment located behind the rear wheels on the left side of the apparatus.

The approximate interior dimensions of this compartment shall be 52.50 inches (1333.50 mm) wide by 69.00 inches (1752.60 mm) high with an upper depth of 12.50 inches (317.50 mm) and the lower portion being transverse into the rear compartment, unless partitions are installed. The framed opening shall measure approximately 50.00 inches (1270.00 mm) wide by 65.00 inches (1651.00 mm) high. The compartment will have approximately 39.24 cubic feet (1.11 cu m) of space.

Compartment "R1"

There shall be one (1) full height compartment ahead of the rear wheels on the right side of the apparatus.

The approximate interior dimensions of this compartment shall be 52.50 inches (1333.50 mm) wide by 69.00 inches (1752.60 mm) high with a lower depth of 25.50 inches (647.70 mm) and an upper depth of 12.50 inches (317.50 mm). The framed opening shall measure approximately 50.00 inches (1270.00 mm) wide by 65.00 inches (1651.00 mm) high. The compartment will have approximately 39.24 cubic feet (1.11 cu m) of space.

Compartment "R2"

There shall be one (1) compartment located directly over the rear wheels on the right side of the apparatus.

The approximate interior dimensions of this compartment shall be 62.00 inches (1574.80 mm) wide by 35.00 inches (889.00 mm) high with a depth of 12.50 inches (317.50 mm). The framed opening shall measure approximately 62.00 inches (1574.80 mm) wide by 31.00 inches (787.40 mm) high. The compartment will have approximately 15.70 cubic feet (0.44 cu m) of space.

Compartment "R3"

There shall be one (1) full height compartment located behind the rear wheels on the right side of the apparatus.

The approximate interior dimensions of this compartment shall be 52.50 inches (1333.50 mm) wide by 69.00 inches (1752.60 mm) high with an upper depth of 12.50 inches (317.50 mm) and the lower portion being transverse into the rear compartment, unless partitions are installed. The framed opening shall measure approximately 50.00 inches (1270.00 mm) wide by 65.00 inches (1651.00 mm) high. The compartment will have approximately 39.24 cubic feet (1.11 cu m) of space.

ROLL-UP DOOR CONSTRUCTION

All horizontal and vertical side compartment doors shall be roll-up style doors.

AMDOR ROLL-UP DOORS

AMDOR™ brand roll-up doors shall be provided and installed on the apparatus complete with the following features:

1.00 inch aluminum double wall slats with continuous ball & socket hinge joint designed to prevent water ingress and weather tight recessed dual durometer seals Double wall reinforced bottom panel with stainless steel lift bar latching system Bottom panel flange with cutouts for ease of access with gloved hands Reusable slat shoes with positive snap-lock securement Smooth interior door curtain to prevent equipment hang-ups One-piece aluminum door track / side frame, top gutter with non-marring seal. Non-marring recessed side seals with UV stabilizers to prevent warping. Dual leg bottom seal, with all wear component material to be Type 6 Nylon. Door striker will include support beneath the lift bar to prevent door curtain bounce

SIDE COMPARTMENT DOORS WET PAINTED

The side compartment roll up doors shall be wet finish painted to color match the apparatus body. The door track and trim shall be satin aluminum finish.

ROLL-UP DOOR PROTECTORS

There shall be a protective cover installed under each body side compartment door roll to protect the door in the rolled up position.

ROLL-UP DOOR PROTECTOR FINISH

The roll-up door protector shall be left Natural finish.

DOOR ASSIST STRAPS

There shall be nylon straps installed on both the left and right body side 'high side' compartment doors to assist in closing the door. The strap shall be attached to each door and permanently mounted to the rearward wall with footman loops using Nutserts, halfway between the top and bottom of the compartment.

DOOR OPEN INDICATOR

Each roll up door shall have an integral door ajar switch system provided by AMDOR™ and shall NOT include magnetic proximity based components. The switch device shall be a military grade contact switch capable of meeting MIL-S-8805, which can only be activated through positive engagement of the lift bar. If the door is not properly closed

and the parking brake is released, it shall activate the “hazard light” in the cab to alert the crew.

REAR CENTER COMPARTMENT

There shall be one (1) compartment, "B1", located at the rear of the apparatus, below the hose bed access area.

The approximate interior dimensions of this compartment shall be 43.00 inches (1092.20 mm) wide and 47.00 inches (1193.80 mm) high or as high as possible determined by the hose bed height and rear configuration. The depth shall be determined by the length of the rear side compartments specified and maximized for the suspension specified for the chassis.

The framed opening shall be approximately 38.00 inches (965.20 mm) wide and 41.00 inches (1041.10 mm) high.

REAR COMPARTMENT DOOR

A non-locking AMDOR™ brand roll-up door shall be provided and installed on the apparatus for the B-1 compartment, complete with the following features:

1.00 inch aluminum double wall slats with continuous ball & socket hinge joint designed to prevent water ingress and weather tight recessed dual durometer seals. Double wall reinforced bottom panel with stainless steel lift bar latching system. Bottom panel flange with cutouts for ease of access with gloved hands. Reusable slat shoes with positive snap-lock securement. Smooth interior door curtain to prevent equipment hang-ups. One-piece aluminum door track / side frame, top gutter with non-marring seal. Non-marring recessed side seals with UV stabilizers to prevent warp age. Dual leg bottom seal, with all wear component material to be Type 6 Nylon. Door striker will include support beneath the lift bar to prevent door curtain bounce.

REAR COMPARTMENT DOOR FINISH

The rear center compartment door shall be satin aluminum finish.

ROLL-UP DOOR PROTECTOR

There shall be a protective cover installed under the rear compartment door roll to protect the door in the rolled up position.

ROLL-UP DOOR PROTECTOR FINISH

The roll-up door protector shall be left Natural finish.

DOOR OPEN INDICATOR

Each roll up door shall have an integral door ajar switch system provided by AMDOR™ and shall NOT include magnetic proximity based components. The switch device shall be a military grade contact switch capable of meeting MIL-S-8805, which can only be activated through positive engagement of the lift bar. If the door is not properly closed and the parking brake is released, it shall activate the “hazard light” in the cab to alert the crew.

FUEL TANK ACCESS PANEL

There shall be a removable panel located on the interior back wall of the rear center compartment for maintenance access to the chassis fuel tank.

RIGHT REAR WALL REINFORCEMENT

The right rear vertical body panel shall be reinforced for installation of a TFT Blitzfire mount by the Dealership.

SILL PLATES

Brushed stainless steel sill plates shall be installed at the bottom of each body compartment door opening.

AMDOR COMPARTMENT STRIP LIGHTING

Luma Bar LED Stand Alone strip lighting shall be installed in the compartments as specified. Each light strip shall be of maximum length available to fit the opening. The lighting in each compartment shall be on a separate circuit, and only illuminate when the compartment doors are open.

The lights shall be manufactured by AMDOR.

Two (2) Luma Bar Stand Alone LED strip lights shall be installed in two (2) over wheel compartment(s).

Two (2) Luma Bar Stand Alone LED strip lights shall be installed in four (4) full height compartment(s).

Two (2) Luma Bar Stand Alone LED strip lights shall be installed in the rear center compartment.

COMPARTMENT LIGHTING ACTIVATION

Each compartment light shall be activated with the ignition, park brake and the respective compartment door open switch

REAR TAILBOARD

The rear of the apparatus body shall be vertical in design - otherwise known as a 'flat-back'.

The rear tailboard shall be fabricated of the same tubular materials as used in the apparatus body. The tailboard shall be an independent assembly welded to the rear body structural framing to provide body protection and a solid rear stepping platform. The rear step shall be designed to incorporate "crush zone" technology. This idea incorporates lighter materials

in the tailboard than the body structure so the step will "crush" in a collision before the body structure. On the rear body surface, a sign shall be attached that states: "DO NOT RIDE ON REAR STEP, DEATH OR SERIOUS INJURY MAY RESULT."

The rear tailboard and body shall be constructed such that the angle of departure shall be no less than 8 degrees at the rear of the apparatus when fully loaded (NFPA) 1901, Standard for Automotive Fire Apparatus.

TAILBOARD LENGTH

The rear tailboard shall be approximately 13.50 inches (342.90 mm) deep and shall incorporate an extruded stair tread "Diamondback" material stepping surface bolted in place which spans the width of the apparatus on non-recess designs, and as wide as possible on inset recess designs. The extruded stepping surface shall be completely enclosed by the supporting structural framework to minimize damage. The ventilated "Diamondback" material shall be capable of being easily replaced if necessary, using only hand tools. The framework shall be covered with an adhesive tape providing an aggressive traction surface. Use of any aluminum diamond plate material on these areas shall not be acceptable.

WHEEL WELLS

Wheel wells shall have semicircular black polymer composite inner liners that are bolted to the wheel well panel and supported inboard by brackets that are connected to the body framework. Each wheel well shall be a continuous piece with no breaks or ledges where road grime or debris may accumulate. This liner shall be removable for access to suspension assembly for repairs. There shall be no exception to the bolted wheel well inner liner requirement.

WHEEL WELL MODULES

The body wheel well area shall be fabricated of same material type as the body and finish painted. There shall be “smart storage” compartmentation features incorporated on each side of the apparatus body wheel well modules to utilize and maximize storage space availability.

LEFT FRONT WHEEL WELL

There shall be provisions in the wheel well on the left side in front of the axle.

SCBA COMPARTMENT

The compartment shall hold three (3) 6.75 inch (171.45 mm) Diameter x 24.00 inch (609.60 mm) long SCBA bottles with 1.00 inch (25.40 mm) nylon safety loops installed.

LEFT REAR WHEEL WELL

There shall be provisions in the wheel well on the left side behind the axle.

FUEL FILL & CYLINDER COMPARTMENT

The compartment shall accommodate the fuel fill and hold one (1) 6.75 inch (171.45 mm) Diameter x 24.00 inch (609.60 mm) long cylinder storage with 1.00 inch (25.40 mm) nylon safety loop installed.

SMART STORAGE FUEL FILL ASSEMBLY

There shall be a fuel fill assembly located on the apparatus body accessing the chassis supplied fuel tank. The assembly shall be located in the rear Smart Storage module specified behind the rear axle. There shall be a drain in the fuel fill assembly to allow overflow to drain on the back side of the apparatus body. The fuel fill cap shall be manufactured of plastic materials, green in color and equipped with a tether. The fuel fill cap shall be labeled "DIESEL FUEL". The fuel fill neck shall have a .375 inch inside diameter vent line installed from the top of the fuel tank to the fill tube.

RIGHT FRONT WHEEL WELL

There shall be provisions in the wheel well on the front side in front of the axle.

FIRE EXTINGUISHER STORAGE COMPARTMENT

The compartment shall hold one (1) 2.5 gallon water extinguisher and one (1) 20 lb. ABC fire extinguisher.

RIGHT REAR WHEEL WELL

There shall be provisions in the wheel well on the right side behind the axle.

SLIDE-OUT FLOOR DRY MODULE

A slide-out floor dry storage module with locking slides shall be provided and installed in the apparatus wheel well smart storage area as specified. The floor dry storage module shall be manufactured as large as possible to maximize the available storage space. The module shall be capable of storing approximately 35-40 pounds of all-purpose floor dry absorbent compound material pending type and brand used by fire department. The floor dry compartment module shall have a hinged lid with mechanical latching device that can be easily accessed for refilling. The module shall include a grab handle for ease of deployment. The module shall be located directly behind the smart storage compartment door. A manual drain shall be located at the bottom of the compartment module for ease of dispensing the material. The storage module shall be labeled "Floor Dry". The slide out floor dry module shall have RED reflective striping installed making the perimeter more readily visible when deployed.

SMART STORAGE DOORS

The smart storage compartment doors shall be smooth and painted stainless steel to match body job color. Where a module storage compartment is specified, a hinged door shall be provided. Each compartment door shall be secured with a round chrome latch.

DOOR OPEN INDICATOR

There shall be a switch installed for each smart storage compartment door. If the door is not properly closed and the parking brake is released, it shall activate the "hazard light" in the cab to alert the crew.

FENDERETTES

Two (2) polished stainless steel fenderettes shall be provided and installed on body rear wheel well openings, one (1) each side. Rubber welting shall be provided between the body and the crown to seal the seam and restrict moisture from entering. A dielectric barrier shall be provided between the fender crown fasteners (screws) and the fender sheet metal to resist deterioration.

LEFT SIDE UPPER STORAGE COMPARTMENTS

Two (2) storage compartments shall be provided and installed on the upper left side of the apparatus body. The approximate length of each compartment shall be 83.00 inches long. The depth of the compartments shall be determined by the hose bed wall height. The compartment shall extend beyond the apparatus body roof and walking surface and provide a vertical edge to prevent water intrusion. An adhesive backed bulb seal shall be applied to the underside perimeter of the lid, excluding the hinge side, to ensure a positive seal. The formed doors, incorporating broken edges of 45 degrees or less, shall extend over the compartments edge approximately 1.00 inch to minimize water penetration. Each door shall be secured by push button weather resistant (C5) South Co Brand style latches. The doors shall be fabricated of embossed aluminum diamond plate and be secured by a stainless steel hinge. If deemed necessary due to width, the doors shall be reinforced to act as a suitable walking or standing surface. Each door shall be held open by a gas charged strut on each side and permit full access to the compartment along its length. The struts shall be concealed inside the compartment when the door is in the closed position. The compartments shall be constructed as part of the body and be accessible from the hose

bed area. The upper compartments shall not be vented. There shall be plastic tubing installed for adequate drainage that is routed from corners of the upper compartment floors down to below the lower compartment floor level.

RIGHT SIDE UPPER STORAGE COMPARTMENTS

Two (2) storage compartments shall be provided and installed on the upper right side of the apparatus body. The approximate length of each compartment shall be 83.00 inches long. The depth of the compartments shall be determined by the hose bed wall height. The compartment shall extend beyond the apparatus body roof and walking surface and provide a vertical edge to prevent water intrusion. An adhesive backed bulb seal shall be applied to the underside perimeter of the lid, excluding the hinge side, to ensure a positive seal. The formed doors, incorporating broken edges of 45 degrees or less, shall extend over the compartments edge approximately 1.00 inch to minimize water penetration. Each door shall be secured by push button weather resistant (C5) South Co Brand style latches. The doors shall be fabricated of embossed aluminum diamond plate and be secured by a stainless steel hinge. If deemed necessary due to width, the doors shall be reinforced to act as a suitable walking or standing surface. Each door shall be held open by a gas charged strut on each side and permit full access to the compartment along its length. The struts shall be concealed inside the compartment when the door is in the closed position. The compartments shall be constructed as part of the body and be accessible from the hose bed area. The upper compartments shall not be vented. There shall be plastic tubing installed for adequate drainage that is routed from corners of the upper compartment floors down to below the lower compartment floor level.

ADJUSTABLE UPPER STORAGE DIVIDER

There shall be one (1) adjustable divider installed in the upper storage compartments. The divider shall be installed on horizontal unistrut to allow for front to back movement.

UPPER STORAGE COMPARTMENT LIGHTING

Two (2) Amdor Luma Bar stand-alone LED strip lights shall be installed in each upper body storage compartment. The light strips shall be of maximum length available to fit in the compartment. The lights shall be on a separate circuit, activating only those lights that have an open compartment door.

UPPER COMPARTMENT FLOOR MATTING

There shall be Turtle Tile floor tile installed in each upper storage compartment floor. The tile shall be custom fitted to the interior compartment floor construction to protect the entire floor surface from equipment damage.

FLOOR MATTING COLOR

The floor tiles shall be black in color.

HOSE STORAGE

A hose bed shall be provided and installed with the minimum capacity as required by (NFPA) 1901, Standard for Automotive Fire Apparatus. The hose bed shall have a slotted .25 inch (6.35 mm) aluminum flooring installed to allow drainage through the tank cavity to the ground below. The aluminum flooring shall be manufactured in discrete sections to allow for ease of removal and stability. The area shall be free of sharp edges to

protect the hose when loading and unloading.

HOSE BED AREA

The hose bed area of the apparatus shall be overlaid with brushed stainless steel material.

HOSE BED AREA TRIMMED W/ BRUSHED SST

The vertical corners at the back hose bed shall be trimmed with brushed stainless steel. The trim shall extend from the hose floor level up to the top edge of the body side.

HOSE BED WALL HEIGHT

The walls of the hose bed shall be 90.00 inches (2.29 m) tall, measured from the bottom edge of the compartments to the top flange.

HOSE BED COVER WITH FIXED SUPPORT DIVIDER

There shall be a double door cover for the hose bed provided and installed. A fixed divider shall be installed in the hose bed to support the covers when they are closed. The construction style of the divider may be similar to adjustable divider(s) if specified. Each cover shall be reinforced and be capable of supporting 400 pounds (181 kg) while standing on the cover.

Each cover shall be capable of being opened independently. The doors shall be fabricated of .125 inch (3.18 mm) embossed aluminum diamond plate material with full length two-piece stainless steel piano hinges. The hose bed covers shall be wired to the hazard light in chassis cab. Inductive proximity switches shall be installed at the hose bed cover door hinges. If the door is not properly closed with the parking brake released, it shall activate the "hazard light" in the cab to alert the crew.

MANUAL RAISED COVERS

Each cover shall be raised independently and manually. There shall be a gas shock hold open device provided to hold each cover in the open position. Each gas shock shall be accompanied by a vinyl covered safety chain.

HANDRAILS

Two (2) 1.25-inch diameter handrails constructed of bright-anodized knurled extruded aluminum with 18.00 inches of grip surface shall be installed on top of the hose bed covers, one (1) each cover, accessible from the rear of the apparatus.

CARGO NET REAR HOSE BED RESTRAINT

There shall be a Cargo Net flap that extends down over the rear of the hose bed provided and installed with the apparatus. The cover shall be fastened by an elastic shock cord sewn into the tarp with brass grommets where the shock cord passes through the hose bed cover. Hooks shall be provided on the lower corners to provide a means of attaching the cover to the apparatus. The hooks shall be made of cast aluminum.

REAR FLAP COLOR

The rear flap shall be black.

LED HOSE BED LIGHTING

There shall be four (4) 42.00 inch (107cm) Amdor Luma Bar Stand Alone LED strip lights installed with protective angles. Two (2) each side at the top of the hose bed walls, centered from front to back.

HOSE BED LIGHT ACTIVATION

The hose bed lights shall be activated when the park brake is set.

HOSE BED DUNNAGE AREA

A vertical bulkhead shall be provided and installed at the front of the hose bed area, behind the water tank fill tower, forming a storage area that is separated from the hose bed.

The rear face of the bulkhead shall serve as a mounting surface for the hose bed dividers, resulting in the ability to move any hose bed divider across the entire width of the hose bed.

HOSE BED DIVIDER(S)

There shall be a full height adjustable divider provided and installed in the hose bed area of the apparatus body. The divider shall be fabricated of .25 inch (6.35 mm) thick aluminum plate with a double sided reinforcement and attached to the adjustable slide rails. The rear of the divider shall have a radius to provide a smooth corner. Hose payout shall be unobstructed by the divider.

There shall be a total of one (1) provided and installed in the hose bed.

HOSE LOAD

The hose bed shall accommodate the following hose loads:

BAY 1:

-300 feet of 2.50 inch hose

BAY 2:

-1000 feet of 4.00 inch hose

TANK CAPACITY

The tank shall be 750 gallons (2839 liters) in capacity.

UPF POLY TANK III

The booster tank shall be constructed of PT3™ polypropylene material. This material shall be a non-corrosive stress relieved thermoplastic and UV stabilized for maximum protection. The booster and/or foam tank shall be of a specific configuration and is so designed to be completely independent of the body and compartments. All joints and seams shall be fused using nitrogen gas as required and tested for maximum strength and integrity. The tank construction shall include PolyProSeal™ technology wherein a sealant shall be installed between the plastic components prior to being fusion welded. This sealing method will provide a liquid barrier offering leak protection in the event of a weld compromise. The top of the booster tank is fitted with removable lifting assembly designed to facilitate tank removal. The transverse and longitudinal swash partitions shall be manufactured of a minimum of 3/8" PT3™ polypropylene. All partitions shall be equipped with vent and air holes to permit movement of air and water between

compartments. The partitions shall be designed to provide maximum water flow. All swash partitions interlock with one another and are completely fused to each other as well as to the walls of the tank. All partitions and spacing shall comply with (NFPA) 1901, Standard for Automotive Fire Apparatus.

The walls shall be welded to the floor of the tank providing maximum strength as part of the tank's unique Full Floor Design™. Tolerances in design allow for a maximum variation of .125 on all dimensions.

WATER FILL TOWER AND COVER

The tank shall have a combination vent and manual fill tower. The fill tower shall be constructed of .50 inch (12.7 mm) PT3™ polypropylene. The fill tower shall be blue in color indicating that it is a water-only fill tower. The tower shall have a .25 inch (6.4 mm) thick removable polypropylene screen and a PT3™ Polypropylene hinged cover. The capacity of the tank shall be engraved on the top of the fill tower lid. Inside the fill tower there shall be a combination vent/overflow pipe. The tank cover shall be constructed of .50 inch (12.7 mm) thick PT3™ polypropylene and UV stabilized, to incorporate a multi-piece locking design, which allows for individual removal and inspection if necessary. The tank cover(s) shall be flush or recessed 3/8" from the top of the tank and shall be fused to the tank walls and longitudinal partitions for maximum integrity. Each one of the covers shall have hold downs consisting of 2.00 inch (50 mm) minimum polypropylene dowels spaced a maximum of 40.00 inch (1016 mm) apart. These dowels shall extend through the covers and will assist in keeping the covers rigid under fast filling conditions. A minimum of two lifting dowels shall accommodate the necessary lifting hardware.

MOUNTING

The UPF Poly-Tank® III shall rest on the body cross members in conjunction with such additional cross members, spaced at a distance that would not allow for more than 530 square inches of unsupported area under the tank floor. In cases where overall height of the tank exceeds 40.00 inch (1016 mm), cross member spacing must be decreased to allow for not more than 400 square inches of unsupported area. The tank must be isolated from the cross members through the use of hard rubber strips with a minimum thickness and width dimension of .25 inch (6.4 mm) x 1.00 inch (25 mm) and a Shore A Hardness of approximately 60 durometer. The rubber must be installed so it will not become dislodged during normal operation of the vehicle. Additionally, the tank must be supported around the entire bottom outside perimeter and captured both in the front and rear as well as side to side to prevent tank from shifting during vehicle operation. A picture frame type cradle mount with a minimum of 2.00 inch (50 mm) x 2.00 inch (50 mm) x .25 inch (6.4 mm) mild steel, stainless steel, or aluminum angle shall be provided or the use of corner angles having a minimum dimension of 4.00 inch (100 mm) x 4.00 inch (100 mm) x 4.00 inch (100 mm) by 6.00 inch (150 mm) high are permitted for the purpose of capturing the tank. Although the tank is designed on a free floating suspension principle, it is required that the tank have adequate vertical hold down restraints to minimize movement during vehicle operation. If proper retention has not been incorporated into the apparatus hose floor structure, an optional mounting restraint system shall be located on top of the tank, halfway between the front and the rear on each side of the tank. These stops can be constructed of steel, stainless steel or aluminum angle having minimum dimensions of 3.00 inch (77 mm) x 3.00 inch (77 mm) x .25 inch (6.4 mm) and shall be approximately 6.00 inch (150 mm) to 12.00 inch (304.80 mm) long. These brackets must incorporate

rubber isolating pads with a minimum thickness of .25 inch and a hardness of 60 durometer affixed on the underside of the angle. The angle should then be bolted to the body side walls of the vehicle while extending down to rest on the top outside edge of the upper side wall of the tank. Hose beds floors must be so designed that the floor slat supports extend full width from side wall to side wall and are not permitted to drop off the edge of the tank or in any way come in contact with the individual covers where a puncture could occur. Tank top must be capable of supporting loads up to 200 lbs. per sq. foot when evenly distributed. Other equipment such as generators, portable pumps, etc. must not be mounted directly to the tank top unless provisions have been designed into the Poly-Tank® III for that purpose. The tank shall be completely removable without disturbing or dismantling the apparatus structure. The tank must be designed and fabricated by a tank manufacturer that is ISO 9001:2008 certified. The ISO certification must be to the current standard in effect at the time of the design and fabrication of the tank.

TANKNOLOGY™ TAG

A tag shall be installed on the apparatus in a convenient location and contain pertinent information including a QR code readable by commercially available smart phones. The information contained on the tag shall include the capacity of the water and foam(s), the maximum fill and pressure rates, the serial number of the tank, the date of manufacture, the tank manufacturer, and contact information. The QR code will allow the user to connect with the tank manufacturer for additional information and assistance.

TANK WARRANTY

A lifetime tank warranty shall be provided by the tank manufacturer, UPF. Please see the official warranty document in the appendix (attached) for specific details.

FILL TOWER

The fill opening shall be approximately 13.00 inches (330.20 mm) x 12.00 inches (304.80 mm). The tower will have a .25 inch (6.40 mm) thick removable Polyprene screen and a Polyprene hinged type cover that will open if the tank is filled at an excess rate. There shall be a removable .25 inch (6.40 mm) thick Polyprene screen to prevent debris from falling into the tank. The fill tower shall have a 4.00 inch (100.00 mm) overflow that will discharge underneath the tank, behind the rear wheels. The overflow shall terminate above the tank water level when filled to the rated capacity.

FILL TOWER LOCATION

The fill tower shall be located to the left side at the front of the hose bed.

SUMP

The sump will be constructed in an 8.00 inch (203.20 mm) x 16.00 inch (406.40 mm) x 3.00 inch (77.00 mm) deep area. The sump will be constructed of .50 inch (12.70 mm) Polyprene and be located in line with the tank suction valve. There shall be a 4.00 inch (100.00 mm) schedule 40 Polyprene tube installed that will run from the suction outlet to the sump location. The tank will have an anti-swirl plate located approximately 2.00 inch (50 mm) above the sump.

SUMP PLUG

The sump shall have a 3.00 inch (77.00 mm) plug for use in draining and cleaning out the tank.

OUTLETS

In addition to the tank suction valve outlet located in the sump, there shall be an outlet provided for the tank fill valve. If there are any additional options selected (such as an extra tank suction or direct tank inlets), there shall be additional outlets provided to accommodate these items.

LADDER COMPARTMENT

The ground ladders shall be stored within a compartment installed beside the booster tank.

All items shall be stored in their own independent section to allow one item to be removed without disturbing another. There shall be polypropylene slide angles installed in each section where applicable, and for the ladders to slide on. There shall be a stop in the front of each section to prevent the items from sliding forward.

LADDER COMPARTMENT MATERIAL

The ground ladder compartment shall be fabricated of .125-inch smooth aluminum.

LADDER COMPARTMENT LOCATION

The ground ladder compartment shall be mounted vertically on the right side of the water tank. The ladder compartment at the front of the body shall be open to give access to the plumbing in the front of the body from the right side front compartment.

LADDER COMPARTMENT DOOR HINGE LOCATION

The door hinge shall be mounted vertically across the inboard edge of the compartment door opening.

LADDER COMPARTMENT DOOR

The door material shall match the rear overlay material. The door shall have two (2) push button type latches installed with a chrome handle centered between the push button latches.

If the door is not properly closed and the parking brake is released, it shall activate the “hazard light” in the cab to alert the crew.

LADDER COMPARTMENT DOOR REFLECTIVE CHEVRON

The ladder compartment door shall be left unfinished and include retro-reflective chevron material matching the rear of the apparatus.

LADDER COMPARTMENT DOOR HANDLE

The ladder compartment doors handle shall be a spring loaded bidirectional D-ring style handle.

LADDER COMPLEMENT

The following ladders shall be supplied with the apparatus:

One (1) Duo-Safety 24 foot (7.0 m) two (2) section aluminum extension ladder(s), model 900A.

One (1) Duo-Safety 14 foot (4.0 m) aluminum roof ladder(s) with folding hooks, model

775A.

One (1) Duo-Safety 10 foot (3.0 m) aluminum attic ladder(s), model 585A.

PIKE POLE STORAGE

There shall be two (2) tubes provided for storage of the pike poles installed with the ground ladder complement.

The pike poles provided shall be standard hook with straight handle.

The pike poles shall be supplied and installed by the Fire Department before the apparatus is placed into service.

ENCLOSED SUCTION HOSE COMPARTMENT

The suction hose shall be stowed in a compartment located at the rear of the body beside the booster tank. All items stowed shall be in their own sleeve to allow one item to be removed without disturbing any others. There shall be a stop in the front of the sections to prevent each item from sliding forward. The interior floor of the compartment shall be lined with Black ABS plastic for ease of stowing and un-stowing of the suction hose. The compartment shall have a vertically hinged door at the rear to access equipment. The door shall be fabricated of the same material as the rear overlay and shall be secured with two (2) push button latches and a chrome handle centered between the push button latches. If the door is not properly closed and the parking brake is released, it shall activate the "hazard light" in the cab to alert the crew.

SUCTION HOSE COMPARTMENT MATERIAL

The suction hose compartment shall be fabricated of .125 inch smooth aluminum.

SUCTION COMPARTMENT LOCATION

The compartment shall be located vertically on the left side of the tank. The door shall be hinged on the right side.

SUCTION HOSE

The following suction hose shall be provided to be stored in the compartment layout as specified above.

There shall be Two (2) 10 foot length(s) of 6.00 inch clear PVC suction hose with lightweight couplings provided with the above specified storage.

EQUIPMENT DOOR STRIPING

Retro-Reflective striping in a chevron pattern matching the rear layout shall be provided on the equipment access door.

COMPARTMENT UNISTRUT

Vertically mounted Unistrut shall be installed in all apparatus body compartments, except the L1 compartment as referenced below, in the upper and lower sections, to accommodate the installation of shelves, trays, and or other miscellaneous equipment.

When sufficient space allows for a shelf/tray to be installed, the unistrut in the L1 compartment will be located on the rearward face of the structure for the operator's panel and the rear wall/forward facing.

OVER-WHEEL COMPARTMENT PARTITIONS

Compartment partitions fabricated of the same material as the body shall be permanently

installed in the left over-wheel compartment, right over-wheel compartment, or both where applicable by design. The partitions shall be permanently installed in place and flush to the forward and rearward frame openings. The partitions shall aid in keeping loose equipment from falling into the fore and aft compartments.

SHELVING

The shelving shall be made out of .190 inch (4.83 mm) smooth aluminum sheet material with a formed 2.00 inch (50.80 mm) lip on the front and back.

The side mounting brackets shall be provided for vertical adjustment. Standard manufacture shelf construction capacity ratings are as follows, any requested change to the

manufacture's standard design may affect/reduce the ratings accordingly:

Shelving shall be rated at a capacity of 200 pounds (90.72 kg) and applicable to the design configuration.

The following shelving shall be provided:

LOWER FULL DEPTH SHELVING

A full width x full depth shelf shall be provided and installed in the lower area of the compartment as specified.

There shall be a total quantity of three (3) provided.

- One (1) located in the L1 compartment.

- One (1) located in the R1 compartment. One (1) located in the R3 compartment.

ROLL OUT TRAY(S)

Each tray shall be fabricated of .19 inch (4.83 mm) thick 3003 grade or higher aluminum sheet material with four (4) 3.00 inch (76.20 mm) side flanges, corner welded for maximum strength and shall be as wide and as deep as compartment allows.

The following shall be supplied:

ROLL-OUT ASSEMBLY/AUSTIN

The floor mounted tray shall be full width and shall be secured to an Austin Hardware 22.00 inch (558.80 mm) long ball bearing "heavy duty" slide assembly. The slide assemblies shall incorporate cadmium plated ball bearing roller slides and a lock-in, lock-out front drawer release system (FDR).

The tray shall have a 300# capacity and 100% extension.

There shall be a total quantity of two (2) provided.

- One (1) located in the R1 compartment.

- One (1) located in the R3 compartment.

ROLL-OUT ASSEMBLY/AUSTIN

The adjustable tray shall be full width and shall be secured to an Austin Hardware 22.00 inch (558.80 mm) long ball bearing "heavy duty" slide assembly. The slide assemblies shall incorporate cadmium plated ball bearing roller slides and a lock-in, lock-out front drawer release system (FDR).

The tray shall have a 300# capacity and 100% extension and adjustable height utilizing unistrut materials.

There shall be a total quantity of one (1) provided.

- One (1) located in the L1 compartment.

SHELF AND ROLL OUT TRAY MATTING

Any shelf or tray provided shall have Turtle Tile floor tiles installed. The tiles shall be custom fitted for durability and a pleasing appearance.

MATTING COLOR

The matting shall be black in color.

ROLL OUT TRAY REFLECTIVE STRIPING

One (1) roll out tray(s) provided shall have full length retro-reflective striping installed to indicate a hazard or an obstruction. The striping shall run the full width and the full depth of each roll out tray.

The reflective striping shall be "Ruby Red" in color.

PULL-OUT TOOL BOARD/PAC TRAC

A Pac-Trac pull-out tool board with DA finish shall be installed in the compartment as specified. The tool board shall be attached to unistrut material mounted on the floor and ceiling of the compartment, extending perpendicular to the rear wall, allowing for horizontal adjustment from front to rear. The tool board shall be mounted utilizing a SlideMaster slide with locking device at the bottom to keep the board in the stored and extended positions.

There shall be a total quantity of one (1).

The pull-out/swing-out style tool board shall have RED reflective striping installed making the perimeter of the tool board more readily visible.

- One (1) located in the L3 compartment.

WALL MOUNTED TOOL BOARD/PAC-TRAC

A Pac Trac tool board with DA finish shall be installed to the back wall of the compartment as specified. The completed tool board assembly shall be attached directly to the upper back wall utilizing custom manufactured plate or angle brackets.

There shall be a total quantity of one (1).

- One (1) located in the L1 compartment.

AIR BAG STORAGE COMPARTMENT

Inflatable air bags shall be stored in individual vertical storage slots of a compartment. Each slot shall be wide enough to accommodate the specified bag dimensions with fill valve. The air bags shall be removable without disturbing the storage of another.

The compartment shall have provisions for the following air bags:

- Two (2) 24.00 inch by 24.00 inch by .875 inch bags
- Two (2) 20.00 inch by 20.00 inch by .875 inch bags
- Two (2) 15.00 inch by 15.00 inch by .875 inch bags
- Two (2) 12.00 inch by 12.00 inch by .875 inch bags
- One (1) 6.00 inch by 12.00 inch by .875 inch bags

AIR BAG COMPARTMENT FINISH

The air bag compartment shall have a dual-action sanded finish on the exterior surfaces.

AIR BAG COMPARTMENT LOCATION

The air bag compartment shall be located at preconstruction meeting.

VELCRO STRAPPING

The air bag compartment shall incorporate heavy duty Velcro strapping to securely retain the equipment during transit.

SCBA AIR BOTTLE STORAGE RACK

There shall be a free standing .125 smooth aluminum air bottle storage rack installed with the apparatus. The storage rack shall be mounted on a slight incline towards the compartment inboard wall. Each individual bottle storage compartment shall incorporate a 1.00 inch nylon safety loop to be attached to the top of the bottle to prevent the bottles from sliding forward when stored. The bottle storage openings shall have an inside dimension of approximately 7.00 inches wide by 7.00 inches high with a maximum depth not to exceed compartment interior depth.

The storage rack shall have provisions to hold the following air bottles:

The rack shall hold six (6) cylinders stacked in a two (2) wide by three (3) high configuration.

SCBA RACK LOCATION

The SCBA storage rack shall be located at pre-construction meeting.

The SCBA storage rack shall be mounted on the compartment floor against the rearward wall.

SCBA STORAGE RACK FINISH

The SCBA storage rack shall have a natural finish on the exterior surfaces.

SCBA BRACKET

A Zico model #UN-6-30-2-SF SCBA spring clip bracket, complete with back plate, foot plate and two (2) spring clips shall be mounted to horizontal unistrut channels and installed in the compartment as specified below:

A total of one (1) bracket(s) shall be provided.

SCBA CLIP(S) LOCATION

The SCBA clips shall be installed on the upper back wall in the L1 compartment.

SIDE RUB RAILS (ALUMINUM CHANNEL)

The lowest edge of the apparatus body side compartments shall be trimmed with brightly anodized aluminum channel rub rail material. The rub rails shall be approximately 3.00 inches high with flanges turned outwards for increased rigidity, with each end chamfered to a 45 degree angle. The rub rails shall not be constructed as an integral part of the apparatus body structure, allowing each rub rail to be easily removed in the event of damage. The rub rails shall be secured with stainless steel fasteners and spaced away from the apparatus body with .50 inch nylon spacers to help absorb moderate side impacts and prevent the collection of water and debris for easier cleaning.

RUB RAIL RETRO-REFLECTIVE STRIPING

One inch retro-reflective striping shall be applied to the length of each side rub rail

section making the perimeter of the apparatus more readily visible.
The reflective striping shall be "Ruby Red" in color.

FOLDING STEPS

Cast Products, Inc. model #SP6610-1CH dual LED illuminated folding steps, made of high strength die cast aluminum with a protective chromed coating, pyramid tread platform conforming to current NFPA requirements, shall be provided and installed on the apparatus as specified. The steps shall have a minimum of 46 sq. inches of surface area capable of sustaining a 1200 lb. static load. The steps shall be mounted no more than 18" inches between each step.

STEP LOCATION

Three (3) folding steps shall be installed on the left rear vertical face of the body.

10" HANDRAIL

One (1) 10.00 inch long by 1.25 inch diameter handrail constructed of extruded aluminum with a knurled grip, full length red reflective strip and full length illuminated LED light strip shall be installed in a location above the rearward step(s) and in accordance with (NFPA) 1901, Standard for Automotive Fire Apparatus, standard requirements. There shall be a minimum of 2.00 inches of clearance between the bracket and the body. To be located at Precon

Each handrail LED light strip specified shall be white/clear in color.

ILLUMINATED HANDRAIL LIGHTING ACTIVATION

The illuminated handrail light shall be activated when the park brake is set.

STEP LIGHT ACTIVATION

The step light shall be activated when the park brake is set.

"SMART" ALUMINUM ACCESS LADDER

A "Smart" aluminum fold down access ladder shall be provided at the rear of the apparatus. The ladder rungs shall be constructed of a slip resistant stepping material. The upper section shall be permanently secured to the body with a mechanical style hinge and fasteners that allow the ladder to extend down and out to the ground from the apparatus body. When deployed, the fold-down steps shall create a safe and comfortable climbing angle.

Two (2) gas cylinders shall be installed to assist in the deployment of the lower fold-down section. A mechanical locking mechanism shall be provided to retain the ladder in a stowed and secured position when in transit or when not in use. Access ladder rung illumination shall be provided during low light conditions. A notch will be provided on all tailboards 'exceeding' 13.50 inches deep when specifying the addition of a Smart Fold Down Ladder. The notch will provide the proper clearance to allow the ladder to 'swing down' freely

when being deployed. If the step is not properly stowed and the parking brake is released, it shall activate the hazard light in the cab to alert the crew.

ACCESS LADDER LOCATION

The ladder shall be installed at the rear of the apparatus on the right side.

STEP LIGHTING

One (1) light shall be installed to illuminate the stepping areas as provided. The light shall be a LED Tube light model #RX-15T16-5050-21CM with an aluminum mounting bezel.

The light shall be directed towards and positioned above the stepping surfaces.

STEP LIGHT ACTIVATION

The step light shall be activated when the park brake is set.

HANDRAILS KNURLED ALUMINUM ILLUMINATED

Handrails shall be 1.25 inches in diameter, constructed of extruded aluminum with a knurled grip, full length red reflective strip and full length illuminated LED light strip. There shall be a 2.00 inch minimum clearance between the handrail and the body. The light shall illuminate an area adjacent to the handrail and in accordance with (NFPA) 1901, Standard for Automotive Fire Apparatus, standard requirements.

The following handrails shall be installed at the approximate lengths noted:

REAR HANDRAIL LOCATION

Two (2) handrails shall be installed on the rear of the apparatus. Each handrail shall be of an adequate length, as available usable space allows, to provide a suitable gripping area for personnel. The handrails shall be spaced away from the body using chrome plated straight stanchions. One (1) vertical handrail shall be installed just below the hose bed side opposite of the rear access ladder. This vertical handrail shall utilize an offset stanchion with the offset directed away from storage door openings for added clearance where applicable.

The remaining handrail shall be installed horizontally, just below the hose bed area. Each handrail LED light strip specified shall be white/clear in color.

ILLUMINATED HANDRAIL LIGHTING ACTIVATION

The illuminated handrail light shall be activated when the park brake is set.

TOW EYES

There shall be two (2) rear tow eyes installed to the frame rails, one each side, accessible below the rear of the apparatus.

They shall be manufactured of 1.00 inch plate steel and each plate shall be bolted to the chassis frame rail with a minimum quantity of six (6) grade 8 bolts. The two plates shall be anchored together with 1.00 inch steel tubing to prevent swaying of the frame rails during a towing operation. All steel components shall be painted black.

SIDE RECEIVERS

There shall be a rescue winch receiver tube located in line with the rear tow eyes below the body, behind the rear axle on the left and right side. The receiver shall have a maximum straight line pull capacity equaling 9000 pounds (4080 kg) to either side. Each receiver shall have a 2.00 inch (50.80 mm) square opening for the attachment of a portable rescue winch.

A receptacle shall be supplied adjacent to each rescue winch receiver tube and wired for a portable electric winch.

A label shall be permanently affixed on or near each winch receiver indicating the

maximum straight line pull rating of the anchor.

REAR RECEIVER

A rescue winch receiver shall be installed at the rear of the apparatus mounted directly to the chassis frame rails and below the apparatus in the center. The receiver shall have a maximum straight line pull capacity equaling 9000 pounds (4080 kg).

The receiver shall have a 2.00 inch (50.80 mm) square opening for the attachment of a portable rescue winch.

A power receptacle shall be installed adjacent to the rescue winch receiver and wired for a portable electric winch.

A label shall be permanently affixed on or near the winch receiver indicating the maximum straight line pull rating of the anchor.

FRONT RECEIVER

A rescue winch receiver with tow eyes, shall be installed on the front of the apparatus mounted directly to the chassis frame rails and below the front bumper in the center. The receiver shall have a maximum straight line pull capacity equaling 9000 pounds (4080 kg).

The receiver shall have a 2.00 inch (50.80 mm) square opening for the attachment of a portable rescue winch.

A power receptacle shall be installed adjacent to the rescue winch receiver and wired for a portable electric winch.

A label shall be permanently affixed on or near the winch receiver indicating the maximum straight line pull rating of the anchor.

ANCHOR POINTS

There shall be rescue anchor points installed on all four (4) upper corners of the body. Each shall be a machined assembly, welded into the body structure, that shall feature a 1.00 inch (25.40 mm) round eye hole for ease of anchoring. Individual anchor point shall be rated for up to a 9,000 pound (4082 kg) no yield straight line pull.

UTILITY AIR REEL

One (1) Hannay model #F series utility air reel shall be installed on the apparatus as specified.

The reel shall be plumbed to the chassis air tanks with a regulator and gauge to control air pressure.

UTILITY AIR HOSE

There shall be 75 feet (22 m) of .50 inch (12.7 mm) ID air hose provided and installed on the reel.

REWIND ACTIVATION

A weather resistant push button switch to activate the reel rewind shall be located next to the reel specified. The switch shall be labeled "UTILITY AIR REEL".

UTILITY AIR REEL SUPPLY

The reel shall be plumbed to the chassis air tanks with a regulator and gauge to control air pressure.

REEL LOCATION

One (1) reel is to be located in the left side upper storage UL-2 Upper Compartment
The reel shall be placed in the rearward position of the above stated compartment.

ROLLER ASSEMBLY

There shall be a four (4) way fixed roller assembly provided and fastened to a plate in the lower compartment
below the reel to guide the cord on and off the spool.

LOW-VOLTAGE ELECTRICAL SYSTEM

The apparatus shall be equipped with a Logic Controlled, Low-Voltage (12v) Electrical System, compliant with the latest revision of the (NFPA) 1901, Standard for Automotive Fire Apparatus. The system shall be capable of performing total load management, load management sequencing, and load shedding via continuous monitoring of the low-voltage electrical system. In addition, the system shall be capable of switching loads (similar to operating as an emergency warning lamp flasher) eliminating the dependency on many archaic electrical components such as conventional flasher modules. The system shall also

incorporate provisions for future expansion or system modification. The low-voltage electrical system shall be designed to distribute the placement of electrical system hardware throughout the apparatus thereby enabling a smaller, optimized wire harness. The programmable, logic controlled system shall eliminate redundant electrical hardware such as extra harnesses, circuit boards, relays, circuit breakers, and separate electrical or interlock subsystems and associated electronics for controlling various electrical loads and inputs. As-built electrical system drawings and an apparatus-specific reference of I/O shall be furnished in the final delivery manuals. These drawings shall illustrate the electrical system broken down into separate functions, or small groups of related functions. Drawings shall depict circuit numbers, electrical components and connectors from beginning to end. **A single drawing for all electrical circuits installed by the apparatus manufacturer shall not be accepted.**

MULTI-PLEXED ELECTRICAL WARRANTY

A four (4) year limited (V-MUX) multiplex system warranty, of Weldon Technologies, Inc.; shall be provided by the apparatus manufacture for parts and labor, while under normal use and service; against mechanical, electrical and physical defects from the date of installation.

The warranty shall exclude; sensors, shunt interface modules, serial or USB kits, transceivers, cameras, GPS, and electrical display screens, which shall be limited to a period of one a (1) year repair parts and labor from the date of installation.

NODE

An electrical distribution node or relay shall be installed in the below locations of the apparatus body. The pump node shall be mounted as high as practical in the full depth portion of the right front compartment. The rear body nodes shall be mounted as high and as far rearward as practical on the back wall of the rearmost compartment. A protective cover shall be installed to prevent damage to the node or electrical system during equipment installation and or removal. Node covers shall be approximately 16.00 to 22.00 inches in length with an

inspection hole positioned for view of the node indicator LED lights. The finish of the cover shall match the compartments interior finish. Node covers will not include any type of shelf mounting structure and shall limit the height of unistrut or shelf height within the compartments.

PERIMETER LIGHTS LOCATION

There shall be four (4) underbody perimeter lights installed on the apparatus positioned to provide illumination to the immediate ground area around the unit.

One (1) under each side of the pumphouse running boards and two (2) under the rear tailboard.

PERIMETER LIGHTS

The underbody perimeter lights provided will be TecNiq model T44 series, 4" round, 8 diode LED lights.

PERIMETER LIGHTS ACTIVATION

The perimeter lights under the body shall illuminate the area with the activation of the chassis ground lights.

UPPER LIGHTING PACKAGE

The following NFPA lighting package, manufactured by Whelen, shall be supplied and installed in the upper areas of the vehicle.

UPPER ZONE B&D-FORWARD:

There shall be two (2) Whelen model 900 series Super-LED lights with chrome bezels provided and installed with the apparatus.

There shall be one (1) each side of the body in the upper forward corners.

SIDE WARNING LIGHTS FLASH

The upper side lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors.

SIDE WARNING LIGHTS COLOR

The upper warning lights mounted on the side positions shall be red with red lenses.

UPPER ZONE B&D-REAR:

There shall be two (2) Whelen model 900 series Super-LED lights with chrome bezels provided and installed with the apparatus.

There shall be one (1) each side of the body in the upper rear corners.

SIDE WARNING LIGHTS FLASH

The upper side lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors.

SIDE WARNING LIGHTS COLOR

The upper warning lights mounted on the side positions shall be red with red lenses.

UPPER SIDE WARNING LIGHT SWITCH E-MASTER/SWITCHED

The upper side warning lights shall be controlled through the master warning switch and a secondary side warning switch located on the dash panel. The switches shall be clearly labeled for ease of identification.

UPPER ZONE C:

There shall be two (2) Whelen model 900 series Super-LED lights with chrome bezels, one (1) each side, provided and installed with the apparatus.

REAR WARNING LIGHTS FLASH

The rear upper lights shall feature multiple flash patterns including steady burn.

REAR WARNING LIGHTS COLOR

The upper warning lights mounted at the rear shall be red with red lenses.

UPPER REAR WARNING LIGHT SWITCH E-MASTER/SWITCHED

The upper rear warning lights shall be controlled through the master warning switch and a secondary rear warning switch located on the dash panel. The switches shall be clearly labeled for ease of identification.

LOWER LED WARNING LIGHTING

The following NFPA lighting package, manufactured by Whelen, shall be supplied and installed in the lower areas of the vehicle.

LOWER ZONE B&D:

There shall be four (4) Whelen model 600 series Super-LED lights with chrome bezels, two (2) each side, provided and installed with the apparatus.

SIDE WARNING LIGHTS FLASH

The lower side lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors.

SIDE WARNING LIGHTS COLOR

The lower side warning lights mounted on the side positions shall be red with red lenses.

SIDE WARNING LIGHTS LOCATION

The warning lights on the side of the apparatus shall be mounted at the rear wheel panel location, centered above the rear axle, and in a housing below the rear tailboard location

LOWER ZONES B&D CAST ALUMINUM RECTANGLE LIGHT HOUSING

A cast aluminum rectangle light housing shall be used for the rearmost warning light in zones B&D to ensure the light is mounted as far rearward as possible below the rear compartment.

LOWER SIDE WARNING LIGHT SWITCH E-MASTER/SWITCHED

The lower side warning lights shall be controlled through the master warning switch and a secondary side warning switch located on the dash panel. The switches shall be clearly labeled for ease of identification.

LOWER ZONE C:

There shall be two (2) Whelen model 600 series Super-LED lights with chrome bezels, one (1) each side, provided and installed on the rear of the body.

REAR WARNING LIGHTS FLASH

The lower side lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors.

REAR WARNING LIGHTS COLOR

The lower rear warning lights mounted at the rear shall be red with red lenses.

LOWER REAR WARNING LIGHT SWITCH E-MASTER/SWITCHED

The lower rear warning lights shall be controlled through the master warning switch and a secondary rear warning switch located on the dash panel. The switches shall be clearly labeled for ease of identification.

LED REAR TAILLIGHT ASSEMBLY

There shall be Whelen model 600 series 4X6 LED rear taillight assemblies provided and installed with the apparatus, one (1) each side at the rear. The following shall be installed in the order as specified from top to bottom:

One (1) 604BTTC LED red brake/taillight

One (1) 604TC LED amber turn signal light populated in the shape of an arrow

One (1) 604BU LED clear back-up light

MOUNTING ASSEMBLY

There shall be Whelen 4-position vertical chrome plated housing provided for each taillight assembly. The upper most open cavity shall be filled with the specified warning light for the rear of the apparatus.

REAR TAILLIGHTS COLOR

The taillights mounted at the rear shall have clear lenses.

BACKUP LIGHTS

The backup lights shall illuminate when the apparatus is placed in reverse.

LED DOT LIGHTING

There shall be seven (7) lights located on the rear of the apparatus. Three (3) of the lights shall be mounted on the rear of the apparatus center location, for use as identification lamps. Two (2) additional lights shall be located on the rear outboard locations, one (1)

each side as high as possible. Two (2) lights shall be mounted on the sides facing the side at the rear corners, for use as clearance lamps.

The lights shall be TecNiq S17 series LED red markers with red lens.

DOT ADDITIONAL MARKER LIGHTS

There shall be two (2) amber LED intermediate marker lights/intermediate turn signals installed in the rub rail, forward of the rear wheel well, one (1) each side.

The lights shall be TecNiq S17 series LED amber markers/turn with amber lens.

INTERMEDIATE TURN SIGNALS

The intermediate turn signals will flash with the turn indicators.

REAR DIRECTIONAL LIGHTBAR

There shall be a directional lightbar shipped loose with the chassis to be installed on the apparatus.

DIRECTIONAL LIGHTBAR LOCATION & PROTECTION

The rear directional lightbar shall be installed as high as possible at the rear of the apparatus. A .125 inch embossed aluminum diamond plate light shield shall be installed directly above the rear directional light bar to protect the light bar from accidental damaged during hose loading and unloading operations. This light shield shall not be used as a stepping surface.

REAR VIEW CAMERA LOCATION

A camera shipped loose with the chassis shall be surface mounted at the center location on the rear of the apparatus body for maximum viewing capability. A protective shroud shall be installed over the system to protect against damage.

SIDE SCENE LIGHT LOCATION

There shall be two (2) scene lights installed on the side of the apparatus, one (1) on each side center location.

SCENE LIGHT MODEL

Whelen Pioneer series model #PFH1 LED flood scene lighting with white housing shall be semi-recess mounted on the apparatus.

Each lamp head shall have one (1) 12v Super-LED® panel at 75 watts total. The light head shall draw 6.5 amps and generate 12,000 lumens. Each LED panel shall be mounted within the semi-recess chrome trim bezel. Each lamp head shall be no more than 4.25 inches in height by 8.35 inches in width.

BODY SIDE SCENE LIGHT ACTIVATION

The scene lighting shall be activated by two (2) rocker switches installed on the switch panel in the cab and two (2) weather resistant push button switches at the pump operator's panel, one (1) for each side of the apparatus.

The switch shall be labeled as follows:

Left Scene

Right Scene

REAR SCENE LIGHT LOCATION

There shall be two (2) scene lights installed on the rear facing vertical surface of the apparatus, one (1) on each side.

SCENE LIGHT MODEL

Whelen Pioneer series model #PCH1 LED single combination flood/spot scene lighting with white housing shall be semi-recess mounted on the apparatus.

Each lamp head shall have one (1) 12v Super-LED® panel at 75 watts total. The light head shall draw 6.5 amps and generate 12,000 lumens. Each LED panel shall be mounted within the semi-recess chrome trim bezel. Each lamp head shall be no more than 4.25 inches in height by 8.35 inches in width.

REAR SCENE LIGHT ACTIVATION

The rear scene lighting shall be activated when the apparatus transmission is shifted into reverse and by a rocker switch located on the switch panel in the cab and a weather resistant push button switch at the pump operator's panel. The scene shall also be interlocked with the park brake. The switch shall be labeled as follows:Rear Scene

HARRISON HYDRAULIC 6,000 WATT GENERATOR

The generator shall be one (1) Harrison Hydraulic Driven Generator rated at 6,000 watts, 50/25 amps, 120/240VAC, 60Hz, 1-phase.

THIRD PARTY TESTING 110/220-VOLT & GENERATOR

The apparatus electrical and generator system shall be tested and certified by the third party testing company.

HARRISON HYDRAULICALLY DRIVEN GENERATOR (MAS FALCON)

The generator shall be designed and assembled by a company with no less than 20 years experience in the manufacture of hydraulic driven generators. The generator components shall be housed in a structural steel frame, which affords protection to the components and provides a unitized mounting module. The generator shall have top access to the oil filter, oil fill tube and electrical interface box. The hydraulic oil reservoir shall include an oil level sight gauge visible from three sides; an oil temperature gauge; an oil fill cap; an oil filter and an internal venturi boost unit to provide positive pressure to the pump suction port. The hydraulic oil reservoir shall be shipped attached to the structural steel frame. The hydraulic oil reservoir

shall have an option to be remote mounted if required. The generator shall have a cover consisting of embossed aluminum diamond plate. A meter package that provides the frequency, voltage and amperage of each leg shall be provided. The generator shall not utilize electronic controls or a multiplex system to control the frequency. The generator shall include a bypass solenoid to remotely turn the generator on/off with a 12 VDC signal. The generator shall be a commercial type with a heavy-duty bearing and of brushless design to ensure low maintenance. No brushes or slip rings shall be allowed. The generator and motor shall be close coupled and aligned using a Morse taper with a through bolt to secure the motor to the generator. No two (2) bearing generators shall be permitted. The system shall be capable of producing the full nameplate power when driven from the vehicle PTO from idle to maximum engine speed. The generator shall be able to be used while vehicle is either

stationary or in motion. The generator shall provide an option for a self-sealing air intake to prevent re circulation of exhaust air. The generator shall provide an option for a vertical exhaust fan in addition to the air intake fan. Single fan systems shall not be allowed. The generator shall provide a dedicated air intake duct for the alternator and a dedicated air intake duct for the heat exchanger. Both air intake ducts shall be located on the same side of the generator. The hydraulic motor and pump shall be of axial piston design to provide low internal leakage and a high degree of frequency stability. Gear motors shall not be allowed. The hydraulic pump shall match the system with the proper orifice, pressure compensator, and load sense settings to provide stable output regardless of engine rpm or electrical load demands. Use of electronics to control the flow shall not be allowed. The system shall be capable of normal operations using a commonly available premium hydraulic oil; Mobile DTE series or equivalent. All fluid service points shall be in close proximity to the reservoir for ease of scheduled maintenance. When properly installed, the system shall be warranted for a period of not less than two (2) years or 2000 hours, whichever should come first.

The generator shall be tested at the full nameplate rated load prior to shipping and the test report shall be included. The test report will document the generator's performance at various loads from no load to full load to ensure reliable power delivery at those loads.

GENERATOR LOCATION

The unit shall be located in the hose bed dunnage area near the front of the apparatus above the water tank.

HOT SHIFT PTO

The hydraulic generator shall be driven by a "hot shift" PTO installed on the chassis transmission. The PTO shall remain 'engaged' to keep fluid circulating through the system. A guarded switch, labeled "GENERATOR EMERGENCY STOP", shall be located on the cab dash or other operator accessible area in the cab. The switch shall be used to disconnect the PTO from the transmission in the event of hydraulic failure (broken hose, etc) during operation or while checking the transmission fluid level. A second switch with an indicator light shall be provided to excite the generator. The switch shall be labeled "GENERATOR EXCITE".

GENERATOR EXCITE

The generator excite application shall be activated by a rocker switch located on the cab dash or other operator accessible area in the cab.

GENERATOR DISPLAY

A FROG (Frequency Regulation of Generator) generator display kit shall be installed to monitor a 60 Hz, generator.

The kit shall include:

- Display module
- Voltage transformer.
- Current transformers and cables.

The display module shall consolidate five (5) generator monitoring instruments into one device. The display case shall be waterproof and have dimensions not to exceed 4.25 inches high by 4.25 inches wide by 3.25 inches deep.

The following continuous displays shall be provided with super bright LED digits more

than .50 inches high:

- Generator frequency in hertz
- Line 1 current in ampere
- Line 2 current in amperes
- Generator voltage in volts

The program shall support the accumulation of elapsed generator hours and the monitoring of hydraulic oil temperature. Generator hours and oil temperature shall be displayed at the push of a button. Audible warning alarm outputs are provided for generator overload, over/under voltage fluctuations, and high oil temperature.

GENERATOR DISPLAY LOCATION

The display shall be installed on the pump operator's gauge panel.

LOAD CENTER

An electrical load center shall be provided and installed in a protected environment on the apparatus. The load center shall have provisions for eight (8) manual reset type circuit breakers.

LOAD CENTER L1

The load center shall be surface mounted to the upper forward wall of the L1 compartment.

LINE VOLTAGE OUTLETS

NEMA 5-15 TWIST LOCK RECEPTACLE(S)

There shall be two (2) type NEMA L5-15 120V/15A twist lock single receptacle with a weather resistant cover installed in the below specified location(s).

RECEPTACLE LOCATION

Two (2) receptacles shall be located, one (1) each side, in the lower rearward portion of the body wheel well panels. The outlet(s) shall be powered by the on board AC generator and shall be live when the generator is in operation.

NEMA 5-20 DUPLEX RECEPTACLE(S)

There shall be four (4) type NEMA 5-20 120V/20A duplex receptacle with a cover installed in the below specified location(s).

RECEPTACLE LOCATION

The L1 body compartment shall be equipped with one (1) receptacle(s).

The outlet shall be located in the compartment, as outboard as practical on the middle portion of the forward wall.

The outlet(s) shall be powered by the shoreline connection or the on board AC generator. An automatic transfer switch shall provide power from the shoreline connection when the apparatus is housed at the station or from the generator when the generator is engaged/excited.

RECEPTACLE LOCATION

The L3 body compartment shall be equipped with one (1) receptacle(s).

The outlet shall be located in the compartment, as outboard as practical on the middle

portion of the forward wall.

The outlet(s) shall be powered by the shoreline connection or the on board AC generator. An automatic transfer switch shall provide power from the shoreline connection when the apparatus is housed at the station or from the generator when the generator is engaged/ excited.

RECEPTACLE LOCATION

The R1 body compartment shall be equipped with one (1) receptacle(s).

The outlet shall be located in the compartment, as outboard as practical on the middle portion of the forward wall.

The outlet(s) shall be powered by the shoreline connection or the on board AC generator. An automatic transfer switch shall provide power from the shoreline connection when the apparatus is housed at the station or from the generator when the generator is engaged/ excited.

RECEPTACLE LOCATION

The R3 body compartment shall be equipped with one (1) receptacle(s).

The outlet shall be located in the compartment, as outboard as practical on the middle portion of the forward wall.

The outlet(s) shall be powered by the shoreline connection or the on board AC generator. An automatic transfer switch shall provide power from the shoreline connection when the apparatus is housed at the station or from the generator when the generator is engaged/ excited.

CORD REEL

One (1) Hannay model #ECR series cord reel shall be installed on the apparatus as specified.

ELECTRICAL CORD

The reel shall come equipped with 150 feet of yellow 10-3 electrical cord. There shall be a cord stop supplied with the reel specified.

JUNCTION BOX

The cord shall be hardwired to a Circle D remote power distribution box with four (4) NEMA L5-15 single receptacles. The distribution box shall be stored in a mounting bracket when not in use. The box shall be equipped with a light to indicate when distribution box is energized.

The distribution box shall be equipped with the following receptacles:

Position 1: NEMA L5-15 R

Position 2: NEMA L5-15 R

Position 3: NEMA L5-15 R

Position 4: NEMA L5-15 R

REWIND ACTIVATION

A weather resistant push button switch to activate the reel rewind shall be located next to the reel specified. The switch shall be labeled "CORD REEL".

REEL LOCATION

One (1) reel is to be located in the left side upper storage UL-1 Upper Compartment.

The reel shall be placed in the rearward position of the above stated compartment.

ROLLER ASSEMBLY

There shall be a four (4) way fixed roller assembly provided and fastened to a plate in the lower compartment below the reel to guide the cord on and off the spool.

WILL-BURT 120 VOLT LED LIGHT TOWER

NIGHT SCAN CHIEF HORIZONTAL MOUNTED

A Will-Burt Night Scan Chief series light tower shall be provided. The horizontal surface mounted tower shall be raised electrically and pneumatically.

Design and Construction

The tower shall be a series of graduated extruded aluminum tubes that nest one inside another. The tower shall have an extended height of approximately 6.0 feet (1.8 m) above the mounting location and a stowed height of approximately 10.06 inches (25.6 cm) above the mounting surface. The tower shall be designed to sustain the intended top load with a 125 percent safety factor and shall exceed NFPA requirements of a minimum 50 mph (80 kph) wind when in a fully raised and un-guyed position. The tower shall be of a compact design with a total weight of 103 pounds (46.7 kg). The light tower shall not exceed 150 pounds (68 kg). The tower tubular sections shall be constructed of high strength, heat-treated 6061-T6 aluminum tubes, and collars. Each tube shall be protected by low friction synthetic collars for smooth operation and long life. Bumpers shall be designed to reduce shock on extension and retraction. All exterior surfaces shall be anodized for long life and fasteners shall be stainless steel for corrosion resistance.

Nesting System

The tower shall have an “auto-stow” function. A double click of the mast down button will stow, retract, and shut power off to the unit. An integrated saddle assembly with synthetic, non-marring rests shall be provided for the tower and light assembly in the nested position.

Floodlight Rotation and Tilt Operation

The tower shall be equipped with a Will-Burt Model RCP (remote control positioner) to control the rotation and direction of the light. The remote control positioner unit shall be equipped with two (2) gear motors; one for rotation and one for the floodlight bank. The positioner shall also rotate the floodlight assembly from zero to 355 degrees and tilt the floodlight assembly from 0 to 337 degrees.

Floodlight System

Four (4) Whelen Pioneer Plus™ Model # PFP2ASF shall be provided. The 150 watt +120v AC Pioneer light heads shall incorporate Super-LED® combination spot/flood light installed in a die-cast white powder coated aluminum housing. The PFP2ASF configuration shall consist of 33 white Super-LEDs in the spotlight left side with an eight degree TIR reflector, 33 white Super-LEDs for the flood light on the right side with a clear optic illuminator/reflector assembly and a clear non-optic polycarbonate lens. The Pioneer spot/flood light shall have 20,614 usable lumens for a total of 82,456 lumens. The fixture shall measure 4.13 inches (10.49 cm) high by 14.00 inches (25.56 cm) wide by 2.50 inches (6.35 cm) deep.

Warranty

The tower assembly shall carry a two (2) year parts and labor warranty. Exact provisions of such warranty shall be provided with the proposal and at time of delivery of product.

Labeling and NFPA Compliance

Essential operating instructions and warning labels shall be provided. Appropriate labels on the "hazards of electrocution" associated with the operation of a light tower shall be installed in the appropriate areas. A label shall be provided at the operator's position by the installer with the following information:

1. Extended height of the tower from the ground.
2. Bulb replacement data.

The tower and installation shall be in full compliance to applicable sections of the current NFPA 1901 Standard. The light tower shall be provided and installed on the top of the body/dunnage area. If required, a raised platform may be installed in the hosebed dunnage area.

The light tower shall be installed in the nested position with the light tree orientated towards the officer's side of the apparatus.

CONTROL KIT

One (1) NFPA compliant handheld remote controller kit shall be provided and installed on the apparatus.

Located on the forward wall of the L1 compartment.

3M REFLECTIVE STRIPING

There shall be a 4.00 inch (101.60 mm) high, 3M reflective stripe applied to the chassis and apparatus body as specified, The above specified Striping shall consist of one color.

The provided stripe shall be:
reflective stripe white in color.

STRIPE PATTERN

The reflective striping shall be applied around the perimeter of the apparatus in a straight line pattern.

REAR RETRO-REFLECTIVE CHEVRON STRIPING

A minimum of 50 percent of the rear-facing vertical surface, visible from the rear of the apparatus, shall be equipped with 3M Diamond Grade, retro-reflective striping in a chevron pattern, sloping downward and away from the centerline of the vehicle at an angle of 45-degrees. The stripe shall be 6.00 inches (152.40 mm) wide alternating in colors.

RETRO-REFLECTIVE STRIPING-SEVERE DUTY STEEL FRONT BUMPER

The vertical surfaces of the steel front bumper shall be equipped with 3M Diamond Grade, retro-reflective striping in a chevron pattern, sloping downward and away from the centerline of the bumper at an angle of 45-degrees. The stripe shall be 6.00 inch (152.40 mm) wide alternating in colors.

CHEVRON COLOR

The retro-reflective chevron striping shall be red and fluorescent yellow-green in color.

22K SIGN GOLD LETTERING

22k Sign Gold lettering with black shadowing and edging shall be provided and installed the apparatus body as directed by the Fire Department. A maximum total of sixty (60) letters up to 6.00 inches (152.4 mm) high shall be provided.\

LICENSE PLATE MOUNTING

A Cast Products, model LP0004-1-B, cast aluminum fully enclosed license plate bracket shall be installed. The bracket shall incorporate a clear LED light (WL0501) to illuminate the license plate and meet DOT requirements

LICENSE PLATE BRACKET LOCATION

The above specified license plate bracket shall be installed at the back of the apparatus on the left side. The bracket shall be mounted to meet all applicable DOT standards.

MISCELLANEOUS EQUIPMENT

The following equipment list shall be provided with the completed apparatus.

WHEEL CHOCKS

One (1) set of NFPA compliant Ziamatic folding wheel chocks model # SAC-44-E shall be supplied with the apparatus.

ZICO WHEEL CHOCK MOUNTING BRACKETS

One (1) set of Ziamatic folding wheel chock underbody horizontal mounts, model # SQCH-44-H, shall be installed on the apparatus under the body in front of the rear wheels on the left side. MOUNTING ALLOWANCE

Provide a tool mounting allowance of \$10,000.00 as part of the apparatus final price.

All other NFPA required equipment to be supplied by the Andover Fire Department

END OF SPECIFICATIONS

Specifications for the Andover Fire Department Rescue Pumper

**Bidder
Complies**

Yes No